

SHAPING THE FUTURE OF BOATING



THE CHOICE OF EXPERIENCED BOATERS

"Glastron's 1994 line of family runabouts continues to set the pace for the pleasure boat industry.

With new manufacturing techniques, advanced materials, and modular components, Glastron is building boats with more value than ever before.

Glastron's evolutionary changes truly are shaping the future of boating."



Russell "Rusty" Kelley
President

GLASTRON®
THE CHOICE OF EXPERIENCED BOATERS

GLASTRON HAS ELIMINATED OVER HALF OF THE WOOD FOUND IN CONVENTIONAL DESIGNS

Glastron has never been content to follow the crowd. Quite the opposite.

We have always been a company with an eye on the future. For over 36 years, Glastron has been recognized as a true innovator in family recreational boating.

The 1994 product line continues this great tradition for the next generation, as advanced manufacturing techniques, new materials, and modular components take their rightful place among earlier Glastron accomplishments.

Glastron is shaping the future of boating; building boats that are more energy efficient, more durable, and lighter-weight.

We have eliminated over half the wood found in conventional designs. By doing so, we've reduced performance-robbing weight, cut costly production time, and raised the comfort level of family boating.

Nowhere is the elimination of wood more critical than in the heart of the boat...the stringer system that reinforces the hull. Glastron has replaced ordinary wood stringers with foam-filled fiberglass stringers that are four times wider, thus giving direct support to a much larger hull area. This adds exceptional strength and rigidity, reduces weight, and eliminates the potential for wood rot.

From decade to decade, Glastron's dry-running

hulls have led the boating industry in responsiveness, tracking and maneuvering. Glastron's new SSV2 hull, backed by a five-year limited warranty, gets you up on plane more quickly and efficiently than previous designs, setting an even higher standard for others to follow.

In virtually every area, Glastron's aggressive research and development team has discovered ways to improve construction by utilizing durable synthetic materials and precast components. The result - a **BETTER BUILT BOAT**.

Advanced materials deliver improved performance, higher quality, and a substantial increase in value, while adding an increased dimension of versatility, safety, and styling.

Take the unique, one-piece contoured side panels, sculpted to accent the smooth interior styling, while adding the convenience of molded-in storage compartments and drink holders.

Or Glastron's sport bucket seats, vacuum-formed to provide gently contoured lumbar support. With no wood, they are not susceptible to water penetration.

Likewise, sleeper seat bases are built of durable components designed to be more resistant to weather and wear.

The modularly constructed instrument panel combines the practicality of easy readability with styling that blends effortlessly with the rest of the cockpit.

From the convenient, precast drawer units in the bow, to the sound-absorbing engine cover, Glastron engineers have harnessed new technology and materials to create quality features that are engineered in, not added on.

At Glastron, we're changing the way you think about boating...by building boats not just for today, but for tomorrow.

FEATURES AND BENEFITS

Before you sell a Glastron –
make sure your customer
knows these facts.

FACTS:

36 years in the marine industry

Purchasing Power – owned by Genmar, the
largest independent boat builder

Performance by Design – winner of 9 awards
in 12 years for top boat performance

* One of the top three most recognized names
in the industry

* Largest percentage of repeat customers

* Glastron owners use their boats on average
more than owners of other brands

* Glastron owners on average have boated
longer than owners of other brands

* Glastron owners consider boat handling and
performance as the #1 reason to buy a
Glastron

* Glastron dealers have been in business
longer on average than dealers of other
brands – with better service and high resale

* Glastron dealer reputation is considered
higher than other brand dealers surveyed.

** From an independent marine market survey conducted by
Irwin Broh and Associates, Inc.*

Before your customer makes a choice –
shouldn't he compare
these features and benefits?

FEATURES:

1. Solid foam core construction
2. Fiberglass stringer system
3. Stringer system is bonded to hull with fiberglass
4. Hull and deck joined with stainless steel screws, not pop rivets
5. Fiberglass molded bow liner bolted to floor
6. Keel areas are overlapped with fiberglass
7. Floor is resin-coated, top to bottom
8. All exposed wood treated with wood life preservative

BENEFITS:

Consistent overall strength without excessive weight for better performance

Strength, no wood to rot, foam filled. 4 times wider than ordinary wood stringers

Rigid stringer system for strength

Better seal; much stronger boat overall

Eliminates wood rot problem; better appearance; stronger

Double strength in this all-important area

Protects against wood rot

Longer life; eliminates wood rot

FEATURES:

9. All deck fittings are backed by under-deck supports glassed into the deck

10. Motor mounts are fiberglass encapsulated to the hull

11. Aircraft locknuts on bolts

12. Marine-grade carpet - one piece lock looped

13. 32-ounce marine-grade vinyl

14. Carpeted storage areas

15. Carpeted ski locker with drain in sub-floor

16. Rotocast nylon seat bases

17. Custom-molded side panels

18. Bow storage drawers available on certain models

19. All models feature automotive-style instrument panel

BENEFITS:

Strength; durability

Strength; reduces engine vibration

Strength; long term durability

Appearance; no seams

UV protected; marine-grade stitching

Appearance; padding for boating gear

Protects the ski; lets water drain away from the stringer system

Eliminates wood; longer life

Lightweight, convenient storage, with no wood to rot

Roto-molded, one-piece construction for longer life

Easy-to-read gauges, convenient controls, improved styling

FEATURES:

20. Built-in swim platform w/stainless steel boarding ladder below platform

21. 36 hours of offshore endurance testing on all new models

22. Each new model is carefully designed for the proper weight to horsepower ratio

23. Five-year hull warranty

24. Choice of MerCruiser or Volvo Power

BENEFITS:

Ease of boarding; lower platform than most competition

Test all component parts plus hull and deck strength before putting new models on market. Very few competitors go to this expense

Complete design concentration on performance; better planing time; better fuel economy

Glastron backs its products

Better choices for each type of boat use

There are many more facts and features that have allowed Glastron to be recognized as an industry leader in innovation and safety. Make sure your customers know why Glastron is...

THE CHOICE OF EXPERIENCED BOATERS

GLASTRON LIMITED WARRANTY

Glastron Boats, a Division of Genmar Industries, Inc. ("Manufacturer") warrants to the first retail purchaser (buyer) of the products it manufactures, under the name Glastron Boats, which are purchased from a factory authorized dealer, that should the hull be proven to be structurally defective in material or workmanship under normal operating conditions: Manufacturer will make the structural repairs (or, at its sole discretion, replace the affected part) necessitated thereby for a period of five (5) years from the date the product was purchased by the first retail purchaser. Manufacturer also warrants to the first retail purchaser to repair (or replace at its sole discretion) non-structural defects in material and workmanship under normal operating conditions subject to the exclusions set forth below for a period of one (1) year. This limited warranty is subject to the following terms and conditions.

If not demanded already, Manufacturer demands that the buyer examine the product to discover any defects in material or workmanship and notify Manufacturer or the selling dealer of same. During the warranty period, warranty repairs will be made without charge by the selling dealer, at the dealer's store or service facility or, at Manufacturer's election, by Manufacturer at its factory. Transportation to and from a Dealership or to Manufacturer's factory shall be at buyer's expense. Manufacturer's election to repair the defective product or replace the defective part is the exclusive remedy of the buyer and is a condition precedent to any legal or equitable action against Manufacturer. Any action for breach of warranty relating to a product must be brought within a period of sixty (60) days following Manufacturer's failure to repair the product or replace the defective part.

WHAT IS NOT COVERED:

This Warranty does not cover:

1. A product which has been repaired or altered without authorization of Manufacturer by persons other than Manufacturer or an authorized Dealer or altered in any way so as to affect its use and operation;
2. Engines, outdrives, controls, propellers, batteries or other equipment or accessories which are not manufactured by Manufacturer whether or not warranted by such other manufacturers;
3. Gelcoat finishes, cracking, crazing, blistering including osmotic blistering;
4. Windshield breakage;
5. Leakage around windshields, hatches or other apertures;
6. A product which has been subjected to unreasonable use, tampering, abuse, mishandling, improper maintenance, negligence, improper trailer, alteration, accident, or used for racing or commercial purposes, or which has been operated contrary to any printed instructions furnished by Manufacturer;
7. A product which has been overpowered according to

8. the maximum recommended engine horsepower specified on the capacity plate affixed thereto;
9. Any representations relating to the speed of a product or weight;
10. Loss of time, inconvenience, travel expense, loss of use, haul out, launch, towing, storage charges or other matters not specifically covered hereunder;
11. Dealer preparation, cleaning and final adjustments and alignments in preparing boat for delivery or commissioning;
12. Any act of God.

This warranty gives you specific rights, and you may also have other rights which vary from state to state. This warranty is governed by the law of the State of Minnesota. This document contains the entire warranty given by Manufacturer and there are no terms, promises, conditions or warranties other than those contained herein. No oral or written information or advice given by Manufacturer, its dealers, representatives, agents or employees shall create a warranty or in any way increase the scope of this warranty. Manufacturer does not authorize any person to extend the time of this warranty or to create or assume for it any other obligation or liability with respect to its products. No person, including a dealer, is authorized to make any repairs or replacements under this warranty without the prior written approval of Manufacturer. Manufacturer reserves the right to improve its products through changes in design, material or parts without being obligated to incorporate such changes in products previously manufactured. This warranty is not transferable or assignable.

THIS EXPRESS WARRANTY IS IN LIEU OF, AND MANUFACTURER DISCLAIMS, ANY AND ALL OTHER WARRANTIES, EXPRESSED, IMPLIED OR STATUTORY, WHATSOEVER INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES UNDER THE UNIFORM COMMERCIAL CODE, ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, THIS WARRANTY SHALL BE THE SOLE AND EXCLUSIVE REMEDY OF ANY PERSON WHETHER IN CONTRACT, TORT OR OTHERWISE AND MANUFACTURER SHALL NOT BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INCIDENTAL DAMAGE, LOST PROFITS, INCONVENIENCE, OR DAMAGE RESULTING FROM A BREACH OF THE EXPRESSED OR ANY IMPLIED WARRANTY WHICH IS NOT DISCLAIMED HEREIN NOR ANY OTHER LOSS OR DAMAGE, EXCEPT AS SET FORTH ABOVE.

In the event that the disclaimer and exclusion of warranties and damages are inconsistent with applicable law, those disclaimers and exclusions are limited to the maximum permitted by applicable law, and all remaining implied obligations and warranties are limited in duration to a period of one (1) year or such shorter period as permitted by applicable law.

Some states do not allow limitations on implied warranties, or the exclusion or limitation of incidental or consequential damages, so the limitations or exclusions may not apply to you.

DEFINITIONS OF BOAT MEASUREMENTS

Length Overall (LOA) – Distance along the centerline from the tip of the bow to the aft-most part of the hull.

Maximum Beam – Maximum width of the boat.

Transom Width – Maximum width of the boat at transom.

Depth – Vertical distance from lowest point of the keel to the highest point of the boat, excluding windshields, lights and other removable components.

Transom – Vertical distance at boat's centerline from the keel/transom intersection to the transom top.

Maximum Depth – Vertical distance from lowest point of the keel to the highest point of boat, including windshields.

Cockpit Depth – Vertical distance from boat floor to top of gunwale as measured at the driver seat.

Length Overall on Trailer – Distance measured along the boat centerline, from forward-most point of trailer to aft-most point of motor/outdrive.

Boat Height on Trailer – Vertical distance from ground to highest point of boat, including windshield.

Draft (Drive unit up) – Total number of inches of boat and/or motor and drive unit below the water-line. Measured unloaded, with the motor/drive unit in the full up position.

Draft (Drive unit down) – Total number of inches of boat and/or motor and drive unit below the waterline. Measured unloaded, with the motor/drive unit in the full down position.

1994 GLASTRON MODEL LINE-UP

SPECIAL EDITION SERIES

SSV 170 SE
SSV 175 SE
SSV 177 SE
SSV 195 SE
SSV 197 SE
SSV 215 SE

OUTBOARD SERIES

SSV 170
SSV 190

ELITE SERIES

SSV 175 ELITE
SSV 177 ELITE
SSV 195 ELITE
SSV 197 ELITE
SSV 215 ELITE

CUDDY CABIN SERIES

SSV 199
SSV 219

SKI & FISH SERIES

SSV 170 SKI & FISH
SSV 175 SKI & FISH
SSV 190 SKI & FISH
SSV 195 SKI & FISH

MODEL DESIGNATOR CODE

0 - Outboard Model
5 - Open Bow Sterndrive Model
7 - Closed Bow Sterndrive Model
9 - Cuddy Cabin Sterndrive Model

SSV 175 SE

SPECIFICATIONS

| | |
|---|---------------------------------------|
| LOA 17' 1" (5.21 m.) | Transom Width 73 1/4" (1.86 m.) |
| Beam 88" (2.24 m.) | Transom Deadrise 21° |
| Depth 43" (1.09 m.) | LOA on Trailer 21' 6" (6.55 m.) |
| Maximum Depth 59" (1.5 m.) | Fuel Capacity 20 gal. (75.7 L.) |
| Cockpit Depth 28 1/2" (.72 m.) | Maximum Load 1250 lbs. (567 kg.) |
| Approx. Wt. w/3.0 GL Volvo Penta 1650 lbs. (747 kg.) | Max. Persons 8 or 1150 lbs. (522 kg.) |
| | NMMA Certified |
| Draft: A. Drive Unit Up 16" (.41 m.) | |
| B. Drive Unit Down 31" (.79 m.) | |

STANDARD FEATURES

| | |
|---|---|
| Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | Stainless steel bow eye and stern eyes |
| Concealed electric horn | 6" cleats |
| Bilge pump and blower | Walk-thru curved glass windshield |
| Navigation lighting | Wraparound bow seats |
| AM/FM stereo cassette with 2 speakers | Bow storage drawers |
| Glove box | Anchor locker |
| Ski locker | Passenger grab handle |
| Ski tow ring | Fold-out sleeper seats with ait jump seats |
| | Side panels with storage |
| | Molded swim platform |
| | Stainless steel boarding ladder |
| | Soft top with concealed storage |

OPTIONS

| | |
|---|-----------------------------|
| Custom ShoreLand'r bunk trailer (V1723) | Mooring cover |
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Cockpit cover/tonneau cover |
| | Full glass windshield |
| | High altitude prop |

ENGINE OPTIONS

| | |
|-------------------------|--------------------|
| 3.0LX MerCruiser (WOPS) | 3.0 GL Volvo Penta |
|-------------------------|--------------------|

STANDARD COLOR

Teal/White

SSV 175 SE

PERFORMANCE DATA

| ENGINE 3.0LX MERCUISER - PROP 13 3/4 X 21 AL | | | |
|--|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2100 | 15 | 2.5 | 102 |
| 2900 | 25 | 3.5 | 121 |
| 3500 | 35 | 7.4 | 80 |
| WOT | 42-45 | - | - |
| 0-20 MPH Acceleration - 3.4 sec. | | | |

| ENGINE 3.0 GL VOLVO PENTA - PROP 15 X 17 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2000 | 10 | 2.1 | 81 |
| 3000 | 20 | 3.2 | 106 |
| 4000 | 35 | 7.6 | 78 |
| WOT | 38-41 | - | - |
| 0-20 MPH Acceleration - 3.7 sec. | | | |

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

| | | |
|------------------|----|-------|
| Boat | \$ | _____ |
| Motor _____ H.P. | | _____ |
| Trailer | | _____ |
| Accessories | | _____ |
| T,T & L | | _____ |
| TOTAL PRICE \$ | | _____ |

NOTES

SSV 177 SE

SPECIFICATIONS

| | |
|---|---------------------------------------|
| LOA 17' 1" (5.21 m.) | Transom Width 73 1/4" (1.86 m.) |
| Beam 88" (2.24 m.) | Transom Deadrise 21° |
| Depth 43" (1.09 m.) | LOA on Trailer 21' 6" (6.55 m.) |
| Maximum Depth 59" (1.5 m.) | Fuel Capacity 20 gal. (75.7 L.) |
| Cockpit Depth 28 1/2" (.72 m.) | Maximum Load 1250 lbs. (567 kg.) |
| Approx. Wt. w/3.0 GL Volvo Penta 1650 lbs. (747 kg.) | Max. Persons 8 or 1150 lbs. (522 kg.) |
| | NMMA Certified |
| Draft: | A. Drive Unit Up 16" (.41 m.) |
| | B. Drive Unit Down 31" (.79 m.) |

STANDARD FEATURES

| | |
|---|---|
| Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | Stainless steel bow eye and stern eyes |
| Concealed electric horn | 6" cleats |
| Bilge pump and blower | Walk-thru curved glass windshield |
| Navigation lighting | Bow access step |
| AM/FM stereo cassette with 2 speakers | Stainless steel bow rails |
| Glove box | Anchor locker |
| Ski locker | Passenger grab handle |
| Ski tow ring | Adjustable bucket/bench seating |
| | Side panels with storage |
| | Molded swim platform |
| | Stainless steel boarding ladder |
| | Soft top with concealed storage |

OPTIONS

| | |
|--|------------------------------------|
| Custom ShoreLand'r bunk trailer (V1723) | Cockpit cover |
| Canvas package: side curtains, stern curtain, soft top boot | Full glass windshield |
| Mooring cover | High altitude prop |
| | Stainless steel stern rail package |
| | Bow pad |

ENGINE OPTIONS

| | |
|-------------------------|--------------------|
| 3.0LX MerCruiser (WOPS) | 3.0 GL Volvo Penta |
|-------------------------|--------------------|

STANDARD COLOR

Teal/White

SSV 177 SE

PERFORMANCE DATA

| ENGINE 3.0LX MERCURISER - PROP 13 3/4 X 21 AL | | | RANGE* |
|---|-------|-----|--------|
| RPM | MPH | GPH | |
| 2100 | 15 | 2.5 | 102 |
| 2900 | 25 | 3.5 | 121 |
| 3500 | 35 | 7.4 | 80 |
| WOT | 42-45 | - | - |
| 0-20 MPH Acceleration - 3.4 sec. | | | |

| ENGINE 3.0 GL VOLVO PENTA - PROP 15 X 17 AL | | | RANGE* |
|---|-------|-----|--------|
| RPM | MPH | GPH | |
| 2000 | 10 | 2.1 | 81 |
| 3000 | 20 | 3.2 | 106 |
| 4000 | 35 | 7.6 | 78 |
| WOT | 38-41 | - | - |
| 0-20 MPH Acceleration - 3.7 sec. | | | |

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

| | |
|-----------------------|--------------|
| Boat | \$ _____ |
| Motor _____ H.P. | _____ |
| Trailer | _____ |
| Accessories | _____ |
| T, T & L | _____ |
| TOTAL PRICE \$ | _____ |

NOTES

SSV 195 SE

SPECIFICATIONS

| | |
|---|---|
| LOA 18' 7" (5.66 m.) | Transom Width 75" (1.9 m.) |
| Beam 90 3/4" (2.31 m.) | Transom Deadrise 21° |
| Depth 47" (1.19 m.) | LOA on Trailer 22' (6.71 m.) |
| Maximum Depth 63" (1.6 m.) | Fuel Capacity 35 gal. (132.5 L.) |
| Cockpit Depth 28 3/4" (.73 m.) | Maximum Load 1500 lbs. (681 kg.) |
| Approx. Wt. w/4.3 GL Volvo Penta 1990 lbs. (903 kg.) | Max. Persons 8 or 1150 lbs. (522 kg.) NMMA Certified |
| Draft: | A. Drive Unit Up 16 1/2" (.42 m.) |
| | B. Drive Unit Down 31 1/2" (.8 m.) |

STANDARD FEATURES

| | |
|---|---|
| Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | Stainless steel bow eye and stern eyes 6" cleats Walk-thru curved glass windshield Wraparound bow seats Bow storage drawers Anchor locker Passenger grab handle Fold-out sleeper seats with aft jump seats Side panels with storage Molded swim platform Stainless steel boarding ladder Soft top with concealed storage |
| Concealed electric horn | |
| Bilge pump and blower | |
| Navigation lighting | |
| AM/FM stereo cassette with 2 speakers | |
| Glove box | |
| Ski locker | |
| Ski tow ring | |

OPTIONS

| | |
|---|--|
| Custom ShoreLand'r bunk trailer (V1928) | Mooring cover |
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Cockpit cover/tonneau cover Full glass windshield High altitude prop |

ENGINE OPTIONS

| | |
|------------------|--------------------|
| 4.3LX MerCruiser | 4.3 GL Volvo Penta |
|------------------|--------------------|

STANDARD COLOR

Teal/White

SSV 195 SE

PERFORMANCE DATA

ENGINE 4.3LX MERCURISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 3.0 | 160 |
| 3200 | 25 | 4.0 | 202 |
| 3700 | 35 | 7.9 | 141 |
| WOT | 47-49 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 4.3 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 10 | 2.8 | 107 |
| 3000 | 25 | 3.6 | 208 |
| 4000 | 35 | 6.6 | 159 |
| WOT | 43-45 | - | - |

0-20 MPH Acceleration - 2.9 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

**RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.*

SALE PRICE

| | | |
|--------------------|-----------|-------|
| Boat | \$ | _____ |
| Motor _____ H.P. | | _____ |
| Trailer | | _____ |
| Accessories | | _____ |
| T, T & L | | _____ |
| TOTAL PRICE | \$ | _____ |

NOTES

SSV 197 SE

SPECIFICATIONS

LOA 18' 7" (5.66 m.)
 Beam 90 3/4" (2.31 m.)
 Depth 47" (1.19 m.)
 Maximum Depth 63" (1.6 m.)
 Cockpit Depth 28 3/4" (.73 m.)
 Wt. w/4.3 GL Volvo Penta
 Appx. 1990 lbs. (903 kg.)

Transom Width 75" (1.9 m.)
 Transom Deadrise 21°
 LOA on Trailer 22' (6.71 m.)
 Fuel Capacity 35 gal. (132.5 L.)
 Maximum Load 1500 lbs. (681 kg.)
 Max. Persons 8 or 1150 lbs. (522 kg.)
 NMMA Certified

Draft: A. Drive Unit Up 16 1/2" (.42 m.)
 B. Drive Unit Down 31 1/2" (.8 m.)

STANDARD FEATURES

Instrument panel includes:
 speedometer, tachometer, trim,
 fuel, oil pressure, voltmeter and
 engine temperature gauges; plus
 switches for bilge pump, blower,
 horn, lights, and accessories

Concealed electric horn
 Bilge pump and blower
 Navigation lighting
 AM/FM stereo cassette
 with 2 speakers
 Glove box
 Ski locker
 Ski tow ring

Stainless steel bow eye
 and stern eyes
 6" cleats
 Walk-thru curved glass windshield
 Bow access step
 Stainless steel bow rails
 Anchor locker
 Passenger grab handle
 Adjustable bucket/bench seating
 Side panels with storage
 Molded swim platform
 Stainless steel boarding ladder
 Soft top with concealed storage

OPTIONS

Custom ShoreLand'r
 bunk trailer (V1928)
 Canvas package: side curtains,
 stern curtain, soft top boot
 Mooring cover

Cockpit cover
 Full glass windshield
 High altitude prop
 Stainless steel stern rail package
 Bow pad

ENGINE OPTIONS

4.3LX MerCruiser
 4.3 GL Volvo Penta

STANDARD COLOR

Teal/White

SSV 197 SE

PERFORMANCE DATA

ENGINE 4.3LX MERCURISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 3.0 | 160 |
| 3200 | 25 | 4.0 | 202 |
| 3700 | 35 | 7.9 | 141 |
| WOT | 47-49 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 4.3 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 10 | 2.8 | 107 |
| 3000 | 25 | 3.6 | 208 |
| 4000 | 35 | 6.6 | 159 |
| WOT | 43-45 | - | - |

0-20 MPH Acceleration - 2.9 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____
 Motor _____ H.P. _____
 Trailer _____
 Accessories _____
 T,T & L _____
 TOTAL PRICE \$ _____

NOTES

SSV 215 SE

SPECIFICATIONS

| | |
|--|---------------------------------------|
| LOA 21' 2" (6.45 m.) | Transom Width 92" (2.34 m.) |
| Beam 97" (2.45 m.) | Transom Deadrise 19° |
| Depth 51" (1.29 m.) | LOA on Trailer 24' 8" (7.51 m.) |
| Maximum Depth 61" (1.54 m.) | Fuel Capacity 45 gal. (170.3 L.) |
| Cockpit Depth 31" (.77 m.) | Maximum Load 1600 lbs. (726 kg.) |
| Approx. Wt. w/5.0 FL Volvo Penta 2755 lbs. (1251 kg.) | Max. Persons 9 or 1300 lbs. (590 kg.) |
| | NMMA Certified |
| Draft: A. Drive Unit Up 17 1/2" (.44 m.) | |
| B. Drive Unit Down 32" (.81 m.) | |

STANDARD FEATURES

| | |
|--|--|
| Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, panel lights, interior lights, and horn | Stainless steel ski tow ring Stainless steel bow eye and stern eyes 6" cleats Walk-thru curved glass windshield Wraparound bow seats Bow storage drawers Anchor locker Passenger grab handle Fold-out sleeper seats with aft jump seats Custom side panels with storage Molded swim platform Stainless steel boarding ladder Soft top with concealed storage |
| Concealed electric horn Cockpit courtesy lights Bilge pump and blower Navigation lighting AM/FM stereo cassette with 2 speakers Lockable glove box Ski locker | |

OPTIONS

| | |
|---|--|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Cockpit cover/tonneau cover Full glass windshield High altitude prop |
| Mooring cover | |

ENGINE OPTIONS

| | |
|------------------|--------------------|
| 5.0LX MerCruiser | 5.0 FL Volvo Penta |
|------------------|--------------------|

STANDARD COLOR

Teal/White

SSV 215 SE

PERFORMANCE DATA

| ENGINE 5.0LX MERCUISER - PROP 14 X 19 AL | | | |
|--|-------|------|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 30 | 9.1 | 125 |
| 3500 | 40 | 12.3 | 123 |
| 4000 | 45 | 17.6 | 97 |
| WOT | 49-51 | - | - |
| 0-20 MPH Acceleration - 3.3 sec. | | | |

| ENGINE 5.0 FL VOLVO PENTA - PROP 14 1/2 X 19 AL | | | |
|---|-------|------|--------|
| RPM | MPH | GPH | RANGE* |
| 2000 | 20 | 7.2 | 106 |
| 3000 | 30 | 8.6 | 133 |
| 4000 | 40 | 15.7 | 97 |
| WOT | 48-50 | - | - |
| 0-20 MPH Acceleration - 3.3 sec. | | | |

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

| | |
|-----------------------|--------------|
| Boat | \$ _____ |
| Motor _____ H.P. | _____ |
| Trailer | _____ |
| Accessories | _____ |
| T, T & L | _____ |
| TOTAL PRICE \$ | _____ |

NOTES

SSV 170

SPECIFICATIONS

| | |
|--|---------------------------------------|
| LOA 17' 1" (5.21 m.) | Transom Deadrise 21° |
| Beam 88" (2.24 m.) | LOA on Trailer 21' 6" (6.55 m.) |
| Depth 43" (1.09 m.) | Fuel Capacity 20 gal. (75.7 L.) |
| Maximum Depth 59" (1.5 m.) | Maximum Load 1800 lbs. (817 kg.) |
| Cockpit Depth 28 1/2" (.72 m.) | Max. Persons 8 or 1150 lbs. (522 kg.) |
| Approx. Wt. 1125 lbs. (511 kg.) | Maximum Horsepower 150 |
| Transom Width 73 1/4" (1.86 m.) | NMMA Certified |
| Draft: A. Drive Unit Up 15 1/2" (.39 m.) | |
| B. Drive Unit Down 28 1/2" (.72 m.) | |

STANDARD FEATURES

| | |
|---|---|
| Instrument panel includes: speedometer, tachometer, and fuel gauges; plus switches for bilge pump, navigation/anchor lights, panel lights, horn, and accessories | Stainless steel bow eye and stern eyes |
| Concealed electric horn | 6" cleats |
| Cockpit courtesy lights | Walk-thru curved glass windshield |
| Bilge pump | Wraparound bow seats |
| Navigation lighting | Bow storage drawers |
| AM/FM stereo cassette with 2 speakers | Anchor locker |
| Glove box | Passenger grab handle |
| Ski locker | Adjustable bucket/bench seating |
| | Custom side panels with storage |
| | Molded swim platform |
| | Stainless steel boarding ladder |
| | Soft top with concealed storage |
| | Hull and deck gelcoat accent stripes |

OPTIONS

| | |
|---|---|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Full glass windshield |
| Mooring cover | Ski tow pylon |
| Cockpit cover/tonneau cover | OMC Pre-Rig includes: ignition switch with ignition interrupt switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls, pre-drilled transom |
| Convenience package: depthsounder, compass, hour meter | |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 170

PERFORMANCE DATA

ENGINE 90 EVINRUDE - PROP 13 1/4 X 17

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2500 | 15 | 2.9 | 88 |
| 3400 | 25 | 4.2 | 102 |
| 4600 | 35 | 6.3 | 95 |
| WOT | 38-40 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 115 EVINRUDE - PROP 12 3/4 X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2500 | 15 | 3.6 | 71 |
| 3300 | 25 | 4.6 | 92 |
| 4700 | 35 | 7.2 | 83 |
| WOT | 42-44 | - | - |

0-20 MPH Acceleration - 3.2 sec.

ENGINE 135 MERCURY (V6) - PROP 13 7/8 X 21 S/S LASER

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 4.2 | 71 |
| 3000 | 25 | 5.1 | 87 |
| 4000 | 35 | 7.1 | 87 |
| WOT | 45-48 | - | - |

0-20 MPH Acceleration - 3.1 sec.

ENGINE 140 JOHNSON - PROP 14 1/4 X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2100 | 15 | 3.5 | 73 |
| 3300 | 25 | 4.4 | 97 |
| 4000 | 35 | 6.9 | 87 |
| WOT | 46-48 | - | - |

0-20 MPH Acceleration - 3.2 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

| | |
|-----------------------|--------------|
| Boat | \$ _____ |
| Motor _____ H.P. | _____ |
| Trailer | _____ |
| Accessories | _____ |
| T, T & L | _____ |
| TOTAL PRICE \$ | _____ |

SSV 190

SPECIFICATIONS

LOA 18' 7" (5.66 m.)
 Beam 90 3/4" (2.31 m.)
 Depth 47" (1.19 m.)
 Maximum Depth 63" (1.6 m.)
 Cockpit Depth 28 3/4" (.73 m.)
 Approx. Wt. 1200 lbs. (545 kg.)
 Transom Width 75" (1.9 m.)
 Draft: A. Drive Unit Up 16" (.41 m.)
 B. Drive Unit Down 29" (.74 m.)

Transom Deadrise 21°
 LOA on Trailer 22' (6.71 m.)
 Fuel Capacity 35 gal. (132.5 L.)
 Maximum Load 1900 lbs. (863 kg.)
 Max. Persons 8 or 1150 lbs. (522 kg.)
 Maximum Horsepower 175
 NMMA Certified

STANDARD FEATURES

Instrument panel includes:
 speedometer, tachometer, and
 fuel gauges; plus switches for
 bilge pump, navigation/anchor
 lights, panel lights, horn, and
 accessories

Concealed electric horn
 Cockpit courtesy lights
 Bilge pump
 Navigation lighting
 AM/FM stereo cassette
 with 2 speakers
 Glove box
 Ski locker

Stainless steel bow eye
 and stern eyes
 6" cleats
 Walk-thru curved glass windshield
 Wraparound bow seats
 Bow storage drawers
 Anchor locker
 Passenger grab handle
 Adjustable bucket/bench seating
 Custom side panels with storage
 Molded swim platform
 Stainless steel boarding ladder
 Soft top with concealed storage
 Hull and deck gelcoat accent stripes

OPTIONS

Canvas package: tonneau cover,
 walk-thru curtain, side curtains,
 stern curtain, soft top boot

Mooring cover
 Cockpit cover/tonneau cover
 Convenience package:
 depthsounder, compass,
 hour meter

Full glass windshield
 Ski tow pylon
 OMC Pre-Rig includes: ignition
 switch with ignition interrupt
 switch, speedometer,
 tachometer, trim gauge, fuel
 gauge, voltmeter, manufacturer
 controls, pre-drilled transom

COLOR OPTIONS

Blue/White
 Red/White
 Teal/White

SSV 190

PERFORMANCE DATA

ENGINE 90 EVINRUDE - PROP 13 1/4 X 17

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2700 | 15 | 3.0 | 160 |
| 3500 | 25 | 4.4 | 182 |
| 4800 | 35 | 6.5 | 173 |
| WOT | 37-39 | - | - |

0-20 MPH Acceleration - 3.4 sec.

ENGINE 115 EVINRUDE - PROP 12 3/4 X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2600 | 15 | 3.7 | 131 |
| 3400 | 25 | 4.8 | 166 |
| 4700 | 35 | 7.2 | 157 |
| WOT | 42-44 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 135 MERCURY (V6) - PROP 13 7/8 X 21 S/S LASER

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2500 | 15 | 4.4 | 109 |
| 3100 | 25 | 5.3 | 150 |
| 4200 | 35 | 7.5 | 147 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 3.2 sec.

ENGINE 150 JOHNSON - PROP 14 1/4 X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 4.5 | 106 |
| 3000 | 25 | 5.5 | 144 |
| 3900 | 35 | 7.8 | 141 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 3.1 sec.

*NOTE: Performance results will vary depending on load, altitude, and other conditions.
 RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____

Motor _____ H.P. _____

Trailer _____

Accessories _____

T, T & L _____

TOTAL PRICE \$ _____

SSV 175 ELITE

SPECIFICATIONS

| | |
|---|---|
| LOA 17' 1" (5.21 m.) | Transom Width 73 1/4" (1.86 m.) |
| Beam 88" (2.24 m.) | Transom Deadrise 21° |
| Depth 43" (1.09 m.) | LOA on Trailer 21' 6" (6.55 m.) |
| Maximum Depth 59" (1.5 m.) | Fuel Capacity 20 gal. (75.7 L.) |
| Cockpit Depth 28 1/2" (.72 m.) | Maximum Load 1250 lbs. (567 kg.) |
| Approx. Wt. w/3.0LX MerCruiser 1750 lbs. (794 kg.) | Max. Persons 8 or 1150 lbs. (522 kg.) NMMA Certified |
| Draft: A. Drive Unit Up 16" (.41 m.) B. Drive Unit Down 31" (.79 m.) | |

STANDARD FEATURES

| | |
|--|--|
| Padded instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | 6" cleats Walk-thru curved full glass windshield Wraparound bow seats Bow storage drawers Anchor locker Passenger grab handle Adjustable fold-out sleeper seats with aft jump seats Molded sleeper seat bases Custom side panels with storage Molded swim platform Stainless steel boarding ladder Soft top with concealed storage Hull and deck gelcoat accent stripes MerC/Volvo controls |
| Concealed electric horn Cockpit courtesy lights Bilge pump and blower Navigation lighting AM/FM stereo cassette with 2 speakers Glove box Ski locker Ski tow ring Stainless steel bow eye and stern eyes | |

OPTIONS

| | |
|--|--|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | High altitude prop Stainless steel prop (MerC only) Adjustable bucket/bench seating Adjustable bucket/sleeper seating |
| Mooring cover Cockpit cover/tonneau cover Convenience package: depthsounder, compass, hour meter | |

ENGINE OPTIONS

| | |
|-------------------------|--------------------|
| 3.0LX MerCruiser (WOPS) | 3.0 GL Volvo Penta |
| 3.0LX MerCruiser (WPS) | 3.0 GS Volvo Penta |
| 4.3 MerCruiser | 4.3 GL Volvo Penta |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 175 ELITE

PERFORMANCE DATA

ENGINE 3.0LX MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2100 | 15 | 2.5 | 102 |
| 2900 | 25 | 3.5 | 121 |
| 3500 | 35 | 7.4 | 80 |
| WOT | 42-45 | - | - |

0-20 MPH Acceleration - 3.4 sec.

ENGINE 4.3 MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2200 | 15 | 2.6 | 99 |
| 2900 | 25 | 3.8 | 112 |
| 3400 | 35 | 7.4 | 80 |
| WOT | 48-51 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 3.0 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 10 | 2.1 | 81 |
| 3000 | 20 | 3.2 | 106 |
| 4000 | 35 | 7.6 | 78 |
| WOT | 38-41 | - | - |

0-20 MPH Acceleration - 3.7 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

**RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.*

SALE PRICE

| | | |
|--------------------|-----------|--------------|
| Boat | \$ | _____ |
| Motor _____ H.P. | | _____ |
| Trailer | | _____ |
| Accessories | | _____ |
| T, T & L | | _____ |
| TOTAL PRICE | \$ | _____ |

SSV 177 ELITE

SPECIFICATIONS

LOA 17' 1" (5.21 m.)
 Beam 88" (2.24 m.)
 Depth 43" (1.09 m.)
 Maximum Depth 59" (1.5 m.)
 Cockpit Depth 28 1/2" (.72 m.)
 Approx. Wt. w/3.0LX MerCruiser
 1750 lbs. (794 kg.)

Transom Width 73 1/4" (1.86 m.)
 Transom Deadrise 21°
 LOA on Trailer 21' 6" (6.55 m.)
 Fuel Capacity 20 gal. (75.7 L.)
 Maximum Load 1250 lbs. (567 kg.)
 Max. Persons 8 or 1150 lbs. (522 kg.)
 NMMA Certified

Draft: A. Drive Unit Up 16" (.41 m.)
 B. Drive Unit Down 31" (.79 m.)

STANDARD FEATURES

Padded instrument panel includes:
 speedometer, tachometer, trim,
 fuel, oil pressure, voltmeter and
 engine temperature gauges; plus
 switches for bilge pump, blower,
 horn, lights, and accessories
 Concealed electric horn
 Cockpit courtesy lights
 Bilge pump and blower
 Navigation lighting
 AM/FM stereo cassette
 with 2 speakers
 Glove box
 Ski locker
 Ski tow ring
 Stainless steel bow eye
 and stern eyes

6" cleats
 Walk-thru curved full glass
 windshield
 Bow access step
 Anchor locker
 Passenger grab handle
 Adjustable fold-out sleeper seats
 with aft jump seats
 Molded sleeper seat bases
 Custom side panels with storage
 Molded swim platform
 Stainless steel boarding ladder
 Soft top with concealed storage
 Hull and deck gelcoat accent stripes
 MerC/Volvo controls

OPTIONS

Canvas package: side curtains,
 stern curtain, soft top boot
 Mooring cover
 Cockpit cover
 Convenience package:
 depthsounder, compass,
 hour meter

High altitude prop
 Stainless steel prop (MerC only)
 Adjustable bucket/bench seating
 Adjustable bucket/sleeper seating
 Stainless steel stern rail package
 Bow pad

ENGINE OPTIONS

3.0LX MerCruiser (WOPS)
 3.0LX MerCruiser (WPS)
 4.3 MerCruiser

3.0 GL Volvo Penta
 3.0 GS Volvo Penta
 4.3 GL Volvo Penta

COLOR OPTIONS

Blue/White
 Red/White
 Teal/White

SSV 177 ELITE

PERFORMANCE DATA

ENGINE 3.0LX MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2100 | 15 | 2.5 | 102 |
| 2900 | 25 | 3.5 | 121 |
| 3500 | 35 | 7.4 | 80 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 3.4 sec.

ENGINE 4.3 MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2200 | 15 | 2.6 | 99 |
| 2900 | 25 | 3.8 | 112 |
| 3400 | 35 | 7.4 | 80 |
| WOT | 48-51 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 3.0 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 10 | 2.1 | 81 |
| 3000 | 20 | 3.2 | 106 |
| 4000 | 35 | 7.6 | 78 |
| WOT | 38-41 | - | - |

0-20 MPH Acceleration - 3.7 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____

Motor _____ H.P. _____

Trailer _____

Accessories _____

T, T & L _____

TOTAL PRICE \$ _____

SSV 195 ELITE

SPECIFICATIONS

LOA 19' 7" (5.96 m.)
 Beam 30 1/2" (2.31 m.)
 Depth 47" (1.19 m.)
 Maximum Depth 63" (1.6 m.)
 Cockpit Depth 28 3/4" (.73 m.)
 Approx. Wt. w/3.0LX MerCruiser 1825 lbs. (829 kg.)
 Draft:

Transom Width 75" (1.9 m.)
 Transom Deadrise 21°
 LOA on Trailer 22' (6.71 m.)
 Fuel Capacity 35 gal. (132.5 L.)
 Maximum Load 1500 lbs. (681 kg.)
 Max. Persons 8 or 1150 lbs. (522 kg.)
 NMMA Certified

A. Drive Unit Up 16 1/2" (.42 m.)
 B. Drive Unit Down 31 1/2" (.8 m.)

STANDARD FEATURES

Padded instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus horn, lights, and accessories
 Concealed electric horn
 Cockpit courtesy lights
 Bilge pump and blower
 Navigation lighting
 AM/FM stereo cassette with 2 speakers
 Glove box
 Ski locker
 Ski tow ring
 Stainless steel bow eye and stern eyes

6" cleats
 Walk-thru curved full glass windshield
 Wraparound bow seats
 Bow storage drawers
 Anchor locker
 Passenger grab handle
 Adjustable fold-out sleeper seats with aft jump seats
 Molded sleeper seat bases
 Custom side panels with storage
 Molded swim platform
 Stainless steel boarding ladder
 Soft top with concealed storage
 Hull and deck gelcoat accent stripes
 Merc/Volvo controls

OPTIONS

High altitude prop
 Stainless steel prop (MerC only)
 Adjustable bucket/bench seating
 Adjustable bucket/sleeper seating

Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot
 Mooring cover
 Cockpit cover/tonneau cover
 Convenience package: depthsounder, compass, hour meter

ENGINE OPTIONS

4.3 GL Volvo Penta
 5.0 FL Volvo Penta
 5.0 Fi Volvo Penta
 5.8 FL Volvo Penta
 5.8 Fi Volvo Penta
 434/4.3 GS DP Volvo Penta
 572/5.7 GL DP Volvo Penta
 5.7 Gi DP Volvo Penta

COLOR OPTIONS

Blue/White
 Red/White
 Teal/White

SSV 195 ELITE

PERFORMANCE DATA

ENGINE 4.3LX MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 3.0 | 160 |
| 3200 | 25 | 4.0 | 202 |
| 3700 | 35 | 7.9 | 141 |
| WOT | 47-49 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 5.0LX MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2200 | 15 | 3.3 | 144 |
| 2800 | 25 | 4.3 | 186 |
| 3500 | 35 | 8.0 | 141 |
| WOT | 53-57 | - | - |

0-20 MPH Acceleration - 3.1 sec.

ENGINE 4.3 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 15 | 2.8 | 161 |
| 3000 | 25 | 3.8 | 197 |
| 4000 | 35 | 6.9 | 152 |
| WOT | 42-45 | - | - |

0-20 MPH Acceleration - 3.2 sec.

ENGINE 434/4.3 GS DP VOLVO PENTA - PROP B6 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 3000 | 25 | 4.6 | 163 |
| 3500 | 35 | 7.2 | 146 |
| 4000 | 40 | 7.8 | 154 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 2.9 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____

Motor _____ H.P. _____

Trailer _____

Accessories _____

T,T & L _____

TOTAL PRICE \$ _____

SSV 197 ELITE

SPECIFICATIONS

| | |
|--|---------------------------------------|
| LOA 18' 7" (5.66 m.) | Transom Width 75" (1.9 m.) |
| Beam 90 3/4" (2.31 m.) | Transom Deadrise 21° |
| Depth 47" (1.19 m.) | LOA on Trailer 22' (6.71 m.) |
| Maximum Depth 63" (1.6 m.) | Fuel Capacity 35 gal. (132.5 L.) |
| Cockpit Depth 28 3/4" (.73 m.) | Maximum Load 1500 lbs. (681 kg.) |
| Approx. Wt. w/3.0LX MerCruiser | Max. Persons 8 or 1150 lbs. (522 kg.) |
| 1825 lbs. (829 kg.) | NMMA Certified |
| Draft: A. Drive Unit Up 16 1/2" (.42 m.) | B. Drive Unit Down 31 1/2" (.8 m.) |

STANDARD FEATURES

- Padded instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories
- Concealed electric horn
- Cockpit courtesy lights
- Bilge pump and blower
- Navigation lighting
- AM/FM stereo cassette with 2 speakers
- Glove box
- Ski locker
- Ski tow ring
- Stainless steel bow eye and stern eyes
- 6" cleats
- Walk-thru curved full glass windshield
- Bow access step
- Anchor locker
- Passenger grab handle
- Adjustable fold-out sleeper seats with aft jump seats
- Molded sleeper seat bases
- Custom side panels with storage
- Molded swim platform
- Stainless steel boarding ladder
- Soft top with concealed storage
- Hull and deck gelcoat accent stripes
- MerC/Volvo controls

OPTIONS

- Canvas package: side curtains, stern curtain, soft top boot
- Mooring cover
- Cockpit cover
- Convenience package: depthsounder, compass, hour meter
- High altitude prop
- Stainless steel prop (MerC only)
- Adjustable bucket/bench seating
- Adjustable bucket/sleeper seating
- Stainless steel stern rail package
- Bow pad

ENGINE OPTIONS

- 3.0LX MerCruiser (WOPS)
- 3.0LX MerCruiser (WPS)
- 4.3 MerCruiser
- 4.3LX MerCruiser
- 5.0 MerCruiser
- 5.0LX MerCruiser
- 5.7 MerCruiser
- 3.0 GL Volvo Penta
- 3.0 GS Volvo Penta
- 4.3 GL Volvo Penta
- 5.0 FL Volvo Penta
- 5.0 Fi Volvo Penta
- 5.8 FL Volvo Penta
- 5.8 Fi Volvo Penta
- 434/4.3 GS DP Volvo Penta
- 572/5.7 GL DP Volvo Penta
- 5.7 Gi DP Volvo Penta

COLOR OPTIONS

- Blue/White
- Red/White
- Teal/White

SSV 197 ELITE

PERFORMANCE DATA

| ENGINE 4.3LX MERCURISER - PROP 13 3/4 X 21 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2400 | 15 | 3.0 | 160 |
| 3200 | 25 | 4.0 | 202 |
| 3700 | 35 | 7.9 | 141 |
| WOT | 47-49 | - | - |
| 0-20 MPH Acceleration - 3.3 sec. | | | |

| ENGINE 5.0LX MERCURISER - PROP 13 3/4 X 21 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2200 | 15 | 3.3 | 144 |
| 2800 | 25 | 4.3 | 186 |
| 3500 | 35 | 8.0 | 141 |
| WOT | 53-57 | - | - |
| 0-20 MPH Acceleration - 3.1 sec. | | | |

| ENGINE 4.3 GL VOLVO PENTA - PROP 15 X 17 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2000 | 15 | 2.8 | 161 |
| 3000 | 25 | 3.8 | 197 |
| 4000 | 35 | 6.9 | 152 |
| WOT | 42-45 | - | - |
| 0-20 MPH Acceleration - 3.2 sec. | | | |

| ENGINE 434/4.3 GS DP VOLVO PENTA - PROP B6 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 25 | 4.6 | 163 |
| 3500 | 35 | 7.2 | 146 |
| 4000 | 40 | 7.8 | 154 |
| WOT | 46-49 | - | - |
| 0-20 MPH Acceleration - 2.9 sec. | | | |

NOTE: Performance results will vary depending on load, altitude, and other conditions.
 *RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____

Motor _____ H.P. _____

Trailer _____

Accessories _____

T, T & L _____

TOTAL PRICE \$ _____

SSV 215 ELITE

SPECIFICATIONS

| | |
|--|---------------------------------------|
| LOA 21' 2" (6.45 m.) | Transom Width 92" (2.34 m.) |
| Beam 97" (2.45 m.) | Transom Deadrise 19° |
| Depth 51" (1.29 m.) | LOA on Trailer 24' 8" (7.51 m.) |
| Maximum Depth 61" (1.54 m.) | Fuel Capacity 45 gal. (170.3 L.) |
| Cockpit Depth 31" (.77 m.) | Maximum Load 1600 lbs. (726 kg.) |
| Approx. Wt. w/5.7 MerCruiser 3050 lbs. (1384 kg.) | Max. Persons 9 or 1300 lbs. (590 kg.) |
| | NMMA Certified |
| Draft: | A. Drive Unit Up 17 1/2" (.44 m.) |
| | B. Drive Unit Down 32" (.81 m.) |

STANDARD FEATURES

| | |
|---|--|
| Padded instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, panel lights, interior lights, and horn | 6" cleats Walk-thru curved full glass windshield Wraparound bow seats Bow storage drawers Anchor locker Passenger grab handle Adjustable fold-out sleeper seats with aft jump seats Molded sleeper seat bases Custom side panels with storage Molded swim platform Stainless steel boarding ladder Soft top with concealed storage Hull and deck gelcoat accent stripes MerC/Volvo controls |
| Concealed electric horn Cockpit courtesy lights Bilge pump and blower Navigation lighting AM/FM stereo cassette with 2 speakers Lockable glove box Ski locker Ski tow ring Stainless steel bow eye and stern eyes | |

OPTIONS

| | |
|--|--|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | High altitude prop Stainless steel prop (MerC only) Adjustable bucket/bench seating Adjustable bucket/sleeper seating |
| Mooring cover Cockpit cover/tonneau cover Convenience package: depthsounder, compass, hour meter | |

ENGINE OPTIONS

| | |
|--|---------------------------|
| 4.3LX MerCruiser | 5.0 Fi Volvo Penta |
| 5.0 MerCruiser | 5.8 FL Volvo Penta |
| 5.0LX MerCruiser | 5.8 Fi Volvo Penta |
| 5.7 MerCruiser | 434/4.3 GS DP Volvo Penta |
| 350 MerCruiser Magnum | 572/5.7 GL DP Volvo Penta |
| 7.4 MerCruiser (SL seating only) | 5.7 Gi DP Volvo Penta |
| 5.7 MerCruiser Bravo III | 740/7.4 GL DP Volvo Penta |
| 7.4 MerCruiser Bravo III (SL seating only) | (SL seating only) |
| 5.0 FL Volvo Penta | |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 215 ELITE

PERFORMANCE DATA

ENGINE 5.7 MERCUISER - PROP 14 X 19 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|------|--------|
| 3000 | 28 | 8.9 | 163 |
| 3500 | 36 | 13.4 | 148 |
| 4000 | 47 | 17.4 | 133 |
| WOT | 50-54 | - | - |

0-20 MPH Acceleration - 3.7 sec.

ENGINE 350 MERCUISER MAGNUM - PROP 19 QSS

| RPM | MPH | GPH | RANGE* |
|------|-------|------|--------|
| 3000 | 29 | 8.9 | 163 |
| 3500 | 37 | 13.5 | 139 |
| 4000 | 47 | 17.6 | 139 |
| WOT | 51-55 | - | - |

0-20 MPH Acceleration - 3.6 sec.

ENGINE 7.4 MERCUISER - PROP 23 MIRAGE

| RPM | MPH | GPH | RANGE* |
|------|-------|------|--------|
| 3000 | 32 | 10.5 | 154 |
| 3500 | 38 | 14.2 | 139 |
| 4000 | 44 | 20.5 | 108 |
| WOT | 57-61 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 572/5.7 GL DP VOLVO PENTA - PROP B6 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|------|--------|
| 3000 | 33 | 9.2 | 136 |
| 3500 | 38 | 12.6 | 115 |
| 4000 | 42 | 17.5 | 91 |
| WOT | 50-53 | - | - |

0-20 MPH Acceleration - 3.4 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

**RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.*

SALE PRICE

| | |
|--------------------|-----------------|
| Boat | \$ _____ |
| Motor _____ H.P. | _____ |
| Trailer | _____ |
| Accessories | _____ |
| T, T & L | _____ |
| TOTAL PRICE | \$ _____ |

SSV 199

SPECIFICATIONS

| | |
|---|---|
| LOA 18' 7" (5.66 m.) | Transom Width 75" (1.9 m.) |
| Beam 90 ³ / ₄ " (2.31 m.) | Transom Deadrise 21° |
| Depth 53" (1.34 m.) | LOA on Trailer 22' (6.71 m.) |
| Maximum Depth 69" (1.75 m.) | Fuel Capacity 35 gal. (132.5 L.) |
| Cockpit Depth 35" (.89 m.) | Maximum Load 1500 lbs. (681 kg.) |
| Approx. Wt. w/3.0LX MerCruiser | Max. Persons 8 or 1150 lbs. (522 kg.) |
| 1825 lbs. (829 kg.) | NMMA Certified |
| Draft: A. Drive Unit Up 16 ¹ / ₂ " (.42 m.) | B. Drive Unit Down 31 ¹ / ₂ " (.8 m.) |

STANDARD FEATURES

- | | |
|---|--|
| Padded instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | 6" cleats |
| Concealed electric horn | Walk-thru curved glass windshield |
| Cockpit courtesy lights | Passenger grab handle |
| Automatic bilge pump | Stbd bucket seat/port sleeper seat with aft jump seats |
| Blower | Custom side panels with storage |
| Navigation lighting | Molded swim platform |
| AM/FM stereo cassette with 2 speakers | Lockable cabin door |
| Ski tow ring | Cabin light |
| Stainless steel bow eye and stern eyes | Forward V-berth |
| | Forward deck hatch |
| | Stainless steel boarding ladder |
| | Soft top with concealed storage |
| | Hull and deck gelcoat accent stripes |

OPTIONS

- | | |
|---|------------------------------------|
| Canvas package: side curtains, stern curtain, soft top boot | High altitude prop |
| Mooring cover | Stainless steel prop (MerC only) |
| Cockpit cover | Adjustable bucket/bench seating |
| Full glass windshield | Stainless steel bow rail package |
| Convenience package: depthsounder, compass, hour meter | Stainless steel stern rail package |
| | Portable head |

ENGINE OPTIONS

- | | |
|-------------------------|---------------------------|
| 3.0LX MerCruiser (WOPS) | 4.3 GL Volvo Penta |
| 3.0LX MerCruiser (WPS) | 5.0 FL Volvo Penta |
| 4.3 MerCruiser | 5.0 Fi Volvo Penta |
| 4.3LX MerCruiser | 5.8 FL Volvo Penta |
| 5.0 MerCruiser | 5.8 Fi Volvo Penta |
| 5.0LX MerCruiser | 434/4.3 GS DP Volvo Penta |
| 5.7 MerCruiser | 572/5.7 GL DP Volvo Penta |
| 3.0 GL Volvo Penta | 5.7 Gi DP Volvo Penta |
| 3.0 GS Volvo Penta | |

COLOR OPTIONS

- Blue/White
- Red/White
- Teal/White

SSV 199

PERFORMANCE DATA

| ENGINE 4.3LX MERCURISER - PROP 13 ³ / ₄ X 21 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2400 | 15 | 3.0 | 160 |
| 3200 | 25 | 4.0 | 202 |
| 3700 | 35 | 7.9 | 141 |
| WOT | 47-49 | - | - |

0-20 MPH Acceleration - 3.3 sec.

| ENGINE 5.0LX MERCURISER - PROP 13 ³ / ₄ X 21 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2200 | 15 | 3.3 | 144 |
| 2800 | 25 | 4.3 | 186 |
| 3500 | 35 | 8.0 | 141 |
| WOT | 53-57 | - | - |

0-20 MPH Acceleration - 3.1 sec.

| ENGINE 4.3 GL VOLVO PENTA - PROP 15 X 17 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 2000 | 15 | 3.0 | 150 |
| 3000 | 25 | 3.8 | 197 |
| 4000 | 35 | 7.1 | 148 |
| WOT | 43-46 | - | - |

0-20 MPH Acceleration - 3.2 sec.

| ENGINE 434/4.3 GS DP VOLVO PENTA - PROP B6 AL | | | |
|---|-------|-----|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 26 | 4.6 | 169 |
| 3500 | 33 | 7.2 | 137 |
| 4000 | 38 | 7.8 | 146 |
| WOT | 47-49 | - | - |

0-20 MPH Acceleration - 2.9 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

| | | |
|--------------------|-----------|--------------|
| Boat | \$ | _____ |
| Motor _____ H.P. | | _____ |
| Trailer | | _____ |
| Accessories | | _____ |
| T, T & L | | _____ |
| TOTAL PRICE | \$ | _____ |

SSV 219

SPECIFICATIONS

LOA 21' 2" (6.45 m.)
 Beam 97" (2.45 m.)
 Depth 58 1/2" (1.49 m.)
 Maximum Depth 71 1/2" (1.82 m.)
 Cockpit Depth 40 1/2" (1.03 m.)
 Approx. Wt. w/5.7 MerCruiser
 3100 lbs. (1407 kg.)
 Draft: A. Drive Unit Up 18 1/2" (.47 m.)
 B. Drive Unit Down 33" (.84 m.)

Transom Width 92" (2.34 m.)
 Transom Deadrise 19°
 LOA on Trailer 24' 8" (7.51 m.)
 Fuel Capacity 45 gal. (170.3 L.)
 Maximum Load 1450 lbs. (658 kg.)
 Max. Persons 8 or 1150 lbs. (522 kg.)
 NMMA Certified

STANDARD FEATURES

Padded instrument panel includes:
 speedometer, tachometer, trim,
 fuel, oil pressure, voltmeter and
 engine temperature gauges; plus
 switches for bilge pump, blower,
 horn, and accessories

Concealed electric horn
 Automatic bilge pump
 Blower
 Navigation lighting
 AM/FM stereo cassette
 with 2 speakers
 Cockpit floor storage compartment
 Stainless steel ski tow
 Stainless steel bow rail
 6" cleats
 Stainless steel bow eye
 and stern eyes

Walk-thru curved glass windshield
 Anchor locker
 Passenger grab handle
 Adjustable fold-out sleeper seats
 w/bench seat
 Lockable cabin door
 Cabin light
 Forward V-berth
 Forward deck hatch
 Custom side panels with storage
 Molded swim platform
 Stainless steel boarding ladder
 Soft top with concealed storage
 Hull and deck gelcoat accent stripes
 MerC/Volvo controls

OPTIONS

Canvas package: side curtains,
 stern curtain, soft top boot
 Mooring cover
 Cockpit cover
 Camper canvas
 Full glass windshield
 Convenience package:
 depthsounder, compass,
 hour meter

High altitude prop
 Stainless steel prop (MerC only)
 Adjustable bucket/bench seating
 Adjustable bucket/sleeper seating
 Stainless steel stern rail package
 Portable head
 Helm seat/entertainment console
 includes: sink, water system,
 alcohol stove and 34-qt. cooler

ENGINE OPTIONS

4.3LX MerCruiser
 5.0 MerCruiser
 5.0LX MerCruiser
 5.7 MerCruiser
 350 MerCruiser Magnum
 7.4 MerCruiser
 5.7 MerCruiser Bravo III
 7.4 MerCruiser Bravo III

5.0 FL Volvo Penta
 5.0 Fi Volvo Penta
 5.8 FL Volvo Penta
 5.8 Fi Volvo Penta
 434/4.3 GS DP Volvo Penta
 572/5.7 GL DP Volvo Penta
 5.7 Gi DP Volvo Penta
 740/7.4 GL DP Volvo Penta

COLOR OPTIONS

Blue/White
 Red/White
 Teal/White

SSV 219

PERFORMANCE DATA

| ENGINE 5.7 MERCURISER - PROP 14 X 19 AL | | | |
|---|-------|------|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 28 | 8.9 | 164 |
| 3500 | 36 | 13.4 | 149 |
| 4000 | 47 | 17.4 | 133 |
| WOT | 48-50 | - | - |
| 0-20 MPH Acceleration - 3.7 sec. | | | |

| ENGINE 350 MERCURISER MAGNUM - PROP 19 QSS | | | |
|--|-------|------|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 29 | 8.9 | 164 |
| 3500 | 37 | 13.5 | 139 |
| 4000 | 47 | 17.6 | 139 |
| WOT | 51-53 | - | - |
| 0-20 MPH Acceleration - 3.6 sec. | | | |

| ENGINE 7.4 MERCURISER - PROP 23 MIRAGE | | | |
|--|-------|------|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 32 | 10.5 | 154 |
| 3500 | 38 | 14.2 | 139 |
| 4000 | 44 | 20.5 | 108 |
| WOT | 54-57 | - | - |
| 0-20 MPH Acceleration - 3.3 sec. | | | |

| ENGINE 572/5.7 GL DP VOLVO PENTA - PROP B6 AL | | | |
|---|-------|------|--------|
| RPM | MPH | GPH | RANGE* |
| 3000 | 32 | 9.4 | 129 |
| 3500 | 38 | 12.7 | 114 |
| 4000 | 42 | 17.6 | 91 |
| WOT | 49-51 | - | - |
| 0-20 MPH Acceleration - 3.5 sec. | | | |

NOTE: Performance results will vary depending on load, altitude, and other conditions.
 *RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____
 Motor _____ H.P. _____
 Trailer _____
 Accessories _____
 T,T & L _____
TOTAL PRICE \$ _____

SSV 170 SKI & FISH

SPECIFICATIONS

| | |
|---------------------------------------|---------------------------------------|
| LOA 17' 1" (5.21 m.) | Transom Deadrise 21° |
| Beam 88" (2.24 m.) | LOA on Trailer 21' 6" (6.55 m.) |
| Depth 43" (1.09 m.) | Fuel Capacity 20 gal. (75.7 L.) |
| Maximum Depth 59" (1.5 m.) | Maximum Load 1800 lbs. (817 kg.) |
| Cockpit Depth 28½" (.72 m.) | Max. Persons 8 or 1150 lbs. (522 kg.) |
| Approx. Wt. 1125 lbs. (511 kg.) | Maximum Horsepower 150 |
| Transom Width 73¼" (1.86 m.) | NMMA Certified |
| Draft: A. Drive Unit Up 15½" (.39 m.) | |
| B. Drive Unit Down 28½" (.72 m.) | |

STANDARD FEATURES

| | |
|--|---|
| Instrument panel includes: speedometer, tachometer, and fuel gauge; plus switches for bilge pump, navigation/anchor lights, panel lights, horn, and accessories | 6" cleats Walk-thru curved glass windshield Wraparound bow seats Bow converts to fishing deck 2 removable fishing seats Anchor locker |
| Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug | Passenger grab handle Side panels with storage Molded swim platform Stainless steel boarding ladder Soft top with concealed storage Hull and deck gelcoat accent stripes |
| Concealed electric horn Bilge pump Navigation lighting AM/FM stereo cassette with 2 speakers | Aerated livewell Trolling motor mount Trolling motor battery trays Rod holder |
| Glove box Ski locker Stainless steel bow eye and stern eyes | |

OPTIONS

| | |
|---|---|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Ski tow pylon Full glass windshield |
| Mooring cover Cockpit cover/tonneau cover | OMC Pre-Rig includes: ignition switch with ignition interrupt switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls, pre-drilled transom |
| Convenience package: depthsounder, compass, hour meter | |
| Fishing package: trolling motor, fish finder | |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 170 SKI & FISH

PERFORMANCE DATA

ENGINE 90 EVINRUDE - PROP 13¼ X 17

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2500 | 15 | 2.9 | 88 |
| 3400 | 25 | 4.2 | 102 |
| 4600 | 35 | 6.3 | 95 |
| WOT | 38-40 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 115 EVINRUDE - PROP 12¾ X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2500 | 15 | 3.6 | 71 |
| 3300 | 25 | 4.6 | 92 |
| 4700 | 35 | 7.2 | 83 |
| WOT | 42-44 | - | - |

0-20 MPH Acceleration - 3.2 sec.

ENGINE 135 MERCURY (V6) - PROP 13¾ X 21 S/S LASER

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 4.2 | 71 |
| 3000 | 25 | 5.1 | 87 |
| 4000 | 35 | 7.1 | 87 |
| WOT | 45-48 | - | - |

0-20 MPH Acceleration - 3.1 sec.

ENGINE 140 JOHNSON - PROP 14¼ X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2100 | 15 | 3.5 | 73 |
| 3300 | 25 | 4.4 | 97 |
| 4000 | 35 | 6.9 | 87 |
| WOT | 46-48 | - | - |

0-20 MPH Acceleration - 3.2 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

**RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.*

SALE PRICE

| | |
|--------------------|-----------------|
| Boat | \$ _____ |
| Motor _____ H.P. | _____ |
| Trailer | _____ |
| Accessories | _____ |
| T, T & L | _____ |
| TOTAL PRICE | \$ _____ |

SSV 175 SKI & FISH

SPECIFICATIONS

| | |
|---|---------------------------------------|
| LOA 17' 1" (5.21 m.) | Transom Width 73 1/4" (1.86 m.) |
| Beam 88" (2.24 m.) | Transom Deadrise 21° |
| Depth 43" (1.09 m.) | LOA on Trailer 21' 6" (6.55 m.) |
| Maximum Depth 59" (1.5 m.) | Fuel Capacity 20 gal. (75.7 L.) |
| Cockpit Depth 28 1/2" (.72 m.) | Maximum Load 1250 lbs. (567 kg.) |
| Approx. Wt. w/3.0LX MerCruiser 1750 lbs. (794 kg.) | Max. Persons 8 or 1150 lbs. (522 kg.) |
| | NMMA Certified |
| Draft: A. Drive Unit Up 16" (.41 m.) | |
| B. Drive Unit Down 31" (.79 m.) | |

STANDARD FEATURES

| | |
|---|--|
| Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | Walk-thru curved glass windshield Wraparound bow seats Bow converts to fishing deck 2 adjustable bucket seats/ 2 removable fishing seats/ bench seat |
| Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug | Anchor locker Passenger grab handle Side panels with storage Molded swim platform Stainless steel boarding ladder Convertible stern sundeck/ fishing platform |
| Concealed electric horn Bilge pump and blower Navigation lighting AM/FM stereo cassette with 2 speakers | Soft top with concealed storage Hull and deck gelcoat accent stripes Aerated livewell Trolling motor mount Trolling motor battery trays Rod holder Tackle box tray |
| Glove box Ski locker Ski tow ring Stainless steel bow eye and stern eyes 6" cleats | |

OPTIONS

| | |
|--|---|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Fishing package includes: trolling motor, fish finder Full glass windshield High altitude prop Stainless steel prop (MerC only) |
| Mooring cover Cockpit cover/tonneau cover Convenience package: depthsounder, compass, hour meter | |

ENGINE OPTIONS

| | |
|-------------------------|--------------------|
| 3.0LX MerCruiser (WOPS) | 3.0 GL Volvo Penta |
| 3.0LX MerCruiser (WPS) | 3.0 GS Volvo Penta |
| 4.3 MerCruiser | 4.3 GL Volvo Penta |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 175 SKI & FISH

PERFORMANCE DATA

ENGINE 3.0LX MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2100 | 15 | 2.5 | 102 |
| 2900 | 25 | 3.5 | 121 |
| 3500 | 35 | 7.4 | 80 |
| WOT | 42-45 | - | - |

0-20 MPH Acceleration - 3.4 sec.

ENGINE 4.3 MERCUISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2200 | 15 | 2.6 | 99 |
| 2900 | 25 | 3.8 | 112 |
| 3400 | 35 | 7.4 | 80 |
| WOT | 48-51 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 3.0 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 10 | 2.1 | 81 |
| 3000 | 20 | 3.2 | 106 |
| 4000 | 35 | 7.6 | 78 |
| WOT | 38-41 | - | - |

0-20 MPH Acceleration - 3.7 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.

**RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.*

SALE PRICE

| | | |
|--------------------|-----------|-------|
| Boat | \$ | _____ |
| Motor _____ H.P. | | _____ |
| Trailer | | _____ |
| Accessories | | _____ |
| T, T & L | | _____ |
| TOTAL PRICE | \$ | _____ |

SSV 190 SKI & FISH

SPECIFICATIONS

| | |
|---------------------------------|---------------------------------------|
| LOA 18' 7" (5.66 m.) | Transom Deadrise 21° |
| Beam 90 3/4" (2.31 m.) | LOA on Trailer 22' (6.71 m.) |
| Depth 47" (1.19 m.) | Fuel Capacity 35 gal. (132.5 L.) |
| Maximum Depth 63" (1.6 m.) | Maximum Load 1900 lbs. (863 kg.) |
| Cockpit Depth 28 3/4" (.73 m.) | Max. Persons 8 or 1150 lbs. (522 kg.) |
| Approx. Wt. 1200 lbs. (545 kg.) | Maximum Horsepower 175 |
| Transom Width 75" (1.9 m.) | NMMA Certified |
| | Draft: A. Drive Unit Up 16" (.41 m.) |
| | B. Drive Unit Down 29" (.74 m.) |

STANDARD FEATURES

| | |
|--|---|
| Instrument panel includes: speedometer, tachometer, and fuel gauge; plus switches for bilge pump, navigation/anchor lights, panel lights, horn, and accessories | 6" cleats Walk-thru curved glass windshield Wraparound bow seats Bow converts to fishing deck 2 removable fishing seats Anchor locker |
| Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug | Passenger grab handle Side panels with storage Molded swim platform Stainless steel boarding ladder Soft top with concealed storage Hull and deck gelcoat accent stripes |
| Concealed electric horn | Aerated livewell |
| Bilge pump | Trolling motor battery trays |
| Navigation lighting | Rod holders |
| AM/FM stereo cassette with 2 speakers | |
| Glove box | |
| Ski locker | |
| Stainless steel bow eye and stern eyes | |

OPTIONS

| | |
|---|---|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Ski tow pylon Full glass windshield |
| Mooring cover | OMC Pre-Rig includes: ignition switch with ignition interrupt |
| Cockpit cover/tonneau cover | switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls, pre-drilled transom |
| Convenience package: depthsounder, compass, hour meter | |
| Fishing package includes: trolling motor, fish finder | |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 190 SKI & FISH

PERFORMANCE DATA

ENGINE 90 EVINRUDE - PROP 13 1/4 X 17

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2700 | 15 | 3.0 | 160 |
| 3500 | 25 | 4.4 | 182 |
| 4800 | 35 | 6.5 | 173 |
| WOT | 37-39 | - | - |

0-20 MPH Acceleration - 3.4 sec.

ENGINE 115 EVINRUDE - PROP 12 3/4 X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2600 | 15 | 3.7 | 131 |
| 3400 | 25 | 4.8 | 166 |
| 4700 | 35 | 7.2 | 157 |
| WOT | 42-44 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 135 MERCURY (V6) - PROP 13 7/8 X 21 S/S LASER

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2500 | 15 | 4.4 | 109 |
| 3100 | 25 | 5.3 | 150 |
| 4200 | 35 | 7.5 | 147 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 3.2 sec.

ENGINE 150 JOHNSON - PROP 14 1/4 X 21

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 4.5 | 106 |
| 3000 | 25 | 5.5 | 144 |
| 3900 | 35 | 7.8 | 141 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 3.1 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

Boat \$ _____
 Motor _____ H.P. _____
 Trailer _____
 Accessories _____
 T,T & L _____
TOTAL PRICE \$ _____

SSV 195 SKI & FISH

SPECIFICATIONS

| | |
|--|---------------------------------------|
| LOA 18' 7" (5.66 m.) | Transom Width 75" (1.9 m.) |
| Beam 90 3/4" (2.31 m.) | Transom Deadrise 21° |
| Depth 47" (1.19 m.) | LOA on Trailer 22' (6.71 m.) |
| Maximum Depth 63" (1.6 m.) | Fuel Capacity 35 gal. (132.5 L.) |
| Cockpit Depth 28 3/4" (.73 m.) | Maximum Load 1500 lbs. (681 kg.) |
| Approx. Wt. w/4.3 MerCruiser | Max. Persons 8 or 1150 lbs. (522 kg.) |
| 2000 lbs. (908 kg.) | NMMA Certified |
| Draft: A. Drive Unit Up 16 1/2" (.42 m.) | B. Drive Unit Down 31 1/2" (.8 m.) |

STANDARD FEATURES

| | |
|---|---|
| Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn, lights, and accessories | Walk-thru curved glass windshield Wraparound bow seats Bow converts to fishing deck 2 adjustable bucket seats/ 2 removable fishing seats/ bench seat |
| Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug | Anchor locker Passenger grab handle Side panels with storage Molded swim platform Stainless steel boarding ladder Convertible stern sundeck/ fishing platform |
| Concealed electric horn Bilge pump and blower Navigation lighting AM/FM stereo cassette with 2 speakers | Soft top with concealed storage Hull and deck gelcoat accent stripes Aerated livewell Trolling motor mount Trolling motor battery trays Rod holders Tackle box tray |
| Glove box Ski locker Ski tow ring Stainless steel bow eye and stern eyes 6" cleats | |

OPTIONS

| | |
|--|--|
| Canvas package: tonneau cover, walk-thru curtain, side curtains, stern curtain, soft top boot | Fishing package: trolling motor, fish finder Full glass windshield High altitude prop Stainless steel prop (MerC only) |
| Mooring cover Cockpit cover/tonneau cover Convenience package: depthsounder, compass, hour meter | |

ENGINE OPTIONS

| | |
|-------------------------|---------------------------|
| 3.0LX MerCruiser (WOPS) | 3.0 GS Volvo Penta |
| 3.0LX MerCruiser (WPS) | 4.3 GL Volvo Penta |
| 4.3 MerCruiser | 5.0 FL Volvo Penta |
| 4.3LX MerCruiser | 5.0 Fi Volvo Penta |
| 5.0 MerCruiser | 5.8 FL Volvo Penta |
| 5.0LX MerCruiser | 5.8 Fi Volvo Penta |
| 5.7 MerCruiser | 434/4.3 GS DP Volvo Penta |
| 3.0 GL Volvo Penta | 572/5.7 GL DP Volvo Penta |

COLOR OPTIONS

Blue/White
Red/White
Teal/White

SSV 195 SKI & FISH

PERFORMANCE DATA

ENGINE 4.3LX MERCURISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2400 | 15 | 3.0 | 160 |
| 3200 | 25 | 4.0 | 202 |
| 3700 | 35 | 7.9 | 141 |
| WOT | 47-49 | - | - |

0-20 MPH Acceleration - 3.3 sec.

ENGINE 5.0LX MERCURISER - PROP 13 3/4 X 21 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2200 | 15 | 3.3 | 144 |
| 2800 | 25 | 4.3 | 186 |
| 3500 | 35 | 8.0 | 141 |
| WOT | 53-57 | - | - |

0-20 MPH Acceleration - 3.1 sec.

ENGINE 4.3 GL VOLVO PENTA - PROP 15 X 17 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 2000 | 15 | 2.8 | 161 |
| 3000 | 25 | 3.8 | 197 |
| 4000 | 35 | 6.9 | 152 |
| WOT | 42-45 | - | - |

0-20 MPH Acceleration - 3.2 sec.

ENGINE 434/4.3 GS DP VOLVO PENTA - PROP B6 AL

| RPM | MPH | GPH | RANGE* |
|------|-------|-----|--------|
| 3000 | 25 | 4.6 | 163 |
| 3500 | 35 | 7.2 | 146 |
| 4000 | 40 | 7.8 | 154 |
| WOT | 46-49 | - | - |

0-20 MPH Acceleration - 2.9 sec.

NOTE: Performance results will vary depending on load, altitude, and other conditions.
*RANGE: Mileage range at designated RPM and MPH as shown above starting with a full tank of gas.

SALE PRICE

| | |
|--------------------|-----------------|
| Boat | \$ _____ |
| Motor _____ H.P. | _____ |
| Trailer | _____ |
| Accessories | _____ |
| T, T & L | _____ |
| TOTAL PRICE | \$ _____ |

ENGINE INFORMATION

The following pages contain data about sterndrives offered in our 1994 product.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height

MERCUISER 3.0LX LITRE

135 hp/101 kw.
4
181
9.3:1
4400-4800
1.98:1
Power
Power
33¹/₄"
22³/₁₆"
19⁷/₁₆" (above crankshaft CL)
28⁵/₈" (overall)
625 lbs. (pkg. weight)

Weight

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height

MERCUISER 3.0LX LITRE w/Power Steering

135 hp/101 kw.
4
181
9.3:1
4400-4800
1.98:1
Power
Power
33¹/₄"
22³/₁₆"
19⁷/₁₆" (above crankshaft CL)
28⁵/₈" (overall)
625 lbs. (pkg. weight)

Weight

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

MERCUISER 4.3 LITRE w/Power Steering

160 hp/116 kw.
6
262
9.3:1
4400-4800
1.84:1
Power
Power
31¹³/₁₆"
29¹/₄"
20¹/₂" (above crankshaft CL)
802 lbs. (pkg. weight)

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

MERCUISER 4.3LX LITRE w/Power Steering

180 hp/134 kw.
6
262
9.3:1
4400-4800
1.84:1
Power
Power
31¹³/₁₆"
29¹/₄"
20¹/₂" (above crankshaft CL)
802 lbs. (pkg. weight)

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height

MERCUISER 5.0 LITRE w/Power Steering

190 hp/142 kw.
8
305
8.5:1
4200-4600
1.65:1
Power
Power
36³/₁₆"
28¹/₂"
20³/₄" (above crankshaft CL)
28¹/₂" (overall)
893 lbs. (pkg. weight)

Weight

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height

MERCUISER 5.0LX LITRE

205 hp/153 kw.
8
305
9.3:1
4200-4600
1.50:1
Power
Power
36³/₁₆"
28¹/₂"
20³/₄" (above crankshaft CL)
28¹/₂" (overall)
893 lbs. (pkg. weight)

Weight

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height

Weight

**MERCUISER 5.7 LITRE
w/Power Steering**

235 hp/172 kw.
8
350
9.0:1
4400-4800
1.50:1
Power
Power
36¹⁵/₁₆"
28¹/₂"
20" (above crankshaft CL)
27³/₄" (overall)
907 lbs. (pkg. weight)

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

MERCUISER 350 MAGNUM*
w/Power Steering

250 hp/179 kw.
8
350
9.3:1
4400-4800
1.50:1
Power
Power
36¹⁵/₁₆"
28⁷/₈" (above crankshaft CL)
938 lbs. (pkg. weight)

*Stainless steel propeller – standard

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

MERCUISER 7.4 LITRE*
w/Power Steering

300 hp/224 kw.
8
454
8.5:1
4200-4600
1.32:1
Power
Power
39"
32"
20¹¹/₁₆" (above crankshaft CL)
1125 lbs. (pkg. weight)

*Stainless steel propeller – standard

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

**5.7 MERCUISER BRAVO III
w/Power Steering**

250 hp/186 kw.
8
350
9.3:1
4400-4800
2.0:1
Power
Power
36⁵/₁₆"
29"
21¹³/₁₆"
998 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

7.4 MERCUISER BRAVO III

300 hp/224 kw.
8
454
8.0:1
4200-4600
2.0:1
Power
Power
39"
32"
23"
1125 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Length
Width
Height
Weight

3.0 GL VOLVO PENTA

120 hp/89 kw.
4
181
9.3:1
4600
1.85:1
Power
Power
35¹/₈"
24³/₄"
19⁵/₈" (above crankshaft CL)
480 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

3.0 GS VOLVO PENTA

130 hp/96 kw.
4
181
9.3:1
4600
1.85:1
Power
35¹/₈"
24³/₄"
19⁵/₈" (above crankshaft CL)
480 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

4.3 GL VOLVO PENTA

160 hp/119 kw.
6
262
9.3:1
4600
1.66:1
Power
31³/₄"
29¹/₂"
19³/₄" (above crankshaft CL)
680 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

5.0 FL VOLVO PENTA

190 hp/142 kw.
8
302
8.4:1
4400
1.66:1
Power
37⁵/₈"
28"
20¹/₈" (above crankshaft CL)
739 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

5.0 Fi VOLVO PENTA

215 hp/160 kw.
8
302
8.5:1
4600
1.66:1
Power
37⁵/₈"
28¹/₂"
20⁷/₁₆" (above crankshaft CL)
764 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

5.8 FL VOLVO PENTA

230 hp/171 kw.
8
351
8.3:1
4400
1.51:1
Power
37⁵/₈"
29³/₄"
20¹/₄" (above crankshaft CL)
796 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

5.8 Fi VOLVO PENTA

255 hp/190 kw.
8
351
8.8:1
4600
1.51:1
Power
37⁵/₈"
30¹/₂"
22" (above crankshaft CL)
850 lbs.

MODEL:

Horsepower at Prop Shaft
Cylinders
Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio
Tilt
Trim
Power
Length
Width
Height
Weight

434/4.3 GS DP VOLVO PENTA

185 hp/138 kw.
6
262
9.3:1
4800
2.3:1
Power
Power
31³/₄"
29¹/₂"
20¹/₄" (above crankshaft CL)
680 lbs.

MODEL:

| | |
|--------------------------|--|
| Horsepower at Prop Shaft | 572/5.7 GL DP VOLVO PENTA |
| Cylinders | 225 hp/168 kw. |
| Cubic Inches | 8 |
| Compression Ratio | 350 |
| Max. Recommended RPM | 9.3:1 |
| Lower Unit Gear Ratio | 4600 |
| Tilt | 1.95:1 |
| Trim | Power |
| Length | Power |
| Width | 40" |
| Height | 28 ⁷ / ₈ " |
| Weight | 21 ³ / ₈ " (above crankshaft CL) 886 lbs. |

MODEL:

| | |
|--------------------------|---------------------------------------|
| Horsepower at Prop Shaft | 5.7 Gi DP VOLVO PENTA |
| Cylinders | 250 hp/187 kw. |
| Cubic Inches | 8 |
| Compression Ratio | 350 |
| Max. Recommended RPM | 9.3:1 |
| Lower Unit Gear Ratio | 4600 |
| Tilt | 1.95:1 |
| Trim | Power |
| Length | Power |
| Width | 38 ¹ / ₂ " |
| Height | 28 ¹ / ₄ " |
| Weight | 22" (above crankshaft CL) 913 lbs. |

MODEL:

| | |
|--------------------------|---|
| Horsepower at Prop Shaft | 740/7.4 GL DP VOLVO PENTA |
| Cylinders | 300 hp/224 kw. |
| Cubic Inches | 8 |
| Compression Ratio | 454 |
| Max. Recommended RPM | 8.0:1 |
| Lower Unit Gear Ratio | 4600 |
| Tilt | 1.78:1 |
| Trim | Power |
| Length | Power |
| Width | 40 ³ / ₄ " |
| Height | 31 ³ / ₈ " |
| Weight | 21 ⁷ / ₈ " 1160 lbs. |

GLASTRON®
THE CHOICE OF EXPERIENCED BOATERS

700 West River Rd., Little Falls, MN 56345
(612) 632-8395 Fax (612) 632-1438