
CVX-20 SPRINT



SPECIFICATIONS

Stor. Capacity 35.8 c.f. 1.01 cu.m. LOA on Trailer 21'91/2" 6.64M Steering Dual Cable Mechanical Max. Load 1515 lbs. 687 kg. Maximum Depth 48" 1.22M Depth 37" .94M Beam 90 1/4" 2.29M Max. Pers. 6 or 1025 lbs. 465 kg. Boat Ht. on Trailer 63" 1.6N Ice Box Cap. .6 c.f. 18 qt. 17 l. Transom Width 8434" 2.15M Approx. Wt. 1050 lbs. 476 kg. Motor Shaft Length 20" Cockpit Depth 26" .66M Max. Horsepower 200 Fuel Cap. 27 gallons

Trailer SC-20 O/B SCT-20 O/B (See Page 12)
Draft: A. Drive Unit Up 12½".32M

B. Drive Unit Down 30" .76M

COLORS

CVX-20 SPRINT

Stainless steel stern rails Two bow storage covers STANDARD FEATURES Instrument panel with: speedometer, tachometer fuel gauge and switches

Stainless steel boarding Positive foam flotation Custom sport wheel Deluxe grab bar

and lights

for bilge pump, horn,

Smoked custom plexiglass Concealed electric horn Carpet storage areas windshield

Full width wrap-around Custom mooring cover Deluxe side trays Custom ski tow Built-in fuel tank Bilge pump

Running lights

rear seat

Drinkholder: including accommodates foamstepped design which

Slide mechanism on Forward bucket seats swive Deluxe center console with helmsman seat insulated-type drinkholder

Plush pile carpet Teak trim and boarding steps

Courtesy light

lockable storage