# 2006 Product Specifications Manual



# 

#### **Table of Contents**

Model Designator Key2
2006 Model Directory3
Glastron's 50th Anniversary4-5
Glastron Performance6
SSV® Hull Design
VEC® Technology8-9
Unitized Deck & Floor10
Unitized Hull & Stringer System11
Customer Satisfaction12
Glastron's Unmatched Warranty13
Component Warranty Summary 14-15
Glastron Warranty16-17
VEC® Warranty18-19
Features & Benefits20-21
Canvas Choices22
Seating Choices23
EZ Loader® Trailers24-25
Financing Guide26
Definitions of Measurements27
Model Specifications28-75
Sterndrive Engine Specifications 76-83





#### Model Designator Key

0 = Outboard5 = Open Bow Sterndrive9 = Cuddy Cabin Sterndrive

Example: the SX 170 is an outboard model.

#### **Model Directory**

MX Runabouts	
MX 170	28
MX 175	30
MX 195	32
SX Runabouts	
SX 170	34
SX 175	
SX 195	38
GX Runabouts	
GX 180	40
GX 185	
GX 205	44
GX 235	46
GX 255	48
GXL Runabouts	
GXL 205	50
GXL 205 Collector's Edition.	
GX Ski & Fish	
GX 180 Ski & Fish	54
GX 185 Ski & Fish	
GX 205 Ski & Fish	
Deck Boats	
DX 205	60
DS 215	
DX 235	
GS Sport Cruisers	
GS 209	66
GS 219	
GS 259	
GS 269	
GS 279	

#### A 50-Year Legacy In Family Boating


- This year is Glastron's **fiftieth year in business**—a milestone few boat companies have achieved. During that time, they have built **nearly half a million fiberglass runabouts**.
- More than any other manufacturer, Glastron has a legacy of unprecedented product innovations and technological breakthroughs. Among them:
  - The deep-vee hull
  - The tri-hull
  - Two-tone graphics
  - Sterndrive-powered boats
  - The SSV® hull
  - Fiberglass stringer systems
  - VEC® closed-mold boat building technology
- More than a few well-known people over the years have owned Glastron boats, from President Lyndon Johnson... to England's Royal Family...to Elvis Presley.

- Glastron has appeared in **numerous movies and television shows** such as
  The Boatniks, Outlaw Blues, and The Price
  is Right. Glastron was James Bond's boat
  of choice in Live and Let Die and
  Moonraker. The most famous Glastron
  ever? The Batboat!
- Glastron has created an entirely new boat the GXL 205 Collector's Edition—to commemorate its 50<sup>th</sup> Anniversary.
- Every Glastron model this year is available with an attractively-priced 50th Anniversary Package of popular options selected just for that model.






#### Glastron Performance



- Glastron's penchant for performance is known throughout the industry.
- Glastron® has collected dozens of design and performance awards over the years. Among them: twelve Product Excellence Awards from Powerboat magazine.
- Every Glastron model delivers performance attributes that every family boater can appreciate (and every Glastron owner knows):
  - Very quick planing times (and minimal bowrise)
  - Impressive top speeds
  - Low minimum planing speeds (particularly important for tubing, kneeboarding and wakeboarding)
  - Agile handling
  - Excellent fuel economy

# Hull Design




- A boat's hull design is the most important thing that determines how that boat will perform. That's why Glastron® has made hull design a top priority right from day one.
- The legendary **SSV® hull** (Super Stable Vee) is the biggest reason Glastron's runabouts plane, run and corner so well.
- In boating circles, people recognize the SSV hull as one of the bestperforming hulls ever designed. If there's any doubt, just ask any Glastron owner how well their boat performs.
- Glastron's SSV hull is patented; only Glastron has it. So no matter what other manufacturers may tell you, they don't have an SSV hull.



#### **VEC®** Technology

- VEC® (Virtual Engineered Composites) is a patented process developed by Genmar and introduced by Glastron®.
- Other manufacturers build fiberglass boats using an open-mold process, a process that is labor-intensive, messy and imprecise. VEC, on the other hand, is a **closed-mold** process.




- The VEC system is a highly automated, computer-controlled manufacturing process—one that results in a near-perfect fiberglass boat hull every time.
- VEC construction eliminates the need for wood stringers. A fiberglass stringer system is an integral part of the hull.

- Every VEC boat has a skid-resistant fiberglass floor.
- VEC is also a cleaner and more **environmentally-friendly** way to build boats. The fiberglass lamination portion of the VEC manufacturing process reduces styrene emissions by 90% compared to conventional handlaid lamination.
- Glastron® backs every VEC boat with the ultimate warranty: a **lifetime limited** warranty on all structural components.






#### Unitized Deck & Floor



- In 2006, all Glastron® runabouts are constructed with a **unitized deck/floor**.
- The entire topside of the boat—deck, floor, side panels, footwells, seat bases—is **fabricated as a single fiberglass component** (versus 2, 3 or more components in conventional construction).
- There are **no seams or joints**, which provides a clean and seamless look.
- Unitized construction means unparalleled structural rigidity, which translates to greater strength.
- Another benefit: boats with unitized construction have a quieter, smoother, more responsive ride. So not only can you see the difference, but you can actually feel the difference on the water.

# Unitized Hull & Stringer System



- Thanks to VEC® technology, several Glastron® runabout models this year also have a completely integrated hull and stringer system.
- The hull and stringer system is a single molded fiberglass structure.
- There are **no wooden stringers** as there are with conventional construction—so there's nothing to rot or separate.
- Integrated fiberglass construction means less weight and enhanced structural rigidity—in other words, a lighter, stronger boat.



#### Customer Satisfaction

- Glastron® has always been known for its ability to anticipate the needs and wants of family boaters. As a result, our boats possess the essential elements for a great boating experience:
  - Attractive styling
  - Highly functional, family-friendly design
  - Impressive performance
  - Lots of built-in safety features
- Over the course of fifty years, we've built a loyal following among Glastron owners. They know Glastron manufacturing standards.
- In independent surveys conducted each year by NMMA (National Marine

Manufacturers Association), every new Glastron owner gets to voice their opinion about their boat.

■ The result: for the past three years in a row, Glastron has received NMMA's Excellence in Customer Satisfaction Award.



#### Glastron's Unmatched Warranty

Manufacturers of quality products tend to stand behind them, so the best way to judge the quality of a boat is to look at how well it's backed. When you compare Glastron® warranties with those of other boat builders, you'll see that Glastron's are among the best in the marine industry.



Every Glastron comes with a lifetime limited warranty on the

■ Glastron models built with VEC® technology (17, 18, 19 and 20-foot runabouts) come with a lifetime limited warranty on all structural components that is transferable to the second owner.



Glastron also provides a 2-year limited warranty on all factory-installed components.\* That's twice as long as most boat builders.

\*Propulsion warranties vary by manufacturer.



#### Component Warranty Summary

Company	Item	Warranty
Faria	Instruments	Lifetime limited warranty
Inland	Perma Panel wood components	Lifetime limited warranty
G&T	Upholstery vinyl & fabrics	5 year limited warranty
Sunbrella	Canvas	5 year limited warranty
Bennett	Trim tabs	5 year limited warranty
Perko	Marine hardware	5 year limited warranty
Garelick	Seat pedestals	3 year limited warranty
Lowrance	Depth sounders & fish finders	3 year limited warranty*
Moeller	Fuel tanks	3 year limited warranty*
Syntec	Marine carpeting	3 year limited warranty
M & G Electronics	Dashes & wiring	3 year limited warranty
Clarion	AM/FM/CD player	2 year limited warranty
Novatron	Dash panel, switches & wiring	2 year limited warranty
Teleflex	Steering & control cables	2 year limited warranty
Minn Kota	Trolling motor	2 year limited warranty
Taylor Made	Windshield	2 year limited warranty*

Company	ltem	Warranty
Ameritex	Windshield	2 year limited warranty*
Moeller	Rotocast components	2 year limited warranty*
Attwood	Bilge pumps & blowers	2 year limited warranty*
RMI	Rotocast components	2 year limited warranty*
* 1 year vendor w	arranty plus additional	year of Glastron warranty.
Volvo Penta	Sterndrive engine & outdrive	2 year limited warranty**
MerCruiser	Sterndrive engine & outdrive	1 year limited warranty
Evinrude	Outboard motor Direct Injection E-TEC	3 year limited warranty 3 year limited warranty
Johnson	Outboard motor 2 stroke 4 stroke	2 year limited warranty 3 year limited warranty
Mercury	Outboard motor 2 stroke up to 125 hp 2 stroke 150+ hp Optimax 4 stroke	o 1 year limited warranty 2 year limited warranty 3 year limited warranty 3 year limited warranty
Yamaha	Outboard motor 2 stroke 4 stroke	1 year limited warranty 3 year limited warranty



# Glastron Limited Warranty

**Glastron Boats** warrants to you, the First Retail Purchaser of a new Glastron boat bought from a factory authorized North American dealer, that it will repair or replace defects in materials or workmanship within the applicable Warranty Periods, subject to the "What This Warranty Does NOT Cover" section set forth below.

The applicable Warranty Period runs from the date of delivery to the first retail customer provided that the boat is delivered within twelve (12) months from the date of manufacture. For boats delivered more than twelve (12) months after the date of manufacture, coverage will run from the date of manufacture and the First Retail Purchaser will be entitled to the coverage remaining under the Warranty Periods. All warranties run concurrently.

Structural defects in the hull: Lifetime Limited Warranty

**Defects in factory installed non-structural parts & components:** Two (2) year Warranty Period

This warranty extends only to the First Retail Purchaser, but may be transferred to a second owner subject to other terms, limitations, and exclusions of the Glastron Limited Warranty. For a transfer fee of \$2.50 and the submittal of the Warranty Transfer Application, the Second Retail Purchaser may obtain a warranty for structural defects in the hull (the available warranty coverage period is the balance of 10 years from the date of the original purchase by the First Retail Purchaser) and factory installed non-structural parts and components (the available warranty coverage period is the balance of 2 years from the date of the original purchase by the First Retail Purchaser). The Warranty Transfer Application must be received by Glastron within 30 days of purchase by the Second Retail Purchaser. Proof of purchase date is required. The warranty may only be transferred once.

Your sole and exclusive remedy is the repair or replacement, at Glastron's sole option, of parts and components covered by this warranty.

This Glastron boat, including any alleged defective part, must be returned to an authorized Glastron dealer within the applicable warranty period to obtain warranty service. The Glastron dealer will carry out the warranty procedures on the owner's behalf. All warranty work will be performed at an authorized dealer, or at another repair facility that Glastron selects. The owner is responsible for the expense associated with transporting the boat to and from the repair facility.

An action for breach of warranty shall be barred unless it is commenced within four (4) years from the date the cause of action accrues. An action for breach of any duty or obligation to repair or replace shall be barred unless it is commenced within one year from the date the cause of action accrues regardless of the time remaining in the Warranty Period.

#### WHAT IS NOT COVERED:

This Warranty does not cover:

- A boat purchased from any party other than an authorized Glastron dealer.
- A boat, including its components that have been altered or modified so as to adversely affect its operation, performance or durability.
- 3. Engines, outdrive, controls, propellers, batteries, appliances and other equipment or accessories that are not manufactured by Glastron, whether or not warranted by other manufacturers.
- Gelcoat finishes (including blistering and osmotic blistering, cracking crazing or discoloration), mirrors, window glass, varnishes, paints, fabrics, chromium plated and stainless steel finishes, because of the varying affects resulting from different climatic and use conditions.
- The cost of removal or re-instatement of parts or disassembly of units to repair or replace components covered by this warranty.
  Any boat which has been misused, used in a negligent
- 6. Any boat which has been misused, used in a negligent manner, used for racing, used for rental, charter, military or other commercial purposes, used without normal maintenance, operated contrary to any instruction furnished by Glastron, or operated in violation of any Federal, State, Coast Guard or other governmental agency laws, rules or regulations.
- Any representation relating to speed, range, fuel consumption or other estimated performance characteristic.
- Characteristic.
   Loss of time, inconvenience, boat payments, retail charges, improper lifting or trailering, travel expense, loss of use, in-and-out-of-water charges, towing and storage charges, loss of or damage to personal property, or other remedies not specifically allowed.
- Dealer preparation, cleaning, final adjustments and alignments in preparing the boat for delivery or commissioning
- commissioning.

  10. Leakage around windshield, hatches or other designed openings.
- 11. Fit and adjustment of exterior canvas tops, enclosures, and weather covers.
- 12. Sacrificial deterioration of anti-fouling paint or zinc anodes.

Remedy under this warranty is expressly limited to repair or replacement of defects in materials or workmanship, and does not include incidental or consequential damages which are specially DISCLAIMED. NOTE: SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. The express limited warranty described on previous page is exclusive. All IMPLIED WARRANTIES ARE LIMITED IN THEIR DURATION TO THE ONE (1) YEAR WARRANTY PERIOD. ALL IMPLIED WARRANTIES, INCLUDING MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED IN THEIR ENTIRETY AFTER EXPIRATION OF THE ONE (1) YEAR WARRANTY PERIOD. There are no warranties which extend beyond the description of the face hereof. NOTE: SOME STATES DO NOT ALLOW LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This document contains the entire warranty given by Glastron. Glastron does not authorize any person or persons, including its Glastron dealers, to change the terms of this express limited warranty, which is Glastron's **only** warranty. Glastron reserves the right to change or improve the design or manufacture of Glastron boats without obligation to modify any boat previously manufactured.



#### VEC<sup>®</sup> Lifetime **Limited Warranty**

**Glastron Boats** warrants to you, the first retail purchaser of this boat manufactured with VEC® technology, that it will repair or replace defects in materials or workmanship that occur within the applicable Warranty Periods, subject to the "What This Warranty Does Not Cover" section on the following page. The applicable Warranty Periods run from the date of purchase to the first retail customer provided that the boat is delivered within twelve (12) months from the date of dealer invoice. For boats delivered more than twelve (12) months after the date of invoice, coverage will run from the date of invoice and the first retail purchaser will be entitled to the coverage remaining under the Warranty Periods. All warranties run concurrently,

Warranty Periods:

Structural defects in the hull, deck, floor, stringers and transom: Lifetime Limited Warranty

Defects in factory installed non-structural parts and components: Two (2) year Warranty Period

Defects in gelcoat cosmetics, including cracking, crazing,

discoloration and fading: One (1) year Warranty Period

Defects causing gelcoat blistering: Five (5) year Warranty Period,
except that Glastron shall have no liability or responsibility to correct
or repair any damage if the original gel surface has been altered in
any way, including repair, application of any coating other than marine anti-fouling bottom paint, improper surface preparation for paint, or excessive sanding or sandblasting

This warranty extends only to the First Retail Purchaser but may be transferred to a second owner subject to other terms, limitations, and exclusions of the Glastron Limited Warranty. For a transfer fee of \$250 and the submittal of the Warranty Transfer Application, the Second Retail Purchaser may obtain a warranty for structural defects in the hull, deck, floor, stringers, and transom (the available warranty coverage period is the balance of 10 years from the date of the original purchase by the First Retail Purchaser) and factory installed non-structural parts and components (the available warranty coverage period is the balance of 2 years from the date of the original purchase by the First Retail Purchaser). The Warranty Transfer Application must be received by Glastron within 30 days of purchase by the Second Retail Purchaser. Proof of purchase date is required. The warranty may only be transferred once.

Your sole and exclusive remedy is the repair or replacement, at its sole option, of parts and components covered by this warranty.

This Glastron boat, including any alleged defective part, must be returned to an authorized Glastron dealer within the applicable warranty period to obtain warranty service. The Glastron dealer will carry out the warranty procedures on the owner's behalf. All warranty work will be performed at an authorized dealer, at the Glastron factory, or at another repair facility that Glastron selects. The owner is responsible for the expense associated with transporting the boat to and from the repair facility.

An action for breach of warranty shall be barred unless it is commenced within four (4) years from the date the cause of action accrues. An action for breach of any duty or obligation to repair or replace shall be barred unless it is commenced within one (1) year from the date the cause of action accrues regardless of the time remaining in the Warranty Period.

What This Warranty Does Not Cover:

A boat purchased from any party other than an authorized Glastron dealer.

A boat, including its components, that has been altered or modified so as to adversely affect its operation, performance or durability.

Dealer or customer installed parts or components, or any damage to the boat due to installation of aftermarket parts and components..

Engines, outdrives, controls, propellers, batteries and 4. other equipment or accessories that are not manufactured by Glastron, whether or not warranted by other manufacturers.

Windshield breakage and leakage around windshields,

hatches or other designed openings.

Any boat that has been misused, used in a negligent manner, used for racing, used for rental or other commercial purposes, used without normal maintenance, operated contrary to any instruction furnished by Glastron, involved in an accident, or operated in violation of any Federal, State, Coast Guard or other governmental agency laws, rules or regulations.

Weight, speed, fuel consumption, or other estimated

performance characteristic.

Loss of time, inconvenience, boat payments, retail charges, travel expense, loss of use, haul out, launch, towing and storage charges, loss of or damage to personal property, or other remedies not specifically allowed.

A boat that has been overpowered according to the maximum recommended engine horsepower specified

on the capacity plate. 10.

Canvas, zippers, vinyl, upholstery, plastics, fabric, or trim. 11.

Dealer preparation, cleaning, final adjustments and alignments in preparing the boat for delivery. Repairs made necessary due to inadequate trailering or trailer support, or trailers that are improperly assembled, designed or adjusted.

Remedy under this warranty is expressly limited to repair or replacement of defects in materials or workmanship, **and does not include incidental or consequential damages** that are specifically **DISCLAIMED.** Note: SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTIAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. The THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. The express limited warranty described above is exclusive. All IMPLIED WARRANTIES are LIMITED IN THEIR DURATION TO TWO (2) YEARS FROM THE DATE OF PURCHASE. IMPLIED WARRANTIES (IF ANY) INCLUDING MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED IN THEIR ENTIRETY AFTER TWO (2) YEARS FROM THE DATE OF PURCHASE. There are no warranties which extend beyond the description on the face hereof. NOTE: SOME STATES DO NOT ALLOW LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS SO THE ABOVE LIMITATION MAY NOT AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS WHICH VARY FROM STATE TO STATE.

This document contains the entire warranty given by Glastron. Glastron does not authorize any person or persons, including Glastron dealers, to change the terms of this express limited warranty, which is Glastron's only warranty. Glastron reserves the right to change or improve the design or manufacture of Glastron boats without obligation to modify any boat previously manufactured.



#### Features & Benefits Summary

#### FEATURES:

#### **BENEFITS:**

1. 50-year legacy of innovation

Glastron® was the first company to produce fiberglass boats on a large scale; no other manufacturer has as many product innovations and as many technological breakthroughs

2. Performance

With a Glastron boat, performance is designed in from the start

3. Patented SSV® hull design

Quick planing; superior handling; enhanced fuel economy

4. VEC® construction on 17, 18, 19 and 20-foot runabout models

State-of-the-art technology with lifetime limited warranty on structural components

5. Unitized deck/floor construction on all runabout models

Clean, seamless appearance; greater structural integrity; smooth, quiet, responsive ride

6. Unitized hull & stringer system on many runabout models

Stronger, lighter, won't rot

7. Key structural areas are Double strength in these reinforced with multiaxial knitted fiberglass

important areas

8. All deck fittings are backed by under-deck supports fiberglassed into deck

Strength; durability

9. Aircraft locknuts on bolts

Strength; long-term durability

10. One-piece, lock looped Better appearance; no marine-grade carpet

seams

**11.** Marine-grade vinyl; marine-grade stitching **UV** protected

12. Ski locker drain in subfloor

Lets water drain into bilge, keeping locker dry

13. Tilt steering wheel standard on most models

More comfortable steering position

14. Individual Faria® analog gauges

Easy-to-read; lifetime warranty

15. Gas fill is located on side of boat (never over swim platform) Eliminates risk of fuel spilling onto swim platform

**16.** Low, built-in swim platform with stainless steel boarding ladder

Ease of boarding

17. Boarding ladder on runabouts is located on starboard side of swim platform

Allows driver to see skier at all times when circling for pickup

18. Each model is carefully designed for the proper weight-tohorsepower ratio

Better planing time; better fuel economy; better top speed

**19.** Choice of MerCruiser® or Volvo Penta® sterndrive power

Customer can select preferred brand


**20.** Choice of Mercury<sup>®</sup>, Yamaha<sup>®</sup>, Evinrude<sup>®</sup> or Johnson® on all outboard models

Customer can select preferred brand



#### Canvas Choices






Soft Top Bimini Top





Canvas Package

Camper Canvas Package





Bow Cover

Mooring Cover

MX models feature blue Sunbrella® canvas.

Cockpit Cover

SX, GX, GXL, GX Ski & Fish, and Deck Boat models feature Sunbrella® canvas color-matched to the boat's exterior.

GS Sport Cruisers feature navy Sunbrella® canvas.

#### **Seating Choices**



Sport Seating (SL)



Ski & Fish Seating (SF)



U-Shaped Seating (U)

Sport Seating (SL) standard on MX models, SX models, plus 18 and 20-foot GX models.

U-Shaped Seating (U) standard on GX 235, GX 255, GXL 205 and GXL 205 Collector's Edition.



#### **EZ Loader Custom Boat Trailers**

Glastron Boat Model	Trailer Model	Axle(s)
MX 170	GL 175E	Single
MX 175 3.0's	GL 175E	Single
MX 175 4.3's	TRST 2800	Single
MX 195	TRST 3500*	Single w/Brakes
SX 170	GL 175ST	Single
SX 175 3.0's	GL 175ST	Single
SX 175 4.3's	EXL 2700	Single
SX 195	TRST 3500*	Single w/Brakes
GX 180	TRST 2900	Single
GX 180 SF	TRST 2900	Single
GX 185	TRST 3000*	Single w/Brakes
GX 185 SF	TRST 3000*	Single w/Brakes
GX 205	EXL 3500*	Single w/Brakes
GX 205 SF	EXL 4000*	Tandem w/Brakes One Axle
GX 235	EXL 5200*	Tandem w/Brakes One Axle
GX 255	EXL 5800*	Tandem w/Brakes One Axle
GXL 205	EXL 3500*	Tandem w/Brakes One Axle
DX 205	EXL 4000*	Tandem w/Brakes One Axle
DS 215	EXL 5200*	Tandem w/Brakes One Axle
DX 235	EXL 5800*	Tandem w/Brakes One Axle
GS 209	EXL 4000*	Tandem w/Brakes One Axle
GS 219	EXL 4400*	Tandem w/Brakes One Axle
GS 259 (Non-Package)	EXL 7500*	Tandem w/Brakes One Axle
GS 269 (Non-Package)	EXL 7500*	Tandem w/Brakes One Axle
GS 279 (Non-Package)	EXL 7500*	Tandem w/Brakes One Axle

<sup>\*</sup> Brakes on One Axle Standard EXL 3000 up to EXL 7500

2006 Standard EXL Features: Tube Construction, Steel Fenders, Double Bunks, Aluminum Steps, Chrome Rims, Underslung Space Carrier, Swing Tongue Standard on all, Trailers thru the EXL 4000

2006 Standard TRST Features: Tube Construction, Steel Fenders, Single Bunks, Alumalook Wheels, Blackwall Bias Tires, Painted Steel Steps, Swing Tongue Standard on all Trailers thru TRST 3500

#### Standard Galvanized Bunk Trailers Glastron Boat Model Trailer Model

MX 170	EZL96B 15-18 2800NB
MX 175 3.0's	EZL96B 15-18 2800NB
MX 175 4.3's	EZL96B 15-18 2800NB
MX 195	TEZL96B 17-20 4000H1X
SX 170	EZL96B 15-18 2800NB
SX 175 3.0's	EZL96B 15-18 2800NB
SX 175 4.3's	EZL96B 15-18 2800NB
SX 195	TEZL96B 17-20 4000H1X
GX 180	EZL96B 17-20 2800NB
GX 180 SF-	EZL96B 17-20 2800NB
GX 185	EZL96B 17-20 3100H1X
GX 185 SF	EZL96B 17-20 3100H1X
GX 205	TEZL96B 17-20/22 4000H1X
GX 205 SF	TEZL96B 17-20/22 4000H1X
GX 235	TEZL96B 19-22 4700H1X
GX 255	TEZB 23-25/27 5800H1X
GXL 205	TEZL96B 17-20/22 4000H1X
DX 205	TEZL96B 17-20/22 4000H1X
DS 215	TEZL96B 17-20/22 4700H1X
DX 235	TEZB 19-22/24 5200H1X
GS 209	TEZL96B 17-20/22 4000H1X
GS 219	TEZL96B 19-22 4700H1X
GS 259 (Non-Package)	TEZB 23-25/27 5800H1X
GS 269 (Non-Package)	TEZB 23-25/27 7500H1X
GS 279 (Non-Package)	TEZB 23-25/27 7500H1X

#### Standard Aluminum Bunk Trailers **Glastron Boat Model** Trailer Model

MX 170	ALB 16-18 2800NB
MX 175 3.0's	ALB 16-18 2800NB
MX 175 4.3's	ALB 16-18 2800NB
MX 195	TALB 18-21 4000H1X
SX 170	ALB 16-18 2800NB
SX 175 3.0's	ALB 16-18 2800NB
SX 175 4.3's	ALB 16-18 2800NB
SX 195	TALB 18-21 4000H1X
GX 180	ALB 18-20 2800NB
GX 180 SF	ALB 18-20 2800NB
GX 185	ALB 18-20 3100H1X
GX 185 SF	ALB 18-20 3100H1X
GX 205	TALB 18-21 4000H1X
GX 205 SF	TALB 18-21 4000H1X
GX 235	TALB 20-23 4600H1X
GX 255	TALB 21-25 6200H1X
GXL 205	TALB 18-21 4000H1X
DX 205	TALB 18-21 4000H1X
DS 215	TALB 20-23 4600H1X
DX 235	TALB 21-25 6200H1X
GS 209	TALB 18-21 4000H1X
GS 219	TALB 20-23 4600H1X
GS 259 (Non-Package)	TALB 23-27 6200H1X
GS 269 (Non-Package)	TALB 23-27 7900 H1X
GS 279 (Non-Package)	TALB 23-27 7900 H1X

LIMITED OPTIONS OFFERED: Load Guides, Brakes on Second Axle, Brake Flash Kit(s), Roller Upgrade, Spare Tire & Wheel w/Carrier.

UPGRADE PACKAGE (aluminum trailers only): Stainless Steel Fasteners w/Hardwaré, Alum. Fenders, Double Bunks, Available in Tandem and Single Axle.

These options are available through the EZ Loader Division or Distributor that will be shipping the trailer profer.

These options are available through the EZ Loader Division or Distributor that will be shipping the trailer order.

We are offering these limited options to simplify the program and to avoid any delays in shipping. These options will be supplied and invoiced to your dealer by the participating EZ Loader Division or Distributor in the Dealer's area.

# Monthly Payments

Length of Loan	Interest Rate	Payment Per \$1000
3 years	6.00%	30.42
	6.50%	30.65
	7.00%	30.88
	7.50%	31.11
	8.00%	31.34
	8.50%	31.57
. :	9.00%	31.80
5 years	6.00%	19.33
5.5	6.50%	19.57
	7.00%	19.80
	7.50%	20.04
	8.00%	20.28
	8.50%	20.52
	9.00%	20.76
7 years	6.00%	14.61
A CONTRACTOR	6.50%	14.85
	7.00%	15.09
	7.50%	15.34 15.59
	8.00% 8.50%	15.59 15.84
	8.50% 9.00%	15.84 16.09
0	9.00%	13.14
8 years	6.00% 6.50%	13.14 13.39
	6.50% 7.00%	13.63
	7.50% 7.50%	13.88
	7.50% 8.00%	14.14
	8.50%	14.39
	9.00%	14.65
10 years	6.00%	11.10
. Jy Julis	6.50%	11.35
	7.00%	11.61
	7.50%	11.87
	8.00%	12.13
	8.50%	12.40
	9.00%	12.67
12 years	6.00%	9.76
	6.50%	10.02
	7.00%	10.28
	7.50%	10.55
	8.00%	10.82
	8.50%	11.10 11.38
	9.00%	
15 years	6.00%	8.44
	6.50%	8.71
	7.00%	8.99 9.27
	7.50%	9.27
	8.00%	9.56
	8.50%	9.85 10.14
	9.00%	IU.14

### Definitions of Measurements

**Length Overall (LOA)** — Distance along the centerline from the tip of the bow to the aft-most part of the hull.

Maximum Beam — Maximum width of the boat.

**Transom Width** — Maximum width of the boat at the transom.

**Depth** — Vertical distance from the lowest point of the keel to the highest point of the boat, excluding windshields, lights and other removable components.

**Transom Deadrise** — Angle of the hull at the transom, as measured in degrees, relative to the water.

**Maximum Depth** — Vertical distance from the lowest point of the keel to the highest point of the boat, including windshields.

**Cockpit Depth** — Vertical distance from the boat floor to the top of gunwale as measured at the driver's seat.

**Length Overall on Trailer** — Distance measured along the boat centerline, from forward-most point of trailer to aft-most point of motor/outdrive.

**Boat Height on Trailer** — Vertical distance from the ground to the highest point of boat, including the windshield.

**Draft (drive unit up)** — Total number of inches of boat and/or motor and drive unit below the waterline. Measured unloaded, with the motor/drive unit in the full up position.

**Draft (drive unit down)** — Total number of inches of boat and/or motor and drive unit below the waterline. Measured unloaded, with the motor/drive unit in the full down position.



Transom Deadrise 21°
LOA on Trailer 21'6" (6.55 m.)
Fuel Capacity 23 gal. (87 L.)
Maximum Load 1800 lbs. (816 kg.)
Max. Persons 7 or 1150 lbs. (522 kg.)
Max. Horsepower 150 (112 kw.)
NMMA Certified

**Draft: A. Drive Unit Up** 15½" (.39 m.) **B. Drive Unit Down** 28½" (.72 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, & fuel
gauges; plus switches for bilge
pump, navigation/anchor lights,
panel lights, horn & accessories
Electric horn
Bilge pump
Navigation lighting
Ski locker
Duel cable steering

Stainless steel boarding ladder 6" cleats Walk-thru curved windshield Fiberglass floor Bow seats w/storage Stainless steel bow & stern eyes Passenger grab handles SL Seating: 2 buckets seats/aft bench seat/sunlounge Molded swim platform

#### Options

Color-coordinated Sunbrella soft top & boot Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain Color-coordinated Sunbrella Bimini top w/boot Color-coordinated Sunbrella cockpit cover

Color-coordinated Sunbrella bow cover Mooring cover Snap-in carpet Ski tow pylon AM/FM/CD stereo w/2 speakers & glove box S0th Anniversary Package: snap-in carpet, Bimini top & AM/FM/CD stereo w/2 speakers & glove box

#### Color Choices

White w/Blue Graphics

#### **Engine Choices**

Johnson 90 PLSD	Mercury 90 ELPT Optimax
Johnson 115 PLSD	Mercury 115 ELPT Optimax
Johnson 150 PLSD	Mercury 135 L Optimax
•	Mercury 150 L Optimax
Eyinrude 115 DSLSD	,
Evinrude 130 DSLSD	Yamaha 90 TLRD
Evinrude 150 DSLSD	Yamaha 115 TLRD
	Yamaha F 115 TLRD
	Yamaha 150 TLRD
	Yamaha F 150 TLRD

#### Performance

Engine: Johnson 115 FastStrike, Prop: 14 x 19			
RPM	MPH	GPH	RANGE <sup>2</sup>
2500	15	2.9	107
3200	25	4.2	123
4200	35	6.3	115
WOT	43-45	_	
Time to plane: 3.5 sec.			

Engine: Johnson 150 FastStrike, Prop: 14½ x 19			
RPM	MPH	GPH	RANGE*
2400	15	3.7	84
3300	30	5.0	124
4500	40	7.5	110
WOT	49-52		_
Time to plane: 3.2 sec.			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	_H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL PRICE	\$



LOA 17' 1" (5.21 m.) Beam 88" (2.24 m.) Depth 44" (1.12 m.) Maximum Depth 57" (1.45 m.) Cockpit Depth 28%" (.72 m.) Approx. Wt. 2300 lbs. (1043 kg.) w/3.0 GL Volvo Penta® Transom Width 86" (2.18 m.) Transom Deadrise 21° LOA on Trailer 21' 10" (6.65 m.) Fuel Capacity 23 gal. (87 L.) Maximum Load 1100 lbs. (499 kg.) Max. Persons 7 or 1000 lbs. (454 kg.) NMMA Certified

Draft: A. Drive Unit Up 16" (.41 m.)
B. Drive Unit Down 31" (.79 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel, oil pressure, voltmeter &
engine temperature gauges; plus
switches for bilge pump, blower,
horn & lights
Electric horn
Bilge pump & blower
Navigation lighting
Ski locker
Ski tow ring

Stainless steel boarding ladder
Stainless steel bow eye & stern eyes
6" cleats
Walk-thru curved windshield
Bow seats w/storage
Fiberglass floor
Passenger grab handles
Molded swim platform
Merc/Volvo prop
SL seating: 2 bucket seats/aft bench
seat/sunlounge

#### **Options**

Color-coordinated Sunbrella soft top & boot
Color-coordinated Sunbrella
Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella Bimini top w/boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover

Mooring cover
AM/FM/CD stereo w/2 speakers
& glove box
Snap-in carpet
High altitude prop
50th Anniversary Package:
snap-in carpet, Bimini top &
AM/FM/CD stereo w/2 speakers
& glove box

#### Color Choices

White w/Blue Graphics

#### **Engine Choices**

3.0L MerCruiser (WPS) (135) 4.3L MerCruiser (190)

3.0 GL Volvo Penta (WPS) (135) 4.3 GL Volvo Penta (190)

#### Performance

Engine: 3.0L MerCi	ruiser, Prop: 14¼ x 2	21	
RPM	MPH	GPH	RANGE*
2000	8	_	_
3000	22	_	_
4000	34		
WOT	40-42	_	_
Time to plane: 3.8 s	ec.		

 Engine: 3.0 GL Volvo Penta, Prop: 14¼ x 21

 RPM
 MPH
 GPH
 RANGE\*

 2000
 9
 —
 —

 3000
 25
 —
 —

 4000
 38
 —
 —

 WOT
 41-44
 —
 —

Time to plane: 3.5 sec.

Engine: 4.3 GL Volv	o Penta, Prop: 14½	x 23	
RPM	MPH	GPH	RANGE*
2000	9		_
3000	31	_	
4000	46		_
WOT	50-53	-	_
Time to plane: 3,3 se			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	H.P.	
Trailer		
Accessories		•
T, T & L		
	TOTAL PRI	CF \$



LOA 19' 4" (5.89 m.)
Beam 92" (2.33 m.)
Depth 43" (1.09 m.)
Maximum Depth 56" (1.42 m.)
Cockpit Depth 29" (.74 m.)
Approx. Wt. 2975 lbs. (1349 kg.)
w/5.0 GL Volvo Penta®

Transom Width N/A
Transom Deadrise 21°
LOA on Trailer 24' 6" (7.46 m.)
Fuel Capacity 35 gal. (132 L.)
Maximum Load 1275 lbs. (578 kg.)
Max. Persons 8 or 1275 lbs. (578 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 16½" (.42 m.) **B. Drive Unit Down** 31½" (.80 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel, oil pressure, voltmeter &
engine temperature gauges; plus
switches for bilge pump, blower,
horn & lights
Electric horn
Bilge pump & blower
Navigation lighting
AM/FM/CD stereo w/2
speakers & glove box
Ski locker

Ski tow ring
Fiberglass floor
Telescopic 3-step boarding ladder
Stainless steel bow & stern eyes
6" cleats
Walk-thru curved windshield
Bow seats w/storage
Passenger grab handles
SL Seating: 2 buckets seats/aft
bench seat/sunlounge
Molded swim platform
Merc/Volvo prop

#### **Options**

Color-coordinated Sunbrella

soft top & boot
Color-coordinated Sunbrella
Canvas Package: bow cover,
walk-thru curtain, side curtains
& stern curtain
Color-coordinated Sunbrella
Bimini top w/boot
Color-coordinated Sunbrella
cockpit cover
Color-coordinated Sunbrella

Mooring cover
Convenience Package: hour
meter, depth sounder &
automatic bilge pump
Tilt steering
High altitude prop
Snap-in carpet
50th Anniversary Package: tilt
steering, snap-in carpet, Bimini
top & convenience package

#### Color Choices

White w/Blue Graphics

bow cover

#### **Engine Choices**

3.0L MerCruiser (WPS) (135) 4.3L MerCruiser (190) 4.3L MPI MerCruiser (220) 5.0L MerCruiser (220) 5.0L MPI MerCruiser (260)	3.0 GL Volvo Penta (WPS) (135) 4.3 GL Volvo Penta (190) 4.3 GXi Volvo Penta (225) 5.0 GL Volvo Penta (220) 5.0 GXi Volvo Penta (270)

#### Performance

Engine: 5.0 GL Vol	vo Penta, Prop: 14¼	x 19	
RPM	MPH	GPH	RANGE*
2000	11	_	_
3000	31		_
4000	48	_	
WOT	50-54	-	_
Time to plane: 2.7 s	ec.		

5.0 GXi Volvo Pent			
RPM	MPH	GPH	RANGE*
2000	13	3.6	109
3000	31	6.5	149
4000	45	11.0	130
WOT	55-58	_	_
Time to plane: 2.8 s	ec.		

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$ <u>·</u>
Motor	_H.P.	
Trailer		
Accessories		- AAAA
T, T & L		
	TOTAL PRICE	· <b>c</b>



LOA 17' 1" (5.21 m.)
Beam 88" (2.24 m.)
Depth 43" (1.09 m.)
Maximum Depth 59" (1.50 m.)
Cockpit Depth 28½" (.72 m.)
Approx. Wt. 1500 lbs. (680 kg.)
w/o engine

Transom Width 86" (2.18 m.)

Transom Deadrise 21°
LOA on Trailer 21' 6" (6.55 m.)
Fuel Capacity 23 gal. (87 L.)
Maximum Load 1800 lbs. (816 kg.)
Max. Persons 8 or 1150 lbs. (522 kg.)
Max. Horsepower 150 (112 kw.)
NMMA Certified

Draft: A. Drive Unit Up 15½" (.39 m.) B. Drive Unit Down 28½" (.72 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, & fuel
gauges; plus switches for bilge
pump, navigation/anchor lights,
panel lights, horn & accessories
Electric horn
Bilge pump
Navigation lighting
AM/FM/CD stereo w/2 speakers &
glove box
Ski locker
Snap-in carpet
Dual cable steering

6" cleats
Walk-thru curved windshield
Fiberglass floor
Bow seats w/storage
Stainless steel bow & stern eyes
Stainless steel grab handles
Stainless steel boarding ladder
Two-tone metallic paint
Passenger grab handles
SL Seating: 2 buckets seats/aft
bench seat/sunlounge
Molded swim platform

#### **Options**

Color-coordinated Sunbrella soft top & boot
Color-coordinated Sunbrella
Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella
Bimini top w/boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover
Mooring cover

Full side glass wings
Telescopic 3-step boarding ladder
Tilt steering
Ski tow pylon
Flip-up bucket seat - (1) each
Convenience Package: automatic
bilge pump, hour meter & depth
sounder
50th Anniversary Package: 3-step
ladder, tilt steering, full side glass
wings, Bimini top & convenience

#### **Color Choices**

White w/Jet Black Metallic White w/Sapphire Blue Metallic White w/Jade Green Metallic White w/Crimson Red Metallic

package

#### **Engine Choices**

Johnson 90 PLSD Johnson 115 PLSD Johnson 150 PLSD	Mercury 90 ELPT Optimax Mercury 115 ELPT Optimax Mercury 135 L Optimax Mercury 150 L Optimax
Evinrude 115 DSLSD Evinrude 130 DSLSD Evinrude 150 DSLSD	Yamaha 90 TLRD Yamaha 115 TLRD Yamaha F 115 TLRD Yamaha 150 TLRD Yamaha F 150 TLRD

#### Performance

Engine: Johnson 115 FastStrike, Prop: 14 x 19			
RPM	MPH	GPH	RANGE*
2500	15	2.9	107
3200	25	4.2	123
4200	35	6.3	115
WOT	43-45	_	
Time to plane: 3.5 sec			

Engine: Johnson 15			
RPM	MPH	GPH	RANGE*
2400	15	3.7	84
3300	30	5.0	124
4500	40	7.5	110
WOT	49-52	_	

Time to plane: 3.2 sec.

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

3

Boat			\$
Motor	H.P.		
Trailer			
Accessories			
T, T & L			
	TOTAL	PRICE	\$



LOA 17' 1" (5.21 m.)

Beam 88" (2.24 m.)

Depth 44" (1.12 m.)

Maximum Depth 59" (1.50 m.)

Cockpit Depth 28½" (.73 m.)

Approx. Wt. 2335 lbs. (1059 kg.)

w/3.0 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 86" (2.18 m.)
LOA on Trailer 21' 10" (6.65 m.)
Fuel Capacity 23 gal. (87 l.)
Maximum Load 1150 lbs. (522 kg.)
Max. Persons 8 or 1150 lbs. (522 kg.)
NMMA Certified

Draft: A. Drive Unit Up 16" (.41 m.) B. Drive Unit Down 31" (.79 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel, oil pressure, voltmeter &
engine temperature gauges; plus
switches for bilge pump, blower,
horn & lights
Electric horn
Bilge pump & blower
Navigation lighting
AM/FM/CD stereo w/2 speakers &
glove box
Ski locker
Ski tow ring
Snap-in carpet

Stainless steel boarding ladder
Stainless steel bow eye & stern eyes
Stainless steel grab handles
6" cleats
Walk-thru curved windshield
Bow seats w/storage
Fiberglass floor
Passenger grab handles
SL seating: 2 bucket seats/aft bench seat/sunlounge
Molded swim platform
Merc/Volvo prop
Two-tone metallic paint

#### **Options**

Color-coordinated Sunbrella soft top & boot
Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella Bimini top w/boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover
Mooring cover

Convenience Package:
hour meter, depth sounder,
& automatic bilge pump
Full side glass wings
High altitude prop
Tilt steering
Telescopic 3-step boarding ladder
Flip-up bucket seat — (1) each
50th Anniversary Package: telescopic
3-step ladder, tilt steering, full side
glass wings, Bimini top &
convenience package

#### Color Choices

White w/Jet Black Metallic White w/Sapphire Blue Metallic White w/Jade Green Metallic White w/Crimson Red Metallic

#### **Engine Choices**

3.0L MerCruiser (WPS) (135) 4.3L MerCruiser (190) 3.0 GL Volvo Penta (WPS) (135) 4.3 GL Volvo Penta (190)

#### Performance

RPM	MPH	GPH	RANGE*
2000	8	_	
3000	22		_
4000	34	_	_
WOT	40-42	_	

Engine: 3.0 GL Volv	o Penta, Prop: 14¼	x 21	
RPM	MPH	GPH	RANGE*
2000	9		Name of the latest and the latest an
3000	25	_	-
4000	38		_
WOT	41-44	_	
Time to plane: 3.5 s	ec.		

RPM	MPH	GPH	RANGE*
2000	9		
3000	31	_	_
4000	46	_	_
WOT	50-53		_

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above,

and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	Н.Р.	
Trailer		Manager 1 and 1 an
Accessories		
T, T & L		
	TOTAL	PRICE \$



LOA 19' 4" (5.89 m.)
Beam 92" (2.33 m.)
Depth 43" (1.09 m.)
Maximum Depth 56" (1.42 m.)
Cockpit Depth 29" (.74 m.)
Approx. Wt. 2750 lbs. (1247 kg.)
w/4.3L MerCruiser®

Transom Deadrise 21°
Transom Width N/A
LOA on Trailer 24' 6" (7.46 m.)
Fuel Capacity 35 gal. (132 L.)
Maximum Load 1275 lbs. (578 kg.)
Max. Persons 9 or 1275 lbs. (578 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 16½" (.42 m.) **B. Drive Unit Down** 31½" (.80 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel, oil pressure, voltmeter &
engine temperature gauges; plus
switches for bilge pump, blower,
horn & lights
Electric horn
Bilge pump & blower
Navigation lighting
AM/FM/CD stereo w/2 speakers &
glove box
Ski locker
Ski tow ring

Fiberglass floor
Snap-in carpet
Stainless steel bow eye & stern eyes
Walk-thru curved windshield
Bow seats w/storage
Passenger grab handles
SL seating: 2 bucket seats/aft bench seat/sunlounge
6" cleats
Molded swim platform
Telescopic 3-step boarding ladder
Merc/Volvo prop
Two-tone metallic paint

#### **Options**

Color-coordinated Sunbrella soft top & boot
Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella Bimini top w/boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover
Extended swim platform

Mooring cover
Convenience Package: hour
meter, depth sounder & automatic
bilge pump
Full side glass wings
Tilt steering
High altitude prop
Flip-up bucket seat — (1) each
Wakeboard tower
50th Anniversary Package: tilt
steering, full side glass wings,
Bimini top & convenience package

#### Color Choices

White w/Jet Black Metallic White w/Sapphire Blue Metallic White w/Jade Green Metallic White w/Crimson Red Metallic

#### **Engine Choices**

3.0L MerCruiser (WPS) (135)	3.0 GL Volvo Penta (WPS) (135)
4.3L MerCruiser (190)	4.3 GL Volvo Penta (190)
4.3L MPI MerCruiser (220)	4.3 GXi Volvo Penta (225)
5.0L MerCruiser (220)	5.0 Gl. Volvo Penta (220)
5.0L MPI MerCruiser (260)	5.0 GXi Volvo Penta (270)

#### Performance

Engine: 5.0 GL Vol	vo Penta, Prop: 14¼	x 19	
RPM	MPH	GPH	RANGE*
2000	11		
3000	31	_	_
4000	48		
WOT	50-54	_	
Time to plane: 2.7 s	ec.		
5.0 GXi Volvo Pent	a. Prop. 14% v 21		

or our voivo i circa, i	10p. 14/4 A & 1		
RPM	MPH	GPH	RANGE*
2000	13	3.6	109
3000	31	6.5	149
4000	45	11.0	130
WOT	55-58		_
Time to plane: 2.8 sec.			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above,

and based on 90 percent of boat's fuel capacity.

Boat	\$
MotorH.P.	· · · · · · · · · · · · · · · · · · ·
Trailer	
Accessories	
T, T & L	
. то	OTAL PRICE S



LOA 18' (5.49 m.)
Beam 91" (2.31 m.)
Depth 43" (1.09 m.)
Maximum Depth 53" (1.35 m.)
Cockpit Depth 29½" (.75 m.)
Approx. Wt. 1710 lbs. (776 kg.)
w/o engine
Transom Width 86" (2.18 m.)

Transom Deadrise 21°
LOA on Trailer 22' 2" (6.76 m.)
Fuel Capacity 29 gal. (110 L.)
Maximum Load 1880 lbs. (853 kg.)
Max. Persons 8 or 1225 lbs. (556 kg.)
Max. Horsepower 150 (112 kw.)
NMMA Certified

Draft: A. Drive Unit Up 16" (.41 m.) B. Drive Unit Down 29" (.74 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel & trim gauges; plus switches
for bilge pump, navigation/anchor
lights, panel lights, horn &
accessories
Bilge pump
Clarion AM/FM/CD stereo
w/4 speakers
Glove box
Tilt steering
Telescopic 3-step boarding ladder
Dual cable steering
Snap-in carpet

6" cleats
Stainless steel bow eye & stern eyes
Walk-thru curved glass windshield
w/open side wings
Stainless steel grab handles
SuspensionAire adjustable bucket
seats w/flip-up bolsters/aft bench
seat/sunlounge
Molded swim platform
Hinged ski locker
Courtesy lights
Electric horn
Navigation lighting

#### **Options**

Color-coordinated Sunbrella

Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella Bimini top w/boot
Color-coordinated Sunbrella soft top & boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover
Mooring cover

Convenience Package: hour meter, depth sounder & automatic bilge pump
Ski tow pylon
Stereo remote for dash
Sirius satellite radio
Two-tone metallic paint (black, blue, green & red)
Low profile black windshield
Full side glass wings
50th Anniversary Package: two-tone metallic paint, full side glass wings & convenience package

#### Color Choices

White w/Charcoal graphics

999999999999999999999

#### **Engine Choices**

Johnson 115 PLSD Johnson 150 PLSD	Mercury 115 ELPT Optimax Mercury 115 ELPT EFI 4 Stroke
JOHNSON 130 1 E3D	Mercury 135 L Optimax
Evinrude 115 DSLSD	Mercury 150 L Optimax
Evinrude 130 DSLSD	
Evinrude 150 DSLSD	Yamaha 115 TLRD
	Yamaha F 115 TLRD
	Yamaha 150 TLRD
	Yamaha F 150 TLRD

#### Performance

Engine: 115 Johnson,	Prop: 14 x 19		
RPM	MPH	GPH	RANGE*
2500	15	3.6	108
3300	25	4.6	142
4700	35	7.2	127
WOT	42-44		_
Time to plane: 3.2 sec			

•			
Engine: 135 Optim RPM	ax Mercury (V6), Pi MPH	op: 14% x 21 GPH	RANGE*
2400	15	4.2	93
3000	25	5.1	128
4000	35	7.1	129
WOT	46-49		

Time to plane: 3.1 sec.

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat	\$
MotorH	
Trailer	
Accessories	,
T, T & L	,
	TOTAL PRICE \$



LOA 18' (5.49 m.)
Beam 91" (2.31 m.)
Depth 43" (1.09 m.)
Maximum Depth 53" (1.35 m.)
Cockpit Depth 29½" (.75 m.)
Approx. Wt. 2750 lbs. (1247 kg.)
W/4.3 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 86" (2.18 m.)
LOA on Trailer 22' 4" (6.81 m.)
Fuel Capacity 29 gal. (110 L.)
Maximum Load 1200 lbs. (544 kg.)
Max. Persons 8 or 1200 lbs. (544 kg.)
NMMA Certified

Draft: A. Drive Unit Up 16" (.41 m.)
B. Drive Unit Down 29" (.74 m.)

#### Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel, oil pressure, voltmeter &
engine temperature gauges; plus
switches for bilge pump, blower,
horn, lights & accessories
Bilge pump
Electric horn
Navigation lighting
Clarion AM/FM/CD stereo
w/4 speakers
Glove box
Ski tow ring
Hinged ski locker
Stainless steel bow eye & stern eyes

Unitized fiberglass deck/floor
Snap-in carpet
Walk-thru curved windshield w/open
side wings
Stainless steel passenger
grab handles
SL Seating: SuspensionAire
adjustable bucket seats w/flip-up
bolsters/aft bench seat/sunlounge
Molded swim platform
6" cleats
Telescopic 3-step boarding ladder
Merc/Volvo prop
Courtesy lights
Tilt steering

#### Options

Color-coordinated Sunbrella soft top & boot w/concealed storage Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain Color-coordinated Sunbrella Bimini top w/boot Color-coordinated Sunbrella cockpit cover Color-coordinated Sunbrella bow cover Mooring cover Convenience package: hour meter, depth sounder & automatic bilge pump

Stereo remote for dash High altitude prop Extended swim platform Sirius satellite radio Full side glass wings Wakeboard tower Two-tone metallic paint (black, blue, green & red) Low profile black windshield SS Upgrade package: SS rubrail, docking lights, pull-up cleats, transom-mounted stereo remote & tilt/trim switch 50th Anniversary Package: two-tone metallic paint, full side glass wings & convenience package

#### Color Choices

White w/Charcoal graphics

tone covings

#### **Engine Choices**

3.0L MerCruiser (WPS) (135)
4.3L MerCruiser (190)
4.3L MPI MerCruiser (220)
3.0 GL Volvo Penta (WPS) (135)
4.3 GL Volvo Penta (190)
4.3 GXi Volvo Penta (225)

#### Performance

Engine: 3.0L MerCruiser			
RPM	MPH	GPH	RANGE*
2100	15	2.5	157
2900	25	3.5	186
3500	35	7.4	123
WOT	42-44	_	
Time to plane: 3.4 sec.			

Engine: 3.0 GL Volvo P RPM	enta, Prop: 14½ x MPH	19 GPH	RANGE*
*** ***	10	2.1	124
2000			163
3000	20	3.2	
4000	35	7.6	120
WOT	41-43	_	_
Time to plane: 3.7 sec.			

Engine: 4.3L MPI Me	DANCE		
RPM	MPH	GPH	RANGE*
2000	10	4.0	67
3000	30	6.5	119
4000	43	11.1	101
WOT	50-52	_	

Time to plane: 3.5 se	с.		
Engine: 4.3 GXi Vo	lvo Penta, Prop: 147	4 x 19	
RPM	MPH	GPH	RANGE'
2500	24	3.5	179
3500	38	8.1	122
WOT	49-52	_	_

WOT Time to plane: 2.9 sec.

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL PRI	CE \$



LOA 19' 11" (6.07 m.)

Beam 96" (2.44 m.)

Depth 45¾" (1.16 m.)

Maximum Depth 56¾" (1.44 m.)

Cockpit Depth 32" (.81 m.)

Approx. Wt. 3045 lbs. (1381 kg.)

w/5.0 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 92" (2.34 m.)
LOA on Trailer 24' 9" (7.54 m.)
Fuel Capacity 35 gal. (132 L.)
Maximum Load 1475 lbs. (669 kg.)
Max. Persons 10 or 1475 lbs. (669 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 16½" (.42 m.) **B. Drive Unit Down** 31½" (.80 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories; hour meter & depth sounder Automatic bilge pump Electric horn Clarion AM/FM/CD stereo w/4 speakers Glove box Hinged ski locker Ski tow ring Stainless steel bow eye & stern eyes 6" cleats

Walk-thru curved full glass windshield Unitized fiberglass deck/floor Snap-in carpet Bow seats w/hinged bow backrest w/storage Courtesy lights Stainless steel passenger grab handles SL Seating: SuspensionAire adjustable bucket seats w/flip-up bolsters/aft bench seat/sunlounge Molded swim platform Merc/Volvo prop Tilt steering Telescopic 3-step boarding ladder Two-tone metallic paint

#### **Options**

Color-coordinated Sunbrella soft top & boot w/concealed storage
Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella Bimini top w/boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover
Mooring cover
Mooring cover
Mooring cover w/extended swim platform
Extended swim platform

& Quiet II
Stereo remote for dash
U-shaped cockpit seating w/filler cushions
High altitude prop
SS Upgrade Package: SS rubrail, docking
lights, pull-up cleats, transom-mounted
stereo remote & till/trim switch
Sirius satellite radio
Docking lights
Wakeboard tower
Low profile black windshield
S0th Anniversary Package: SS upgrade
package, stereo remote for dash &
extended swim platform

Captain's Call (electric) w/Corsa Quick

#### Color Choices

White w/Jet Black Metallic White w/Sapphire Blue Metallic

44

White w/Jade Green Metallic White w/Crimson Red Metallic

#### **Engine Choices**

4.3 L MerCruiser (190)
4.3 L MPI MerCruiser (220)
4.3 L MPI Bravo III MerCruiser (220)
5.0 L MerCruiser (220)
5.1 MerCruiser (250)
5.7 MerCruiser (250)
5.7 L Bravo III MerCruiser (250)
5.7 L Mag MPI Alpha MerCruiser (300)
4.3 GXi Volvo Penta (225)
4.3 GXi Volvo Penta (225)
5.0 GX Volvo Penta (220)
5.0 GXi Volvo Penta (270)
5.7 GXi Volvo Penta (315)

#### Performance

Engine: 5.0 GL Volvo Pe	nta, Prop: 14%	x 21	
RPM	MPH	GPH	RANGE*
2000	12		_
3000	31		_
4000	45		
WOT	49-52	-	_
Time to plane: 3.0 sec.			

5.0L MerCruiser, Pro RPM	p: 14½ x 19 Alum MPH	ı. (with wakeboar GPH	d tower) RANGE*
2000	9	_	
3000	26	_	_
4000	38	Lighting	-
WOT	44-47	_	_
Time to plane: 3.6 sec			

Engine: 5.7L MerC	ruiser, Prop: 14¼ x 2	21	
RPM	MPH	GPH	RANGE <sup>*</sup>
2200	15	3.3	143
2800	25	4.3	183
3500	35	8.0	138
WOT	52.54		_

Time to plane: 3.1 sec.

うううううううううううりつう

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		3
Motor	_H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL PRICE	: <b>S</b>

LOA 231 (7.01 m.) Beam 102" (2.59 m.) Depth 53" (1.35 m.) Maximum Depth 65" (1.65 m.) Cockpit Depth 37" (.94 m.) Approx. Wt. 3800 lbs. (1724 kg.) w/5.7L MerCruiser®

Transom Deadrise 21° Transom Width 98" (2.49 m.) **LOA on Trailer** 25' 10" (7.87 m.) Fuel Capacity 47 gal. (178 L.) Maximum Load 1650 lbs. (748 kg.) Max Persons 12 or 1650 lbs. (748 kg.) **NMMA** Certified

Draft: A. Drive Unit Up 17½" (.44 m.) B. Drive Unit Down 33" (.84 m.)

Snap-in carpet

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, panel lights, interior lights & horn; hour meter & depth sounder Courtesy lights Electric horn Navigation lighting Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Glove box Hinged ski locker Ski tow ring 6" cleats

Fiberglass floor (bow & cockpit) Molded extended swim platform Walk-thru curved full glass windshield Bow seats w/hinged bow backrest w/storage Automatic bilge pump Stainless steel telescopic 3-step boarding ladder Stainless steel bow eye & stern eyes Merc/Volvo prop Tilt steering SuspensionAire adjustable bucket seats w/flip-up bolsters; U-shaped cockpit seating w/filler cushions; table & sunlounge; walk-thru

transom wake Tower Bim Avail.

**Options** 

Color-coordinated Sunbrella soft top & boot w/concealed storage Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain SS Upgrade Package: SS rubrail, Color-coordinated Sunbrella Bimini top w/boot Color-coordinated Sunbrella cockpit cover Color-coordinated Sunbrella bow cover Mooring cover Bow filler cushions Stereo remote for dash

High altitude prop Captain's Call (electric) w/Corsa Quick & Quiet II Docking lights docking lights, pull-up cleats, transom-mounted stereo remote & tilt/trim switch Yes Wakeboard tower - He Bim. Low profile black windshield 50th Anniversary Package: SS upgrade package, stereo remote for dash & bow filler cushions

#### Color Choices

White w/Jet Black Gelcoat White w/Sapphire Blue Gelcoat

46

White w/Jade Green Gelcoat White w/Crimson Red Gelcoat

#### **Engine Choices**

#### Performance

Engine: 350 Magnum M	PI Bravo I MerCu	iser, Prop: 13¾ x 2	21 Vengeance SS
RPM	MPH	GPH	RANGE*
2000	. 9	4.5	83
3000	29	7.8	160
4000	43	13.3	135
WOT	50-55		deprises
Time to plane: 3.5 sec.			

Engine: 350 Magnum MPI Bravo III MerCruiser, Prop: 26 uncupp			6 uncupped
RPM	MPH	GPH	RANGE*
2500	25	6.5	163
3500	37	10.0	157
WOT	50-53	_	_
Time to plane: N/A			

Engine: 5.7 GXi Volvo Penta, Prop: 14½ x 19			
RPM	MPH	GPH	RANGE*
2000	9	4.3	91
3000	29	7.7	159
4000	41	13.8	127
WOT	50-54	_	_
Time to plane: 3.0 s	ec.		

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions. \*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

2

Boat		\$
Motor	H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL PRIC	'F <b>\$</b>

47

LOA 25' (7.62 m.)
Beam 102" (2.59 m.)
Depth 57½" (1.46 m.)
Maximum Depth 69½" (1.77 m.)
Cockpit Depth 37" (.94 m.)
Approx. Wt. 4600 lbs. (2087 kg.)
w/5.7L MerCruiser®

Transom Deadrise 21°
Transom Width 98" (2.49 m.)
LOA on Trailer 26' 5" (8.05 m.)
Fuel Capacity 56 gal. (212 L.)
Maximum Load 2000 lbs. (907 kg.)
Max Persons 12 or 1800 lbs. (816 kg.)
NMMA Certified

Draft: A. Drive Unit Up 18½" (.47 m.)

B. Drive Unit Down 34" (.86 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, panel lights, interior lights & horn; hour meter & depth sounder Courtesy lights Electric horn Navigation lighting Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Hinged ski locker Ski tow ring 6" cleats Snap-in carpet

Unitized fiberglass deck/floor Molded extended swim platform Walk-thru curved full glass windshield Bow seats w/hinged bow backrest w/storage Automatic bilge pump & blower Stainless steel telescopic 3-step boarding ladder Stainless steel bow eye & stern eyes Merc/Volvo prop Tilt steering Enclosed head w/porta-pottie SuspensionAire adjustable bucket seats w/flip-up bolsters; U-shaped cockpit seating w/filler cushions; table & sunlounge; walk-thru transom

#### **Options**

Color-coordinated Sunbrella soft top & boot w/concealed storage
Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain
Color-coordinated Sunbrella Bimini top w/boot
Color-coordinated Sunbrella cockpit cover
Color-coordinated Sunbrella bow cover
Mooring cover
Docking lights

Stereo remote for dash
High altitude prop
Captain's Call (electric) w/Corsa
Quick & Quiet II
Wet bar
Bow filler cushion
SS Upgrade Package: SS rubrail,
docking lights, pull-up cleats,
transom-mounted stereo remote
& tilt/trim switch
50th Anniversary Package: SS upgrade
package, stereo remote for dash &
bow filler cushions

#### **Color Choices**

White w/Jet Black Gelcoat White w/Sapphire Blue Gelcoat White w/Jade Green Gelcoat White w/Crimson Red Gelcoat

#### **Engine Choices**

5.7L MerCruiser (250)
5.7L Bravo III MerCruiser (250)
350 Mag MPI Bravo I MerCruiser (300)
350 Mag MPI Bravo III MerCruiser (300)
MX 6.2 MPI Bravo II MerCruiser (320)
MX 6.2 MPI Bravo II MerCruiser (320)
496 Mag MPI Bravo I MerCruiser (375)

5.0 GXi Volvo Penta (270) 5.7 Gi Volvo Penta (280) 0) 5.7 Gi DP Volvo Penta (280) 5.7 GXi Volvo Penta (315) 0) 5.7 GXi DP Volvo Penta (375) 8.1 Gi DP Volvo Penta (375)

#### Performance

496 Mag MPI Bravo III MerCruiser (375)

Engine: 5.7 Gi DP V			
RPM	MPH	GPH	RANGE*
2000	12	4.2	141
3000	27	7.6	177
4000	38	12.4	155
WOT	45-49	_	
Time to plane: 3.0 se	ec.		

Engine: 496 Magnum MPI Bravo III MerCruiser, Prop: 28 uncup			
RPM	MPH	GPH	RANGE*
2000	15	6.2	123
3000	33	10.5	- 157
4000	47	18.0	131
WOT	57-60	Accorde	_
Time to plane: 3.4 sec.			

Engine: 8.1 Gi Volvo Penta, Prop: F6 Duoprop			
RPM	MPH	GPH	RANGE*
2000	20	5.7	177
3000	35	11.1	160
4000	49	19.3	128
WOT	58-61		_

Time to plane: 3.0 sec.

つつつつつつつ

2

2

2

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL PRIC	E \$



LOA 19' 11" (6.07 m.)
Beam 96" (2.44 m.)
Depth 45%" (1.16 m.)
Maximum Depth 56%" (1.44 m.)
Cockpit Depth 32" (.81 m.)
Approx. Wt. 3045 lbs. (1381 kg.)
w/5.0 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 92" (2.34 m.)
LOA on Trailer 24' 9" (7.54 m.)
Fuel Capacity 35 gal. (132 L.)
Maximum Load 1475 lbs. (669 kg.)
Max. Persons 10 or 1475 lbs. (669 kg.)
NMMA Certified

Draft: A. Drive Unit Up 16½" (.42 m.)

B. Drive Unit Down 31½" (.80 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories; hour meter & depth sounder Electric horn Clarion AM/FM/CD stereo w/4 speakers Glove box Hinged ski locker Ski tow ring Stainless steel bow eye & stern eyes Pull-up cleats Two-tone metallic paint

Courtesy lights Walk-thru curved full glass windshield Automatic bilge pump Stainless steel passenger grab handles Molded swim platform U-shaped cockpit seating, SuspensionAire adjustable bucket seat w/flip-up bolsters, walk-thru sunlounge w/port & starboard storage compartments Merc/Volvo prop Tilt steering Telescopic 3-step boarding ladder, fore & aft Snap-in carpet

#### Options

Color-coordinated Sunbrella Canvas
Package: bow cover, walk-thru
curtain, side curtains & stern curtain
Color-coordinated Sunbrella
Bimini top w/boot
Color-coordinated Sunbrella soft top
& boot w/concealed storage
Color-coordinated Sunbrella
cockpit cover
Color-coordinated Sunbrella
bow cover
Mooring cover w/extended swim
platform
Extended swim platform

Sirius satellite radio
Docking lights
High altitude prop
SS Upgrade Package: SS rubrail,
docking lights, transom-mounted
stereo remote & tilt/trim switch
Stereo remote for dash
Stern filler cushions
Bow filler cushions
Low profile black windshield
Wakeboard tower
50th Anniversary Package:
SS upgrade package, stereo
remote for dash & extended
swim platform

#### Color Choices

White w/Jet Black Metallic White w/Sapphire Blue Metallic

50

White w/Jade Green Metallic White w/Crimson Red Metallic

#### Engine Choices

5.0L MerCruiser (220)
5.0L MPI MerCruiser (260)
5.7L MerCruiser (250)
5.7L Bravo III MerCruiser (250)
5.7L Bravo III MerCruiser (250)
3.7 GXi Volvo Penta (280)
5.7 GXi Volvo Penta (315)

#### Performance

Engine: 5.7 Gi Volvo I			
RPM	MPH	GPH	RANGE*
2000	12		
3000	34		_
4000	47		
WOŢ	56-59	_	_
Time to plane: 3.1 sec.			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

Boat		\$
Vlotor	H.P.	
Trailer		
Accessories		
T, T & L		
•	TOTAL PRIC	E \$

51

#### GXL 205 Collector's Edition



#### Specifications

LOA 19¹ 11" (6.07 m.)
Beam 96" (2.44 m.)
Depth 45¾" (1.16 m.)
Maximum Depth 56¾" (1.44 m.)
Cockpit Depth 32" (.81 m.)
Approx. Wt. 3045 lbs. (1381 kg.)
w/5.0 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 92" (2.34 m.)
LOA on Trailer 24' 9" (7.54 m.)
Fuel Capacity 35 gal. (132 L.)
Maximum Load 1475 lbs. (669 kg.)
Max. Persons 10 or 1475 lbs. (669 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 16½" (.42 m.) **B. Drive Unit Down** 31½" (.80 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories; hour meter & depth sounder Electric horn Clarion AM/FM/CD stereo w/4 speakers Dash-mounted stereo remote Glove box Hinged ski locker Ski tow ring Stainless steel bow eye & stern eyes Pull-up cleats Two-tone metallic paint Courtesy lights Walk-thru curved full glass windshield

Automatic bilge pump Stainless steel passenger grab handles Molded swim platform U-shaped cockpit seating, SuspensionAire adjustable bucket seat w/flip-up bolsters, walk-thru sunlounge w/port & starboard storage compartments Merc/Volvo prop Tilt steering Telescopic 3-step boarding ladder, fore & aft Snap-in carpet Collector's Edition Package: SS rubrail, docking lights, transommounted stereo remote & tilt/trim switch, stereo remote for dash & bow/stern filler cushions

#### **Options**

Color-coordinated Sunbrella Canvas
Package: bow cover, walk-thru
curtain, side curtains & stern curtain
Color-coordinated Sunbrella
Bimini top w/boot
Color-coordinated Sunbrella soft top
& boot w/concealed storage
Color-coordinated Sunbrella
cockpit cover
Color-coordinated Sunbrella
bow cover

Mooring cover
Mooring cover w/extended swim
platform
Captain's Call (electric) w/Corsa
Quick & Quiet II
Extended swim platform
Sirius satellite radio
High altitude prop
Low profile black windshield
Wakeboard tower

#### Color Choices

White w/Sunfire Copper Metallic

0

0

C

)

#### **Engine Choices**

5.0L MerCruiser (220)	5.0 GL Volvo Penta (220)
5.0L MPI MerCruiser (260)	5.0 GXi Volvo Penta (270)
5.7L MerCruiser (250)	5.7 Gi Volvo Penta (280)
5.7L Bravo III MerCruiser (250)	5.7 GXi Volvo Penta (315)
350 Magnum MPI Alpha MerCruiser (300)	

#### Performance

Engine: 5.7 Gi Volvo Pe			
RPM	MPH	GPH	RANGE*
2000	12	_	
3000	34		_
4000	47	_	_
WOT	56-59	_	
Time to plane: 3.1 sec.			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Votor	H.P.	
Frailer		
Accessories		
T, T & L		
•	TOTAL PRIC	CE \$



**LOA** 18' (5.49 m.) Beam 91" (2.31 m.) Depth 43" (1.09 m.) Maximum Depth 53" (1.35 m.) Cockpit Depth 29½" (.75 m.) Approx. Wt. 1720 lbs. (780 kg.) w/o engine Transom Width 86" (2.18 m.)

Transom Deadrise 21° LOA on Trailer 22' 2" (6.76 m.) Fuel Capacity 29 gal. (110 L.) Maximum Load 1880 lbs. (853 kg.) Max. Persons 8 or 1225 lbs. (556 kg.) Max. Horsepower 150 (112 kw.) **NMMA** Certified

Draft: A. Drive Unit Up 16" (.41 m.) B. Drive Unit Down 29" (.74 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, fuel & trim gauges; plus switches for bilge pump, horn, navigation/ anchor lights, panel lights & accessories Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug Clarion AM/FM/CD stereo w/4 speakers Electric horn Navigation lighting Hinged ski locker Tilt steering 6" cleats Stainless steel bow eye & stern eyes Walk-thru curved open glass windshield

Bilge pump Unitized fiberglass deck/floor Snap-in carpet Courtesy lights Reversible bow seats/fishing deck SuspensionAire adjustable bucket seats w/flip-up bolsters/2 removable fishing seats/aft bench seating Stainless steel grab handles Molded swim platform Telescopic 3-step boarding ladder Bow storage compartments Glove box Aerated livewell Trolling motor mount Rod holders Tackle box trays Dual cable steering

#### Options

Color-coordinated Sunbrella soft top & boot w/concealed storage Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain Color-coordinated Sunbrella Bimini top w/boot Color-coordinated Sunbrella cockpit cover Color-coordinated Sunbrella bow cover Mooring cover Sirius satellite radio

Ski tow pylon Fishing Package: trolling motor, fish finder Convenience Package: hour meter, depth sounder & automatic bilge pump Stereo remote for dash Full side glass wings Two-tone metallic paint (black, blue, green & red) 50th Anniversary Package: two-tone metallic paint, fishing package & convenience package

#### Color Choices

White w/Charcoal graphics

C C う う う

C

C

#### **Engine Choices**

-	
Johnson 115 PLSD	Evinrude 115 DSLSD
Johnson 150 PLSD	Evinrude 130 DSLSD
JOHNSON 100 1 200	Evinrude 150 DSLSD
Yamaha 115 TLRD	
Yamaha F 115 TLRD	Mercury 115 ELPT Optimax
Yamaha 150 TLRD	Mercury 115 ELPT EFI 4 Stroke
Yamaha F 150 TLRD	Mercury 135 L Optimax
	Mercury 150 L Optimax

#### Performance

Engine: 115 Johnson, Prop: 14 x 17			
RPM	MPH	GPH	RANGE*
2500	15	3.6	109
3300	25	4.6	142
4700	35	7.2	127
WOT	42-44	_	
Time to plane: 3.2 sec.			

Engine: 135 Optimax Mercury (V6), Prop: 14¼ x 21			
RPM .	MPH	GPH	RANGE*
2400	15	4.2	93
3000	25	5.1	128
4000	35	7.1	129
WOT	46-49		_

Time to plane: 3.1 sec.

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	H.P.	Haran San San San San San San San San San S
Trailer		
Accessories		
T, T & L		
	TOTAL PR	ICE \$



LOA 18' (5.49 m.)
Beam 91" (2.31 m.)
Depth 43" (1.09 m.)
Waximum Depth 53" (1.35 m.)
Cockpit Depth 29½" (.75 m.)
Approx. Wt. 2760 lbs. (1252 kg.)
w/4.3 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 86" (2.18 m.)
LOA on Trailer 22' 4" (6.81 m.)
Fuel Capacity 29 gal. (110 L.)
Maximum Load 1200 lbs. (544 kg.)
Max. Persons 8 or 1200 lbs. (544 kg.)
NMMA Certified

Draft: A. Drive Unit Up 16" (.41 m.)

B. Drive Unit Down 31" (.79 m.)

#### Standard Features

speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug Electric horn Navigation lighting Clarion AM/FM/CD stereo w/4 speakers Glove box Hinged ski locker Ski tow ring 6" cleats Walk-thru curved windshield Courtesy lights

Instrument panel includes:

Unitized fiberglass deck/floor Reversible bow seats/fishing deck SuspensionAire adjustable bucket seats w/flip-up bolsters/2 removable fishing seats/aft bench seating Bow storage compartments Stainless steel passenger grab handles Molded swim platform Tilt steering
Convertible stern sundeck/fishing platform Bilge pump & blower Aerated livewell Trolling motor mount Rod holders Tackle box trays Merc/Volvo prop Telescopic 3-step boarding ladder Snap-in carpet

#### **Options**

Color-coordinated Sunbrella soft top & boot w/concealed storage Color-coordinated Sunbrella Canvas Package: bow cover, walk-thru curtain, side curtains & stern curtain Color-coordinated Sunbrella Bimini top w/boot Color-coordinated Sunbrella cockpit cover Color-coordinated Sunbrella bow covee Mooring cover Extended swim platform

Convenience Package: hour meter, depth sounder & automatic bilge pump
Fishing Package: trolling motor, fish finder
High altitude prop
Stereo remote for dash
Full side glass wings
Sirius satellite radio
Two-tone metallic paint (black, blue, green & red)
50th Anniversary Package: two-tone metallic paint, fishing package & convenience package

#### Color Choices

White w/Charcoal graphics

56

#### **Engine Choices**

3.0L MerCruiser (WPS) (135)
4.3L MerCruiser (190)
4.3L MPI MerCruiser (220)
4.3 GXi Volvo Penta (190)
4.3 GXi Volvo Penta (225)

#### Performance

Engine: 3.0L MerCruiser, Prop: 14½ x 19				
RPM	MPH	GPH	RANGE*	
2100	15	2.5	157	
2900	25	3.5	186	
3500	35	7.4	123	
WOT	42-44	-		
T	_			

Time to plane: 3.4 sec.

)

**5** 

うう

5

うう

9

Engine: 3.0 GL Volvo Penta, Prop: 14¼ x 19			
RPM	MPH	GPH	RANGE*
2000	8	_	
3000	19		_
4000	31	_	
WOT	38-40		_
Time to plane: 3.7 se	ec.		

Engine: 4.3 GL Volv	o Penta, Prop: 14¼ x	23	
RPM	MPH	GPH	RANGE*
2000	9		
3000	29	_	_
4000	40		
WOT	48-50		_

Time to plane: 4.2 sec.

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

Boat		<b>3</b>
Motor	H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL DDI	CE &

OTAL PRICE \$\_\_\_\_\_

57



LOA 19' 11" (6.07 m.)
Beam 96" (2.44 m.)
Depth 45%" (1.16 m.)
Maximum Depth 56%" (1.44 m.)
Cockpit Depth 32" (.81 m.)
Approx. Wt. 3095 lbs. (1404 kg.)
W/5.0 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 92" (2.34 m.)
LOA on Trailer 24' 9" (7.54 m.)
Fuel Capacity 35 gal. (132 L.)
Maximum Load 1475 lbs. (669 kg.)
Max. Persons 10 or 1475 lbs. (669 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 16½" (.42 m.) **B. Drive Unit Down** 31½" (.80 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories Bow panel includes: aerator switch, voltmeter, tilt switch, battery charger switch, battery selector switch, trolling motor plug Electric horn Navigation lighting Clarion AM/FM/CD stereo w/4 speakers Glove box Hinged ski locker Ski tow ring Stainless steel bow eye & stern eyes 6" cleats Bilge pump & blower

Walk-thru curved open glass windshield Unitized fiberglass deck/floor Snap-in carpet Reversible bow seats/fishing deck SuspensionAire adjustable bucket seats w/flip-up bolsters/2 removable fishing seats/aft bench seating Stainless steel passenger grab rails Molded swim platform Convertible stern sundeck/fishing platform Aerated livewell Trolling motor mount Rod holders Tackle box trays Merc/Volvo prop Telescopic 3-step boarding ladder Courtesy lights Tilt steering

#### Options

Color-coordinated Sunbrella soft top & boot w/concealed storage
Color-coordinated Sunbrella Canvas
Package: bow cover, walk-thru
curtain, side curtains & stern curtain
Color-coordinated Sunbrella
Bimini top w/boot
Color-coordinated Sunbrella
cockpit cover
Color-coordinated Sunbrella
bow cover
Mooring cover

Fishing Package: trolling motor, fish finder
Convenience Package: hour meter, depth sounder & automatic bilge pump
High altitude prop
Stereo remote for dash
Extended swim platform
Full side glass wings

#### Color Choices

White w/Jet Black Metallic White w/Sapphire Blue Metallic White w/Jade Green Metallic White w/Crimson Red Metallic

#### **Engine Choices**

4.3L MerCruiser (190)

4.3L MPI MerCruiser (220)

4.3L MPI Bravo III MerCruiser (220)

5.0L MerCruiser (220)

5.0L MPI MerCruiser (260) 5.7L MerCruiser (250)

Ĵ

**う** 

Ć

5.7L Bravo III MerCruiser (250)

Time to plane: 3.3 sec.

350 Mag MPI Alpha MerCruiser (300)

4.3 GL Volvo Penta (190)

4.3 GXi Volvo Penta (225)

4.3 GXi DP Volvo Penta (225)

5.0 GL Volvo Penta (220) 5.0 GXi Volvo Penta (270)

5.7 Gi Volvo Penta (280)

#### Performance

Engine: 4.3L MerCruiser, Prop: 14½ x 19			
RPM	MPH	GPH	RANGE*
2400	15	3.0	158
3200	25	4.0	197
3700	35	7.9	140
WOT	45-47		_

Engine: 5.0 GL Volv	o Penta, Prop: 14½	x 19	
RPM	MPH	GPH	RANGE*
2000	9	_	_
3000	27		
4000	39	_	_
WOT	48-50		******
Time to plane: 2.7 se	ec.		

Engine: 5.7L MerCruiser, Prop: 14½ x 19 Aluminum			
RPM	МРН	GPH	RANGE*
2000	12	_	_
3000	30	_	
4000	42		_
WOT	48-51	_	

Time to plane: 2.5 sec.

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat	\$
MotorH.P.	
Trailer	
Accessories	
Τ, Τ & L	
TOTAL PRIC	`F ¢

# DX 205 - NOW - CURRENT 201

#### Specifications

LOA 20' 1" (6.12 m.)
Beam 102" (2.59 m.)
Depth 50½" (1.28 m.)
Maximum Depth 59" (1.50 m.)
Cockpit Depth 35" (.89 m.)
Approx. Wt. 2900 lbs. (1315 kg.)
w/4.3L MerCruiser9

Transom Deadrise 17°
Transom Width 94" (2.39 m.)
LOA on Trailer 25' 3" (7.70 m.)
Fuel Capacity 50 gal. (189 L.)
Maximum Load 1400 lbs. (635 kg.)
Max. Persons 10 or 1400 lbs. (635 kg.)
NMMA Certified

Draft: A. Drive Unit Up 13" (.33 m.)

B. Drive Unit Down 28" (.71 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories Electric horn Automatic bilge pump Navigation lighting Clarion AM/FM/CD stereo w/4 speakers Ski locker Ski tow ring Fiberglass floor Carry-on cooler Color-coordinated Sunbrella Bimini top w/boot Wrap-around bow seats Snap-in carpet

Stainless steel bow eye & stern eyes Windscreen Bow storage compartments Passenger grab handles Single fishing seat for aft casting deck 6" cleats Molded swim platform Stainless steel boarding ladder Merc/Volvo prop Courtesy lights Aerated livewell Trolling motor plug SuspensionAire adjustable bucket seats w/flip-up bolsters Walk-thru transom w/gate Convenience Package: hour meter, depth sounder Tilt steering

#### Options

Color-coordinated Sunbrella cockpit cover High altitude prop Bow table w/floor mount Forward fishing seat & pedestal 50th Anniversary Package: bow table, forward fishing seat & pedestal

#### Color Choices

White w/Jet Black Gelcoat White w/Sapphire Blue Gelcoat White w/Jade Green Gelcoat White w/Crimson Red Gelcoat

#### **Engine Choices**

4.3L MerCruiser (190)	4.3 GL Volvo Penta (190)
4.3L MPI MerCruiser (220)	4.3 GXi Volvo Penta (225)
5.0L MerCruiser (220)	5.0 GL Volvo Penta (220)
5.0L MPI MerCruiser (260)	5.0 GXi Volvo Penta (270)

#### Performance

Engine: 5.0 GL Volv	o Penta, Prop: 14¼	x 21	
RPM	MPH	GPH	RANGE*
2000	8	- ,	*****
3000	31	Nation (Nation )	_
4000	46	_	
WOT	51-55		_
Time to plane: 3.0 se	c.		

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL	DDICE \$

LOA 201 11" (6.38 m.)
Beam 102" (2.59 m.)
Depth 57½" (1.46 m.)
Maximum Depth N/A
Cockpit Depth 28½" (.72 m.)
Approx. Wt. 3600 lbs. (1633 kg.)
w/5.0L MPI MerCruiser®

Transom Deadrise 16°
Transom Width 96" (2.44 m.)
LOA on Trailer 23' 9" (7.24 m.)
Fuel Capacity 56 gal. (212 L.)
Maximum Load 1900 lbs. (862 kg.)
Max. Persons 13 or 1950 lbs. (885 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 14" (.36 m.) **B. Drive Unit Down** 30" (.76 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges Dockside boarding gate Bow anchor locker Stainless steel ski tow ring Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Electric horn 6" cleats Fiberglass floor Snap-in carpet Tilt steering Stainless steel bow eye & stern eyes Stainless steel grab handles Courtesy lights Navigation lighting Wraparound bow seats

**Enclosed head** Windscreen Entertainment console w/sink, electric water pump (12.5 gal) & carry-on cooler Ski locker SuspensionAire adjustable bucket seats w/flip-up bolster Merc/Volvo prop Fore & aft swim platforms w/concealed ladders Bow storage compartments Color-coordinated Sunbrella Bimini top w/boot Walk-thru transom w/gate Convenience Package: hour meter & depth sounder Automatic bilge pump

#### Options

Color-coordinated Sunbrella cockpit cover Docking lights Compass Table w/bow & aft floor mounts Porta-pottie Extended swim platform Bow filler cushions High altitude prop
Fishing Package: livewell w/switch at
dash, 2 bow fishing seats & bow
trolling motor plug
50th Anniversary Package: bow filler
cushions, docking lights & cockpit
cover & table w/bow & aft floor
mounts

#### Color Choices

White w/Jet Black Gelcoat White w/Sapphire Blue Gelcoat White w/Jade Green Gelcoat White w/Crimson Red Gelcoat

#### **Engine Choices**

4.3L MerCruiser (190) 4.3 GL Volvo Penta (190)
4.3L MPI MerCruiser (220) 4.3 GXi Volvo Penta (225)
4.3L MPI Bravo III MerCruiser (220) 5.0 GL Volvo Penta (225)
5.0L MPI MerCruiser (260) 5.0 GXi Volvo Penta (220)
5.7L MerCruiser (250) 5.7 Gi Volvo Penta (280)
5.7L Bravo III MerCruiser (250)
350 Maq MPI Alpha MerCruiser (300)

#### Performance

Engine: 5.0L MPI MerCruiser, Prop: 141/2 x 19 Aluminum			
RPM	MPH	GPH	RANGE
2000	9	3.8	119
3000	27	7.0	192
4000	39	11.4	171
WOT	47-49		_

Time to plane: 4.3 sec.

00000000000

Engine: 5.0L MerCruiser, Prop: 14½ x 19 Aluminum			
RPM	MPH	GPH	RANGE
2000	9	_	
3000	26	-	-
4000	38	_	_
WOT	42-45	_	
Time to plane: 4.5 sec.	•		

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		
Motor	Н.Р.	
Trailer		
Accessories		
T, T & L		
	TOTAL DDICE	¢

LOA 22' 6" (6.86 m.)

Beam 102" (2.59 m.)

Depth 60" (1.52 m.)

Maximum Depth 69" (1.75 m.)

Cockpit Depth 31" (.79 m.)

Approx. Wt. 4000 lbs. (1814 kg.)

w/5.7 GL Volvo Penta®

Transom Deadrise 15°
Transom Width 94" (2.39 m.)
LOA on Trailer 30' 6" (9.30 m.)
Fuel Capacity 73 gal. (276 L.)
Maximum Load 1950 lbs. (885 kg.)
Max. Persons 13 or 1950 lbs. (885 kg.)
NMMA Certified

**Draft: A. Drive Unit Up** 18" (.46 m.) **B. Drive Unit Down** 32" (.81 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges Courtesy lights Electric horn Navigation lighting Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Ski locker Ski tow ring 6" cleats Automatic bilge pump & blower Color-coordinated Sunbrella Bimini top w/boot Removable cooler Walk-thru transom w/gate Snap-in carpet

Walk-thru curved full glass windshield Wraparound bow seats w/storage Fore & aft swim platforms w/concealed ladders Stainless steel bow eye & stern eyes Anchor locker Stainless steel grab handles Enclosed head & sink SuspensionAire adjustable bucket seats w/flip-up bolster Table w/bow & aft floor mounts Dockside boarding gate Tilt steering Merc/Volvo prop Fiberglass floor Convenience Package: hour meter & depth sounder

#### Options

Color-coordinated Sunbrella bow/cockpit cover Docking lights Pump-out head Compass High altitude prop Bow filler cushions Extended swim platform
Transom shower
Porta-pottie
50th Anniversary Package: docking
lights, bow/cockpit cover &
extended swim platform

#### Color Choices

White w/Jet Black Gelcoat White w/Sapphire Blue Gelcoat White w/Jade Green Gelcoat White w/Crimson Red Gelcoat

#### **Engine Choices**

5.0L MerCruiser (220)
5.0L MPI MerCruiser (260)
5.7L MerCruiser (250)
5.7L Bravo III MerCruiser (250)
5.7L Bravo III MerCruiser (250)
350 Mag MPI Alpha MerCruiser (300)
350 Mag MPI Bravo III MerCruiser (300)

#### Performance

ingine: 5.0 GXi Volvo l	Penta, Prop. 14	4 x 19	
RPM	MPH	GPH	RANGE
2000	9	3.6	104 162
3000	26	6.9 10.1	150
4000	39 48-50	10.1	
WOT Time to plane: 3.5 sec.	40-30		
Tittle to plane, 3,3 sec.			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	_H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL DRIC	F <b>S</b>

LOA 20' 2" (6.15 m.)
Beam 94¼" (2.39 m.)
Depth 50" (1.27 m.)
Maximum Depth 71" (1.80 m.)
Cockpit Depth 35" (.89 m.)
Approx. Wt. 2852 lbs. (1294 kg.)
w/5.0 GL Volvo Penta®

Transom Deadrise 21°
Transom Width 90° (2.29 m.)
LOA on Trailer 24' 8° (7.52 m.)
Fuel Capacity 45 gal. (170 L.)
Maximum Load 1450 lbs. (658 kg.)
Max. Persons 8 or 1150 lbs. (522 kg.)
NMMA Certified

Draft: A. Drive Unit Up 18½" (.47 m.) B. Drive Unit Down 33" (.84 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, horn, lights & accessories Electric horn Automatic bilge pump Blower Navigation lighting Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Floor storage area Ski tow ring Stainless steel bow eye & stern eyes 6" cleats Tilt steering Color-coordinated Sunbrella Bimini top & boot

Convenience Package: hour meter & depth sounder Cuddy cabin includes: upholstered V-berth, lounge seat, cabin courtesy light, deck hatch w/screen & lockable door BS Seating: SuspensionAire adjustable bucket seat w/flip-up bolsters/port sleeper/aft jump seats Molded swim platform Helm storage locker Merc/Volvo prop Bow access step Bow anchor locker Passenger grab handles Walk-thru curved full glass windshield Telescopic 3-step boarding ladder Stainless steel bow rails

#### Options

Color-coordinated Sunbrella Canvas Package: side curtains, stern curtain Color-coordinated Sunbrella Camper Canvas Package: includes Canvas Package less stern curtain, plus aft camper top, aft camper side curtains & aft camper stern curtain Color-coordinated Sunbrella cockpit cover Mooring cover High altitude prop Galley Package: alcohol stove, ice box, sink, water system, dual helm seat & aft jump seats

SL Seating: SuspensionAire
adjustable bucket seat w/flip-up
bolsters/aft bench seat/sunlounge
(Galley Package not available in
this seating option)
Porta-pottie

50th Anniversary Package: sport interior & porta-pottie

#### Color Choices

White w/Mediterranean Blue Gelcoat & Yellow hull stripe

# 00000 00000000000000000

#### **Engine Choices**

4.3 L MerCruiser (190)
4.3 L MPI MerCruiser (220)
4.3 L MPI Bravo III MerCruiser (220)
4.3 L MPI Bravo III MerCruiser (220)
5.0 L MerCruiser (220)
5.0 L MPI MerCruiser (260)
4.3 GXi Volvo Penta (225)
5.0 GL Volvo Penta (220)
5.0 L MPI MerCruiser (260)
5.0 GXi Volvo Penta (270)

#### Performance

Engine: 4.3L MerCru	iser, Prop: 14¼ x 21		•
RPM	MPH	GPH	RANGE*
2400	15	4.2	145
3200	25	5,5	184
3700	35	8.6	165
WOT	44-46	_	_
Time to plane: 3.5 sec			•

Engine: 4.3 GL Volv	o Penta, Prop: 14¼ x	21	
RPM	MPH	GPH	RANGE*
2000	15	4.0	152
3000	25	5.3	191
4000	35	9.0	158
WOT	43-45	_	_
Time to plane: 3.6 se	ec.		

Engine: 5.0L MerCruiser, Prop: 14½ x 19 Aluminum			
RPM	MPH	GPH	RANGE*
2000	9	_	_
3000	- 27	_	
4000	39	_	_
WOT	43-46	_	*****

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

Time to plane: 4.0 sec.

Boat		\$
Motor	_H.P.	
Trailer		
Accessories		
т, т & L		
	TOTAL PRICE	<u> </u>

LOA 21' 6" (6.55 m.)

Beam 102" (2.59 m.)

Depth 62" (1.57 m.)

Maximum Depth 72" (1.83 m.)

Cockpit Depth 34" (86 m.)

Approx. Wt. 3600 lbs. (1633 kg.)

w/5.0 GXi Volvo Penta®

Transom Deadrise 21°
Transom Width 96" (2.44 m.)
LOA on Trailer 26' 4" (8.03 m.)
Fuel Capacity 56 gal. (212 L.)
Maximum Load 1950 lbs. (885 kg.)
Max. Persons 8 or 1150 lbs. (522 kg.)
NMMA Certified

Draft: A. Drive Unit Up 18" (.46 m.) B. Drive Unit Down 36" (.91 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, lights & horn; hour meter & depth sounder Horn Porta-pottie Blower Navigation lighting Hour meter Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Stainless steel bow rails Stainless steel bow eye & stern eyes 6" cleats Ski tow ring Cuddy cabin includes: upholstered V-berth, cabin courtesy light, deck hatch & bi-fold lockable door

BS Seating: SuspensionAire adjustable bucket seat w/flip-up bolsters/port sleeper/aft jump seats Molded swim platform Stainless steel telescopic 3-step boarding ladder Color-coordinated Sunbrella Bimini top & boot Merc/Volvo prop Tilt steering Floor storage area Walk-thru curved full glass Carry-on ice chest Bow anchor locker 12V power plug Stereo remote for dash Snap-in carpet Fiberglass floor Battery switch Automatic bilge pump

#### **Options**

Color-coordinated Sunbrella Camper Canvas Package: includes Canvas Package less stern curtain, plus aft camper top & aft camper side curtains & aft camper stern curtain Color-coordinated Sunbrella Canvas Package for Bimini top; side curtains, aft curtain & clear connector Color-coordinated Sunbrella cockpit cover Mooring cover

Galley Package: stainless steel sink, 5-gal. water system, butane stove Spot light
High altitude prop Compass
SL Seating: SuspensionAire adjustable bucket seats w/flip-up bolsters/aft bench seat/sunlounge (Galley Package not available in this seating option)
50th Anniversary Package: sport interior & spot light

#### Color Choices

White w/Mediterranean Blue Gelcoat & Yellow hull stripe

#### **Engine Choices**

4.3L MerCruiser (190)	4.3 GL Volvo Penta (190)
5.0L MerCruiser (220)	5.0 GL Volvo Penta (220)
5.0L MPI MerCruiser (260)	5.0 GXi Volvo Penta (270)
5.7L MerCruiser (250)	5.7 Gi Volvo Penta (280)
5.7L Bravo III MerCruiser (250)	5.7 Gi DP Volvo Penta (280)
350 Mag MPI Alpha MerCruiser (300)	
350 Mag MPI Bravo I MerCruiser (300)	

#### Performance

Engine: 5.7L MerCruiser Bravo III, Props: 14 x 26 and 15¼ x 26			
RPM	MPH	GPH	RANGE
2000	10		_
3000	28	_	
4000	40	-	_
WOT	45-49	_	_
Time to plane: 2.5 sec			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat		\$
Motor	H.P.	
Trailer		-
Accessories		
T, T & L		
	TOTAL DRICE	•

LOA 24' 10" (7.57 m.) Beam 102" (2.59 m.) Depth 84" (2.13 m.) Maximum Depth 91¼" (2.32 m.) w/o arch

Cockpit Depth 36" (.91 m.) Approx. Wt. 5450 lbs. (2472 kg.) w/5.7L MerCruiser® Transom Deadrise 20°
Transom Width 98" (2.49 m.)
LOA on Trailer N/A
Fuel Capacity 56 gal. (212 L.)
Maximum Load 2240 lbs. (1016 kg.)
Max. Persons 10 or 2240 lbs. (1016 kg.)
NMMA Certified

Draft: A. Drive Unit Up 22" (.56 m.)

B. Drive Unit Down 36" (.91 m.)

#### Standard Features

Instrument panel Includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, panel lights, interior lights & horn Color-coordinated Sunbrella Bimini top & boot Horn/blower/compass Automatic bilge pump Translucent deck hatch w/screen Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Stainless steel rails Stainless steel bow eye & stern eyes Stainless steel cleats Main cabin includes; enclosed head w/4-gallon porta-pottie, fiberglass shower stall, hanging clothes locker, cabin table, cabin courtesy lights & on-demand water faucet

Hydraulic trim tabs Cockpit area includes: wet bar w/sink, removable ice chest, removable stern seat, portside lounge seat & double wide sunlounge helm seat Galley Package: microwave oven, 12/110V refrigerator, alcohol/electric stove, hot water heater & 110V dockside power Molded swim platform w/stainless steel telescopic 3-step boarding ladder Walk-thru curved full glass windshield Bow pulpit w/roller & bow rope locker Dual battery switch Fiberglass floor 18-gallon water tank Merc/Volvo prop Vented cabin windows (3) Tilt steering Ski tow ring Remote control spotlight Snap-in carpet Transom shower

#### Options

Color-coordinated Sunbrella Camper Canvas Package includes: Canvas Package less stern curtain, plus aft campter top, aft camper side curtains, aft camper stern curtain Color-coordinated Sunbrella Canvas Package for Bimini top: side curtains, aft curtain, clear connector Color-coordinated Sunbrella cockpit cover Electric anchor windlass Manual china head w/pump-out Stereo remote
Starboard windshield wiper
High altitude prop
Dockside air conditioner/reverse heat
Electric china head
13" flat screen TV w/DVD
Radar arch
High/low dual helm seat w/filler cushion
Grey water system
50th Anniversary Package: electric
anchor windlass & dockside A/C &
reverse heat

#### Color Choices

White w/Mediterranean Blue Gelcoat & Yellow hull stripe

### Engine Choices 5.0 L MerCruiser (220) 5.0 GL Volvo Penta (220)

5.0L MerCruiser (220)
5.0L MPI MerCruiser (260)
5.7L MerCruiser (250)
5.7L Bravo III MerCruiser (250)
350 Mag MPI Bravo I MerCruiser (300)
350 Mag MPI Bravo II MerCruiser (300)
MX 6.2 MPI Bravo I MerCruiser (320)
MX 6.2 MPI Bravo III MerCruiser (320)

5.0 GXi Volvo Penta (270)
5.0 GXi DP Volvo Penta (270)
5.0 OSi DP Volvo Penta (270)
5.7 Gi Volvo Penta (280)
5.7 Gi DP Volvo Penta (280)
5.7 OSi DP Volvo Penta (280)
5.7 GXi Volvo Penta (315)
5.7 GXi DP Volvo Penta (315)
5.7 GXi DP Volvo Penta (320)

#### Performance

5

2

うつうつつつ

つつつつつつつつつつつつつ

Engine: 350 Magnum MPI Bravo III MerCruiser, Props: 144 x 22 and 154 x 22

13/4 A 66		
MPH	GPH	RANGE*
8	4.1	102
21	7.7	137
34	11.6	147
45-47	_	_
	<b>MPH</b> 8 21 34 45-47	MPH GPH  8 4.1  21 7.7  34 11.6  45-47 —

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

Boat	\$
MotorH.P.	
Trailer	
Accessories	
T, T & L	

TOTAL PRICE S

LOA 26' 11" (8.20 m.)
Beam 102" (2.59 m.)
Depth 86" (2.18 m.)
Maximum Depth 92" (2.34 m.)
Cockpit Depth 36" (.91 m.)
Approx. Wt. 5850 lbs. (2654 kg.)
w/5.7 Gi Volvo Penta®
Transom Deadrise 20°

Transom Width 97" (2.46 m.) LOA on Trailer 30' (9.14 m.) Fuel Capacity 72 gal. (273 L.) Bridge Clearance 79" (2.01 m.) Bridge Clearance w/Arch 106" (2.69 m.) NMMA Certified

**Draft: A. Drive Unit Up** 19" (.49 m.) **B. Drive Unit Down** 40" (1.02 m.)

#### Standard Features

Instrument panel Includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter, engine temperature, hour meter & depth sounder gauges; plus switches for bilge pump, blower, navigation/ anchor lights, panel lights, interior lights & horn Electric horn Compass Blower Depth sounder & hour meter Automatic bilge pump Stainless steel bow eye & stern eyes Stainless steel cleats Stainless steel bow rails & grabrails Dual battery switch Fiberglass cockpit floor Walk-thru curved full glass windshield Remote control spotlight Main cabin includes: locker, V-berth cushions w/table & filler cushions, cabin courtesy lights & hot water system

Deck hatch w/screen Cockpit area includes: wet bar w/sink, ice box & water system, removable stern seat, portside lounge seat & double wide sunlounge helm seat Galley Package: microwave oven, 12/110V refrigerator, alcohol/ electric stove, 110V dockside power, sink & water system 18-gallon water tank Snap-in carpet Molded swim platform w/stainless steel telescopic 3-step boarding ladder Sunbrella Bimini top & boot Merc/Volvo prop Tilt steering Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Manual china head w/pump-out Transom shower Battery charger Ski tow ring Hydraulic trim tabs Vented cabin windows (4)

#### Options

Color-coordinated Sunbrella Canvas Package for Birnini top: side curtains, aft curtain, clear connector Color-coordinated Sunbrella cockpit cover 13" flat screen TV w/DVD Stereo remote Fore deck sun pad High altitude prop Electric anchor windlass
Starboard windshield wiper
Radar arch
Grey water system
Electric china head
Dockside air conditioner/reverse heat
Soth Anniversary Package: electric
anchor windlass & dockside A/C
& reverse heat

#### **Color Choices**

White w/Mediterranean Blue Gelcoat & Yellow hull stripe

2

#### **Engine Choices**

350 Mag MPI Bravo I MerCruiser (300) 350 Mag MPI Bravo III MerCruiser (300) MX 6.2 MPI Bravo I MerCruiser (320) MX 6.2 MPI Bravo III MerCruiser (320)

5.0 GXi Volvo Penta (270) 5.0 GXi DP Volvo Penta (270) 5.7 Gi Volvo Penta (280) 5.7 Gi DP Volvo Penta (280) 5.7 OSi DP Volvo Penta (280) 5.7 GXi Volvo Penta (315) 5.7 GXi DP Volvo Penta (315)

5.7 OSXi DP Volvo Penta (320)

#### Performance

Engine: 5.7 Gi DP Vo	lvo Penta, Prop: F	3	
RPM	MPH	GPH	RANGE*
2000	9	4.2	140
3000	20	8.3	156
4000	33	12.1	176
WOT	40-42		_
Time to plane: 4.9 sec			•

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

#### Sale Price

Boat		\$
Motor	H.P.	
Trailer		
Accessories		
T, T & L		
	TOTAL PRIC	CE \$

73

**LOA** 27' 5" (8.36 m.) **Beam** 102" (2.59 m.) **Depth** 89" (2.26 m.) Maximum Depth 97" (2.46 m.) Cockpit Depth 36" (.91 m.) Approx. Wt. 6200 lbs. (2812 kg.) w/5.0 GL Volvo Penta® Transom Deadrise 20°

Transom Width 97" (2.46 m.) **LOA on Trailer** 30' 6" (9.30 m.) Fuel Capacity 72 gal. (273 L.) Bridge Clearance 84" (2.13 m.) Bridge Clearance w/Arch 106" (2.69 m.) NMMA Certified

Draft: A. Drive Unit Up 19" (.49 m.) B. Drive Unit Down 40" (1.02 m.)

#### Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter, engine temperature, hour meter & depth sounder gauges; plus switches for bilge pump, blower, navigation/ anchor lights, panel lights, interior liahts & horn Electric horn Compass Blower Automatic bilge pump Stainless steel bow eye & stern eyes Stainless steel cleats Walkaround deck Walk-thru curved full glass windshield waik-und curved full glass Windshield Vented cabin windows (2) Main cabin includes: hanging clothes locker, V-berth cushions w/table & filler cushions, cabin courtesy lights & hot water system Molded swim platform w/stainless steel telescopic 3-step boarding ladder Bow pulpit w/roller & bow rope locker 18-gallon water tank

Cockpit area includes: wet bar w/sink, ice box & water system, removable stern seat, portside lounge seat, double wide sunlounge helm seat Galley Package: microwave oven, 12/110V refrigerator, alcohol/ electric stove, 110V dockside power, sink & water system Deck hatch w/screen Sunbrella Bimini top w/boot Merc/Volvo prop Tilt steering
Clarion AM/FM/CD/Sirius satellite stereo w/4 speakers Manual china head w/pump-out Transom shower Battery charger Dual battery switch Walk-thru transom w/gate Hydraulic trim tabs Fiberglass cockpit floor Ski tow ring
Stainless steel bow rail & grabrails Starboard windshield wiper Remote control spotlight
Depth sounder & hour meter

#### Options

Snap-in carpet

Canvas Package includes: Canvas Package less stern curtain, plus aft camper top, aft camper side curtains & aft camper stern curtain Color-coordinated Sunbrella Canvas Package for Birnini top: side curtains, aft curtain & clear connector Color-coordinated Sunbrella cockpit cover 13" flat screen TV w/DVD

Color-coordinated Sunbrella Camper

High altitude prop Electric anchor windlass Stainless steel storage rack for docking fenders Extended swim platform Grey water system
Dockside air conditioner/reverse heat Additional vented cabin windows (2) Westerbeke 5KW generator Electric china head 50th Anniversary Package: electric anchor windlass & dockside A/C & reverse heat

White w/Mediterranean Blue Gelcoat & Yellow hull stripe

Radar arch Color Choices 74

# う う 555555 **つ** ううううううつ **ううううううう**

#### **Engine Choices**

350 Mag MPI Bravo I MerCruiser (300) 350 Mag MPI Bravo III MerCruiser (300) MX 6.2 MPI Bravo I MerCruiser (320) MX 6.2 MPI Bravo III MerCruiser (320)

5.0 GXi Volvo Penta (270) 5.0 GXi DP Volvo Penta (270) 5.7 Gi Volvo Penta (280) 5.7 Gi DP Volvo Penta (280) 5.7 OSi DP Volvo Penta (280) 5.7 GXi Volvo Penta (315) 5.7 GXi DP Volvo Penta (315) 5.7 OSXi DP Volvo Penta (320)

#### Performance

ingine: 5.7L MerCruiser Bravo III, Props: 14¼ x 22 and 15¾ x 22			
RPM	MPH	GPH	RANGE*
2000	9	_	_
3000	19		
4000	32	_	_
WOT	38-41	warm.	_
Time to plane: 4.5 sec.			

Engine: 5.7 GXi DP Volvo Penta, Prop: F4 Duoprop			
RPM	MPH	ĠPH	RANGE*
2500	16	6.7	155
3500	30	10.9	178
WOT	43-46		_
Time to plane: 4.9 sec			

Note: All with two persons and full tank of fuel. Performance results will vary depending on load, altitude, and other conditions.

\*Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Boat	\$		
MotorH.P.			
Trailer			
Accessories			
T, T & L			
TOTAL DDICE \$			



#### MerCruiser Sterndrive Engine Information

The following pages contain data about sterndrives offered in our 2006 product.

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Heiaht Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Width Height Weight

#### **3.0L MERCRUISER**

135 hp/101 kw. 181 9.3:1 4400-4800 2.0:1 Power Power 29" 26" 21" (above crankshaft at CL)

635 lbs. (pkg. weight)

#### 4.3L MERCRUISER

190 hp/142 kw. 6 262 9.4:1 4400-4800 1.81:1 Power Power 28<sup>11</sup> 21" (above crankshaft at CL) 848 lbs. (pkg. weight)

220 hp/164 kw.

#### 4.3L MPI MERCRUISER

262 9.4:1 4400-4800 1.62:1 Power 22" (above crankshaft at CL) 865 lbs. (pkg. weight)

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### 4.3L MPI BRAVO III MERCRUISER

220 hp/164 kw.

262 9.4:1 4400-4800 2.2:1 Power Power 22" (above crankshaft at CL) 921 lbs. (pkg. weight)

#### **5.0L MERCRUISER**

220 hp/164 kw. 305 9.4:1 4400-4800 1.62:1 Power Power 32" 30ª 22" (above crankshaft at CL) 946 lbs. (pkg. weight)

#### 5.0L MPI MERCRUISER

260 hp/194 kw. 305 9.4:1 4600-5000 1.62:1 Power Power 22" (above crankshaft CL) 952 lbs. (pkg. weight)

#### 5.7L MERCRUISER

250 hp/186 kw. 350 9.4:1 4400-4800 1.62:1 Power Power 32" 22" (above crankshaft at CL) 946 lbs. (pkg. weight)



#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height

#### 5.7L BRAVO III MERCRUISER

250 hp/186 kw. 8 350 9.4:1 4400-4800 2.2:1 Power Power 32" 30" 22" (above crankshaft at CL)

#### 350 MAGNUM MPI ALPHA MERCRUISER

1013 lbs. (pkg. weight)

300 hp/ 224 kw. 8 350 9,4:1 4800-5200 1,47:1 Power Power Power 22" 30" 22" (above crankshaft at CL) 952 lbs. (pkg. weight)

#### 350 MAGNUM MPI BRAVO I MERCRUISER

300 hp/224 kw. 8
350
9,4:1
4800-5200
1.50 to1.65:1
Power
Power
32"
30"
22" (above crankshaft at CL)
993 lbs. (pkg. weight)

#### 350 MAGNUM MPI BRAVO III MERCRUISER

8 350 hp/224 kw. 8 350 9.4:1 4800-5200 2.00 to 2.20:1 Power Power 32" 30" 22" (above crankshaft at CL) 1019 lbs. (pkg. weight)

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Tilt Trim Length Width Height Weight

#### MX 6.2 MPI BRAVO I MERCRUISER

320 hp/239 kw. 8 377 9.0:1 4800-5200 1.50 to 1.65:1 Power Power 32" 30" 22" (above crankshaft at CL) 993 lbs. (pkg. weight)

#### MX 6.2 MPI BRAVO III MERCRUISER

MERCRUISER
320 hp/239 kw.
8
377
9.0:1
4800-5200
2.00 to 2.20:1
Power
32"
30"
22" (above crankshaft at CL)
1019 lbs. (pkg. weight)

#### 496 MAGNUM MPI BRAVO I MERCRUISER

75 h/280 kw.

8

496

9.1:1

4400-4800

1.5:1

Power

Power

33"

24" (above crankshaft at CL)

1199 lbs. (pkg. weight)

#### 496 MAGNUM MPI BRAVO III MERCRUISER

496 9.1:1 4400-4800 2.00:1 Power 75" 33" 24" (above crankshaft at CL) 1225 lbs. (pkg. weight)

375 hp/280 kw.



### Volvo Penta Sterndrive Engine Information

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio
Max. Recommended RPM Lower Unit Gear Ratio Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### **3.0 GL VOLVO PENTA** 135 hp/100 kw.

181 9,2:1 4600 1.97:1 Power 32½° 26″ 21" (above crankshaft at CL)

729 lbs. (pkg. weight)

#### 4.3 GL SX VOLVO PENTA

190 hp/141 kw. 262 9.4:1 4600 1.79:1 Power Power 20¼" (above crankshaft at CL) 896 lbs. (pkg. weight)

#### 4.3 GXI SX VOLVO PENTA

225 hp/168 kw. 262 9.4:1 4800 1.60 to 1.66:1 Power Power 22" (above crankshaft at CL) 916 lbs. (pkg. weight)

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height

#### Weight MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Weight

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height

#### 4.3 GXI DP VOLVO PENTA

225 hp/167 kw. 6 262 9.4:1 4800 1.95:1 Power Power 32½" 21" (above crankshaft at CL) 916 lbs. (pkg. weight)

#### 5.0 GL SX VOLVO PENTA

220 hp/164 kw. 305 9.4:1 4800 1.60:1 Power Power 28¼" 22" (above crankshaft at CL) 995 lbs. (pkg. weight)

#### 5.0 GXI SX VOLVO PENTA

270 hp/201 kw. 305 9.4:1 5000 1.60:1 Power Power 22" (above crankshaft at CL) 1040 lbs. (pkg. weight)

#### 5.0 GXI DP VOLVO PENTA

270 hp/201 kw. 9.4:1 5000 1.95:1 Power Power

22" (above crankshaft at CL) 1040 lbs. (pkg. weight)



#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### 5.0 OSI DP VOLVO PENTA

270 hp/201 kw. 305 9.4:1 5000 2.32:1 Power Power 28¼° 22" (above crankshaft at CL) 995 lbs. (pkg. weight)

#### 5.7 GI SX VOLVO PENTA

280 hp/209 kw. 350 9.4:1 5000 1.51:1 Power Power 37" 28¼" 22" (above crankshaft at CL) 1040 lbs. (pkg. weight)

#### 5.7 GI DP VOLVO PENTA

280 hp/209 kw. 350 9.4:1 5000 1.95:1 Power Power 28¼" 22" (above crankshaft at CL) 1040 lbs. (pkg. weight)

#### 5.7 OSI DP VOLVO PENTA

280 hp/209 kw. 5000 1.78:1 Power Power 22" (above crankshaft at CL) 1000 lbs. (pkg. weight)

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches
Compression Ratio
Max. Recommended RPM
Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

)

) )

2

) )

2222

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### MODEL:

Horsepower at Prop Shaft Cylinders Cubic Inches Compression Ratio Max. Recommended RPM Lower Unit Gear Ratio Trim Length Width Height Weight

#### 5.7 GXI SX VOLVO PENTA

320 hp/239 kw. 350 9.4:1 5200 1.51:1 Power Power 281/4" 22" (above crankshaft at CL) 1031 lbs. (pkg. weight)

5.7 GXI DP VOLVO PENTA 320 hp/239 kw. 350 9.4:1 5200 1.95:1 Power Power 37" 281/4" 22" (above crankshaft at CL) 1040 lbs. (pkg. weight)

#### 5.7 OSXI DP VOLVO PENTA

320 hp/239 kw. 8 350 9.4:1 5200 1.78:1 Power Power 37° 28¼" 22" (above crankshaft at CL) 1015 lbs. (pkg. weight)

#### 8.1 GI DP VOLVOPENTA

375 hp/280 kw. 496 9.1:1 4600 1.68:1 Power Power 41" 21.4" (above crankshaft at CL) 1258 lbs. (pkg. weight)

SURSTRON

P.O. Box 460 Little Falls, Minnesota 56345; USA Phone 320/632-8395

Visit our web site at www.glastron.com