2013

PRODUCT SPECIFICATIONS MANUAL

GLASTRON

Table of Contents

1
2–3
4
5–6
7–14
16–65
66–79
Directory
MX 180 42
MX 185 Models
MX 18544
MX 185 SF45
MX 205 Models
MX 20547 MX 205 SF48
GLS 195 50
GLS 215 52
DS 200 54
DS 205 56
DS 215 58
GS 249 60
GS 259 62
GS 289 64
33 models
•

GLASTRON

Over 58 Years of Leadership

 Glastron has been making boats for 58 years a milestone few boat companies have achieved.

During that time, they have built nearly half a million fiberglass boats.




- More than any other manufacturer, Glastron has a legacy of unprecedented product innovations and technological breakthroughs.
 Among them:
 - -The deep-vee hull
 - -The tri-hull
 - -Two-tone graphics
 - -Sterndrive-powered boats
 - -The SSV® hull
 - -Fiberglass stringer systems



 More than a few well-known people over the years have owned Glastron boats, from President Lyndon Johnson...to England's Royal Family...to Elvis Presley. Glastron boats also appeared in numerous movies and television shows. Glastron was James Bond's boat of choice

in Live and Let Die and Moonraker. The most famous Glastron ever? The Batboat!



 The Glastron "sweep spear" is the most well-known icon in boating. It's the marine industry's equivalent to the Nike "swoosh."




- Throughout the company's 58 years, its focus has been on designing and building boats that provide a great overall family boating experience. The company has always managed to stay ahead of other companies in building boats that possess three distinct Glastron qualities:
 - Advanced technology
 - Highly functional, family-friendly designs
 - Outstanding performance



Glastron Performance


 Glastron's penchant for performance is known throughout the industry.



- Every Glastron model delivers performance attributes that every family boater can appreciate (and every Glastron owner knows):
 - Very quick planing times
 - Minimal bowrise
 - Impressive top speeds
 - Low minimum planing speeds (particularly important for tubing, kneeboarding and wakeboarding)
 - Agile handling
 - Excellent fuel economy
- Glastron provides performance data on every model. Found on pages 16–65 of this manual, it includes authenticated speed, acceleration and, in many cases, fuel economy figures for popular engine choices.

SSV® Hull Design


- The legendary SSV (Super Stable Vee) hull design is the biggest reason Glastron boats perform so well. It's quick to plane (with minimal bowrise), stable at high speeds and tracks tight in the turns.
- The SSV hull's light weight and hydrodynamic efficiency results in another big advantage:



excellent fuel economy.

 The SSV hull features tuned strakes molded longitudinally into the hull. They form a series of horizontal planing surfaces that create lift by deflecting spray down and away from the hull—a key reason why Glastron boats get on plane so quickly.

GLASTRON



 Under power, the SSV hull's wide reverse chines create a "bank" of water for added lift

and precise, stable turning. Boats without them have a flatter running surface that results in a more jarring ride and a tendency to slide in turns.

 On most boat hulls, the chines diminish in the forward half of the hull. In comparison, the SSV hull's wide chines extend far forward.

These extended chines reduce rocking from side-to-side and front-

to-back by acting as sponsons when the boat is at rest.





With diminishing chines

With extended chines

 Glastron's SSV® hull; only Glastron has it. So no matter what other manufacturers may tell you, they don't have an SSV hull.

2013 Glastron Fiberglass Boats and Trailers Limited Warranty (North America)

Rec Boat Holdings, LLC dba Glastron ("Glastron") warrants to you, the first North American retail purchaser of this 2013 model year Glastron boat and/or trailer or a second North American retail purchaser as noted below ("you"), that it will repair or replace, at its sole discretion, defects in materials or workmanship that occur and are reported to Glastron, or its factory authorized dealer, within the applicable limited warranty periods, subject to the terms, conditions and exclusions set forth below. Your acceptance of delivery of the warranted Glastron boat and/or trailer constitutes your acceptance of the terms of this limited warranty. This limited warranty gives you specific legal rights and you may have other rights which may vary from state to state.

This limited warranty is the sole and exclusive express warranty from Glastron regarding your 2013 Glastron boat and/or trailer and there are no express warranties which extend beyond those outlined in this limited warranty. Under the laws of certain states, there may be no implied warranties from Glastron and ALL IMPLIED WARRANTIES (INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED WHERE ALLOWED BY APPLICABLE LAW. ANY IMPLIED WARRANTIES (IF APPLICABLE) ARE LIMITED TO THE MINIMUM PERIOD OF TIME ALLOWED UNDER APPLICABLE LAW. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you.

Coverage Under this Limited Warranty

<u>Trailer Limited Warranty:</u> The limited warranty period runs for one (I) year for defects in trailer components.

Exterior Cosmetic Gel Coat Limited Warranty: The limited warranty period runs for one (I) year for defects in the boat's exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except as noted below.

Non-Structural Parts and Components Limited Warranty: The limited warranty period runs for one (I) year for defects in the boat's non-structural parts and components, except as noted below.

Osmotic Hull Blister Limited Warranty: The limited warranty period to the first North American retail purchaser runs for five (5) years, except as noted below, for osmotic hull blisters on the boat, which are defined as blisters larger than 1/8" diameter and with a depth of 1/16" or greater, which occur on the boat hull below the waterline. This limited warranty is not transferrable to a second North American retail purchaser.

If the boat is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period, this limited warranty will only apply if a marine barrier coating with proper surface preparation is applied to the boat hull before it is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period.

In the event of osmotic blistering, Glastron must approve of any repairs, and their method and cost, before the repairs are performed, for this limited warranty to apply. Once any repairs are completed, a marine barrier coating will be applied to the affected hull surface area(s).

Repairs under this limited warranty are limited to one time. Any repair costs covered under this limited warranty are limited to labor and materials only. They will be paid on a prorated basis, according to the schedule outlined below. The repair costs cannot exceed \$150 (US) per foot of boat length prior to the prorating outlined helow:

Osmotic hull blistering reported to Glastron:

Amount of repair costs paid:

Less than two (2) years from date of delivery Two (2) to less than three (3) years from date of delivery Three (3) to less than four (4) years from date of delivery 100% 75% 50%





25%

Structural Component Limited Warranty: The limited warranty period to the first North American retail purchaser runs for the duration of the first North American retail purchaser's period of ownership for structural components. The limited warranty period to the second (if applicable) North American retail purchaser runs for ten (10) years, regardless of when the limited warranty is transferred to the second North American retail purchaser. For purposes of this limited warranty, the "Hull" shall mean the single fiberglass molded shell and integral structural within the shell, including stringers, floorboards, transom and related structural reinforcements, all of which are below the flange (i.e. gunwale) and the "Deck" shall mean the single fiberglass molded shell and integral fiberglass structural components above the hull flange (i.e. gunwale). A "Structural Hull Defect" shall mean a defect that causes the Hull or Deck to be unsafe or unfit for use under normal operating conditions.

The applicable limited warranty period runs from the date of delivery of the boat and/or trailer to the first North American retail purchaser, provided that the boat and/or trailer is delivered to that purchaser within twelve (12) months from the date of its manufacture. For a boat and/or trailer delivered to that purchaser more than twelve (12) months after the date of its manufacture, calculation of the remaining warranty period will run from the date of its manufacture, not from the date the boat and/or trailer was delivered to the first North American retail purchaser. For a boat and/or trailer delivered to that purchaser more than twelve (12) months and up to thirty-six (36) months after its date of manufacture, the selling dealer will be required to submit a condition report on the boat and/or trailer with photos to Glastron before delivery of the boat and/or trailer to the first North American retail purchaser; Glastron will then determine and advise what warranty coverage remains in effect on the boat and/or the trailer, if any. For a boat and/or trailer delivered to that purchaser more than thirty-six (36) months after the date of its manufacture, only the structural component limited warranty on the boat will be in effect and it runs from the date of the boat's manufacture, not from the date the boat was delivered to the first North American retail purchaser; all other limited warranties are voided. All warranties run concurrently.

Certain portions of this limited warranty, as noted above, extend only to the first North American retail purchaser. Other portions of this limited warranty, as noted above, may be transferred to a second North American retail purchaser, if the transfer occurs within five (5) years of the boat's and/or trailer's sale to the first North American retail purchaser, for a non-refundable recording fee of \$150 (US), for boats less than twenty (20) feet in length, or \$300 (US), for boats over twenty (20) feet in length, provided the second North American retail purchaser purchases the boat and/or trailer from the first North American retail purchaser or an authorized Glastron dealer. To transfer the limited warranty, the second North American retail purchaser or the authorized Glastron dealer have been to the second North American retail purchaser or the authorized Glastron dealer must send to Glastron, within fifteen (15) days of the boat's and/or trailer's purchase, at the address noted below, the: 1) first North American retail purchaser's plastic registration card, if available; 2) proof of the purchase; and 3) the non-refundable recording fee made payable to Rec Boat Holdings, LLC dba Glastron. This limited warranty may only be transferred once. Glastron will confirm all limited warranty transfers, in writing, to the authorized Glastron dealer and/or second North American retail purchaser via email. Glastron boat and/or trailer that has been damaged, neglected or otherwise previously excluded from limited warranty coverage.

THIS LIMITED WARRANTY DOES NOT COVER

- A boat and/or trailer purchased from any party other than an authorized Glastron dealer or the first North American retail purchaser.
- A boat and/or trailer, including its components, that has been altered or modified so as to adversely affect its operation, performance or durability, as determined by Glastron, or a boat and/or a trailer that has been salvaged, declared a total loss or a constructive total loss for any reason not covered in this limited warranty.
- 3. Any damage resulting from an accident or impact with another object or any damage caused by an act of nature.
- Damage, breakage and leakage around windshields, hatches or other designed openings.

- Boats or trailers that are damaged due to storage or exposure conditions including, but not limited to, sun or cold weather.
- 5. Engines, power trains, outdrives, controls, propellers, batteries, appliances and other equipment, accessories or components that are not manufactured by Glastron, whether or not they are warranted by other manufacturers. Note: it is the purchaser's responsibility to complete any warranty registration procedure that may be applicable to these components.
- 7. Window glass, mirrors, varnish, paint, fabrics and chromium, stainless steel and
- 8. Gelcoat fading or discoloration that occurs below or at the water line on the hull.
- The original gel surface that has been altered in any way, including by repair, by application of any coating other than marine barrier coating or marine barrier coating followed by bottom paint, by improper surface preparation for paint or by improper or excessive sanding, scraping or sandblasting.
- 10. The cost of removal or re-instatement of parts or disassembly of units to repair or replace components covered by this limited warranty.
- 11. A boat that has been overpowered, according to the boat's maximum recommended engine horsepower, or overloaded in excess of the maximum limits as stated on the U.S. Coast Guard Capacity Plate.
- 12. Any boat and/or a trailer that has been misused or used in a negligent manner; a boat that has been used for racing, speed or endurance contests; used for rental or charter; used for military, rescue, fire, safety, medical, police, law enforcement, patrol or similar government uses; used for commercial purposes; used without normal maintenance; operated contrary to any instruction furnished by Glastron; improperly lifted or trailered; improperly secured to a trailer; or operated in violation of any federal, state, local, Coast Guard or other governmental agency laws, rules or regulations. Also, this limited warranty does not cover any damage to a boat resulting from failure to use a lower unit support device when transporting the boat.
- Estimated characteristics such as weight, speed, range, fuel consumption or other estimated performance characteristics.
- 14. Dealer preparation, cleaning, final adjustments and alignments in preparing the boat and/or trailer for delivery.
- 15. Fit and adjustment of exterior canvas tops, enclosures and weather covers.
- 16. Sacrificial deterioration of anti-fouling paint or zinc anodes.
- 17. Damage resulting from electrolysis or corrosion of any nature from any source.
- Any failure or defect arising from previous repairs made by a non-authorized service provider, unless preapproved by Glastron.
- 19. Any defect that results in the redesign of the Glastron boat and/or trailer.
- Trailer tires, paint or Gatorhyde defects caused by fading, peeling, chipping, scratches or rusting attributed to normal use.

THE SOLE AND EXCLUSIVE REMEDY UNDER THIS LIMITED WARRANTY AND ANY APPLICABLE IMPLIED WARRANTY IS THE REPAIR OR REPLACEMENT, AT GLASTRON'S SOLE OPTION, OF WARRANTED PARTS AND COMPONENTS. GLASTRON EXCLUDES AND DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF TIME, INCONVENIENCE, INSTALLMENT PAYMENTS, INSURANCE PAYMENTS, MARINA FEES, RETAIL CHARGES, TRAVEL EXPENSES, LOSS OF USE, HAUL OUT, LAUNCH, TOWING AND/OR STORAGE CHARGES, LOSS OF OR DAMAGE TO PERSONAL PROPERTY OR OTHEI SIMILAR COSTS AND EXPENSES, OR ANY CLAIM NOT SPECIFICALLY COVERED BY THIS LIMITED WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Any legal action allegin breach of any applicable warranty coverage must be brought within one (1) year from the date the alleged breach first occurred.



GLASTRON

PRE-DELIVERY SERVICE AND WARRANTY REGISTRATION

Prior to delivering a new Glastron boat and/or trailer to the first North American rrior to delivering a new Glastron Doat and/or trailer to the lirst North American retail purchaser, the authorized dealer is required to inspect and perform all necessary pre-delivery services including completing the "Pre-Delivery Service Record" portion of the limited warranty. Any cost associated with the pre-delivery inspection is the responsibility of the first North American retail purchaser. After completion of the necessary pre-delivery services: the first North American retail completion of the necessary pre-delivery services, the first North American retail purchaser. After purchaser must sign the Glastron warranty registration form and Pre-Delivery Service Record provided by the dealer, where indicated. No warranty coverage is applicable to the boat and/or trailer unless these forms are completed, signed and pre-delivery at the address indicated below, or vice a authorized Glastron at the address indicated below, or vice a authorized Glastron. application to the boat and/or it alies unless these forms are completed, signed and returned to Glastron at the address indicated below, or via an authorized Glastron dealer's online dealer extranet.

OBTAINING REPAIRS UNDER THIS LIMITED WARRANTY

The authorized Glastron dealer will carry out the warranty procedures on your behalf. All limited warranty work will be performed at an authorized dealer, at the Glastron factory, or at another repair facility approved by Glastron. You are responsible for the expense associated with transporting the boat and/or trailer responsible from the repair facility. Glastron must receive written notice of all limited to and from the repair facility. Glastron must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to resolve them.

To obtain warranty service, you must return the boat and/or trailer, including any alleged defective part, to an authorized Glastron dealer and present the Owner's Registration Card. If necessary, you should call Glastron for assistance to locate the nearest Glastron dealer in your area. The following procedures will apply to a warranty claim:

- . A. The dealer will contact and receive an authorization number from Glastron $\boldsymbol{\mathsf{G}}$
- B. Upon completion of repairs, you must pay the dealer for non-covered items.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Glastron warranty claim form if the claim is not submitted through the Glastron Extranet by the dealer.

If sublet warranty repairs are required for any reason, the authorized Glastron dealer will be responsible for choosing a qualified and reputable repair facility and the authorized Glastron Dealer will be responsible for all work performed the authorized Glastron Dealer will be responsible for all work performed by the sublet repair facility. Before referring any work to a sublet repair facility, the authorized Glastron dealer must submit a written estimate to Glastron's claims department to obtain written pre-authorization (including a claim authorization number). Glastron will not honor or pay for claims submitted for repairs by sublet repair facilities unless this procedure has been followed. Glastron will not authorize or pay for sublet repairs initiated because of a followed. Glastron will not authorize or pay for sublet repairs initiated because of a lack of dealer service facilities.

This document contains the entire limited warranty provided by Glastron. Any This document contains the entire limited warranty provided by Glastron. Any questions concerning the scope of this limited warranty should be directed to Glastron. The terms and conditions contained in this limited warranty may not be modified, altered, or waived by any action, inaction or representation, whether oral or in writing, except upon the express, written authority of a senior management level employee of Glastron Glastron does not authorize any person or persons (except a senior management level employee of Glastron), including Glastron dealers to change the terms of this limited warranty. (Note that your authorized (except a senior management level employee of Glastron), including Glastron dealers, to change the terms of this limited warranty. (Note that your authorized Glastron dealer is an independent business, authorized to sell and service Glastron products, but is not an agent of Glastron). Glastron reserves the right to change or improve the design or manufacture of Glastron boats and/or trailers without obligation to modify any boat and/or trailer previously manufactured.

Glastron, LLC 925 Frisbie Street Cadillac, MI 49601 Telephone: (231) 775-1351

2013 Glastron Fiberglass Boats Limited Warranty (International)

Rec Boat Holdings, LLC dba Glastron ("Glastron") warrants to you, the first International retail purchaser of this 2013 model year Glastron boat or a second International retail purchaser as noted below ("you"), that it will repair or replace, at its sole discretion, defects in materials or workmanship that occur and are reported to Glastron, or its factory authorized dealer, within the applicable limited warranty periods subject to the terms conditions and exclusions set forth below. Your periods, subject to the terms, conditions and exclusions set forth below. Your periods, subject to the terms, conditions and exclusions set forth below. Your acceptance of delivery of the warranted Glastron boat constitutes your acceptance of the terms of this limited warranty. Retail purchasers in the European Union (EU) may have legal rights under applicable national legislation and the Consumers Protective Directive 1999/44/EC of the European Parliament and of the Council of 25 May 1999, governing the sale of consumer goods, which are not affected by this limited warranty. Retail purchasers in other countries may also have legal rights which are not affected by this limited warranty.

This limited warranty is the sole and exclusive express warranty from This limited warranty is the sole and exclusive express warranty from Glastron regarding your 2013 Glastron boat, and there are no express warranties which extend beyond those outlined in this limited warranty. There are no implied warranties from Glastron unless otherwise required under applicable law, and ALL IMPLIED WARRANTIES (INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED WHERE ALLOWED BY APPLICABLE LAW, ANY IMPLIED WARRANTIES (IF APPLICABLE) ARE LIMITED TO THE MINIMUM PERIOD OF TIME ALLOWED UNDER APPLICABLE LAW. ALLOWED UNDER APPLICABLE LAW.

Coverage Under this Limited Warranty: Exterior Cosmetic Gel Coat Limited Warranty: The limited warranty period runs for one (1) year for defects in the exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except

Non-Structural Parts and Components Limited Warranty: The limited warranty period runs for one (I) year for defects in non-structural parts and components, except as noted below.

Osmotic Hull Blister Limited Warranty: The limited warranty period to the first international retail purchaser runs for five (5) years, except as noted below, for osmotic hull blisters, which are blisters larger than 1/8" diameter and with a depth of 1/16" or greater, which occur on the boat hull below the waterline. This limited warranty is not transferrable to a second International retail purchaser.

If the boat is bottom painted or left in water for more than sixty (60) days in any If the boat is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period, this limited warranty will only apply if a marine barrier coating with proper surface preparation is applied to the boat hull before it is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period.

In the event of osmotic blistering, Glastron must approve of any repairs, and their method and cost, before the repairs are performed, for this limited warranty to apply. Once any repairs are completed, a marine barrier coating will be applied to the affected hull surface area(s).

Repairs under this limited warranty are limited to one time. Any repair costs covered under this limited warranty are limited to labor and materials only. They will be paid on a prorated basis, according to the schedule outlined below. The repair costs cannot exceed \$150 (US) per foot of boat length prior to the prorating outlined

. 1

Osmotic hull blistering	Amount o	repair
reported to Glastron: costs paid: Less than two (2) years from date of delivery Two (2) to less than three (3) years from date of delivery Three (3) to less than four (4) years from date of delivery Four (4) to five (5) years from date of delivery	very ivery	100% 75% 50% 25%

Structural Component Limited Warranty:

Structural Component Limited Warranty: The limited warranty period to the first International retail purchaser runs for the duration of the first International retail purchaser's period of ownership for structural components. The limited warranty period to the second (if applicable) International retail purchaser runs for ten (10) years, regardless of when the limited warranty is transferred to the second International retail purchaser. For purposes of this limited warranty, the "Hull" shall mean the single fiberglass molded shell and integral structural within the shell, including stringers, floorboards, transom and related structural reinforcements, all of which are below the flange (i.e. gunwale) and the "Deck" shall mean the single fiberglass molded shell and integral fiberglass structural components above the hull flange (i.e. gunwale). A "Structural Hull Defect" shall mean a defect that causes the Hull or Deck to be unsafe or unfit for use under normal operating conditions.

The applicable limited warranty period runs from the date of delivery of the boat to the first International retail purchaser, provided that the boat is delivered to that purchaser within twelve (12) months from the date of its manufacture. For a boat delivered to that purchaser more than twelve (12) months after the date of its manufacture, calculation of the remaining warranty period will run from the date of its manufacture, not from the date the boat was delivered to the first International retail purchaser. For a boat delivered to that purchaser more than twelve (12) months and up to thirty-six (36) months after its date of manufacture, the selling dealer will be required to submit a condition report on the boat with photos to Glastron before delivery of the boat to the first International retail purchaser; Glastron will then determine and advise what warranty coverage remains in effect on the boat, if any. For a boat delivered to that purchaser more than thirty-six (36) months after the date of its manufacture, only the structural component limited warranty on the boat will be in effect and it runs from the date of the boat's manufacture, not from the date the boat was delivered to the first International retail purchaser; all other limited warrantes are voided. All warranties run concurrently.

Certain portions of this limited warranty, as noted above, extend only to the first International retail purchaser. Other portions of this limited warranty, as noted above, may be transferred to a second International retail purchaser, if the transfer occurs within five (5) years of the boat's and/or trailer's sale to the first International retail purchaser, for a non-refundable recording fee of \$150 (US), for boats less than twenty (20) feet in length, or \$300 (US), for boats over twenty (20) feet in length, provided the second International retail purchaser purchases the boat and/or trailer from the first International retail purchaser or an authorized Glastron dealer. To transfer the limited warranty, the second International retail purchaser or the authorized Glastron dealer must send to Glastron, within fifteen (15) days of the boat's and/or trailer's purchase, at the address noted below, the: 1) first International retail purchaser's plastic registration card, if available; 2) proof of the purchase; and 3) the non-refundable recording fee made payable to Rec Boat Holdings, LLC dba Glastron. This limited warranty may only be transferred once. Glastron will confirm all limited warranty transfers, in writing, to the authorized Glastron dealer and/or second International retail purchaser via email. Glastron reserves the right to reject a limited warranty transfer request for a Glastron boat that has been damaged, neglected or otherwise previously excluded from limited warranty coverage.

THIS LIMITED WARRANTY DOES NOT COVER

- A boat purchased from any party other than an authorized Glastron dealer or the first International retail purchaser.
- A boat, including its components, that has been altered or modified so as to
 adversely affect its operation, performance or durability, as determined by
 Glastron, or a boat that has been salvaged, declared a total loss or a constructive
 total loss for any reason not covered in this limited warranty.
- Any damage resulting from an accident or impact with another object or any damage caused by an act of nature.
- Damage, breakage and leakage around windshields, hatches or other designed openings.
- Boats that are damaged due to storage or exposure conditions including, but not limited to, sun or cold weather.

- 6. Engines, power trains, outdrives, controls, propellers, batteries, appliances and other equipment, accessories or components that are not manufactured by Glastron, whether or not they are warranted by other manufacturers. Note: it is the purchaser's responsibility to complete any warranty registration procedure that may be applicable to these components.
- Window glass, mirrors, varnish, paint, fabrics and chromium, stainless steel and other metal finishes.
- 8. Gelcoat fading or discoloration that occurs below or at the water line on the hull.
- 9. The original gel surface that has been altered in any way, including by repair, by application of any coating other than marine barrier coating or marine barrier coating followed by bottom paint, by improper surface preparation for paint or by improper or excessive sanding, scraping or sandblasting.
- 10. The cost of removal or re-instatement of parts or disassembly of units to repair or replace components covered by this limited warranty.
- II. A boat that has been overpowered, according to the boat's maximum recommended engine horsepower, or overloaded in excess of the maximum limits as stated on the U.S. Coast Guard Capacity Plate.
- 12. Any boat that has been misused or used in a negligent manner; a boat that has been used for racing, speed or endurance contests; used for rental or charter; used for military, rescue, fire, safety, medical, police, law enforcement, patrol or similar government uses; used for commercial purposes; used without normal maintenance; operated contrary to any instruction furnished by Glastron; improperly lifted or trailered; improperly secured to a trailer; or operated in violation of any federal, state, local, Coast Guard or other governmental agency laws, rules or regulations. Also, this limited warranty does not cover any damage to a boat resulting from failure to use a lower unit support device when transporting the boat.
- Estimated characteristics such as weight, speed, range, fuel consumption or other estimated performance characteristics.
- 14. Dealer preparation, cleaning, final adjustments and alignments in preparing a boat for delivery.
- 15. Fit and adjustment of exterior canvas tops, enclosures and weather covers.
- 16. Sacrificial deterioration of anti-fouling paint or zinc anodes.
- 17. Damage resulting from electrolysis or corrosion of any nature from any source.
- 18. Any failure or defect arising from previous repairs made by a non-authorized service provider, unless preapproved by Glastron.
- 19. Any defect that results in the redesign of a Glastron boat.
- 20 Trailers

THE SOLE AND EXCLUSIVE REMEDY UNDER THIS LIMITED WARRANTY AND ANY APPLICABLE IMPLIED WARRANTY IS THE REPAIR OR REPLACEMENT, AT GLASTRON'S SOLE OPTION, OF WARRANTED PARTS AND COMPONENTS. GLASTRON EXCLUDES AND DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF TIME, INCONVENIENCE, INSTALLMENT PAYMENTS, INSURANCE PAYMENTS, MARINA FEES, RETAIL CHARGES, TRAVEL EXPENSES, LOSS OF USE, HAUL OUT, LAUNCH, TOWING AND/OR STORAGE CHARGES, LOSS OF OR DAMAGE TO PERSONAL PROPERTY OR OTHER SIMILAR COSTS AND EXPENSES OR ANY CLAIM NOT SPECIFICALLY COVERED BY THIS LIMITED WARRANTY. Any legal action alleging breach of any applicable warranty coverage must be brought within one (1) year from the date the alleged breach first occurred or the shortest period of time allowed under applicable law. Any claim by a retail purchaser in the EU that the boat was nonconforming at the time of delivery must be made within two (2) years from the date of delivery.

PRE-DELIVERY SERVICE AND WARRANTY REGISTRATION

Prior to delivering a new Glastron boat to the first International retail purchaser, the authorized dealer is required to inspect and perform all necessary pre-delivery services including completing the "Pre-Delivery Service Record" portion of the limited warranty. Any cost associated with the pre-delivery inspection is the responsibility of the first International retail purchaser. After completion of the necessary pre-delivery services, the first International retail purchaser must sign the Glastron warranty registration form and Pre-Delivery Service Record provided by the dealer, where indicated. No warranty coverage is applicable to the boat unless these forms are completed, signed and returned to Glastron at the address indicated below, or via an authorized Glastron dealer's online dealer extranet.

OBTAINING REPAIRS UNDER THIS LIMITED WARRANTY

The authorized Glastron dealer will carry out the warranty procedures on your behalf. All limited warranty work will be performed at an authorized dealer, at the Glastron factory, or at another repair facility approved by Glastron. You are responsible for the expense associated with transporting the boat to and from the repair facility. Glastron must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to respoke them.

To obtain warranty service, you must return the boat, including any alleged defective part, to an authorized Glastron dealer and present the Owner's Registration Card. If necessary, you should call Glastron for assistance to locate the nearest Glastron dealer in your area. The following procedures will apply to a warranty claim:

- A. The dealer will contact and receive an authorization number from Glastron for repairs.
- B. Upon completion of repairs, you must pay the dealer for non-covered items.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Glastron warranty claim form if the claim is not submitted through the Glastron Extranet by the dealer.

If sublet warranty repairs are required for any reason, the authorized Glastron dealer will be responsible for choosing a qualified and reputable repair facility and the authorized Glastron Dealer will be responsible for all work performed by the sublet repair facility. Before referring any work to a sublet repair facility, the authorized Glastron dealer must submit a written estimate to Glastron's claims department to obtain written pre-authorization (including a claim authorization number). Glastron will not honor or pay for claims submitted for repairs by sublet repair facilities unless this procedure has been followed. Glastron will not authorize or pay for sublet repairs initiated because of a lack of dealer service facilities.

This document contains the entire limited warranty provided by Glastron. Any questions concerning the scope of this limited warranty should be directed to Glastron. The terms and conditions contained in this limited warranty may not be modified, altered, or waived by any action, inaction or representation, whether oral or in writing, except upon the express, written authority of a senior management level employee of Glastron Glastron does not authorize any person or persons (except a senior management level employee of Glastron), including Glastron dealers, to change the terms of this limited warranty. (Note that your authorized Glastron dealer is an independent business, authorized to sell and service Glastron products, but is not an agent of Glastron). Glastron reserves the right to change or improve the design or manufacture of Glastron boats and/or trailers without obligation to modify any boat and/or trailer previously manufactured.

Glastron, LLC 925 Frisbie Street Cadillac, MI 49601 Telephone: (231) 775-1351

GT 160 CB

GTS 160 CB

Specifications

LOA 16' 6" (5.03 m) Beam 7' 0" (2.13 m) Total Height 4'3" (1.3 m.) Cockpit Height at Helm 25" (63 cm.) Approx. boat & engine weight 1900 lbs. (861 kg)

Drive Unit Up 14" (35.6 cm.) Draft Drive Unit Down 301/4" (76.8 cm.) Deadrise 17° Fuel Capacity 12 gallons (45/68 L.) Maximum Load 1590 lbs (720 kg.) Maximum Persons 6 (USA) (5 CE) Trailer Weight Single 754 lbs. (342 kg) Maximum Horsepower 115 (86 kw)

Standard Features

Instrumentation, helm: tachometer and Curved glass windshield with walk-thru speedometer, navigation lights & courtesy lights Aft swim platforms All white deck Automatic bilge pump Color match single axle trailer w/brakes Custom non-directional steering wheel Dash, chrome pull switches Electric horn Fiberglass floor **Bucket seats** Courtesy lights

Drink holders 3 cleats Glove box w/hinge & latch Grab handles Gunneling, white plastic w/flex chrome insert Hinged ski locker lid Merc/Brp/Yam prop Navigation lighting Stainless steel bow & stern eyes Storage under bow Two-tone colored hull

Optional Features

XL Package: Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (3), Bow

scuff plate, Chrome vent, Ski pylon, Two tone deck, Spear Graphics, Close deck only: deck plate

Color Choices

White & Electric Yellow White & Jet Black

GTL package:

Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat, Fiberglass seat back, XL pkg, Stereo upgrade, Fiberglass seat back, LED lights - bow.

White & Royal Blue White & Laser Red

Specifications

LOA 16' 6". (5.03 m) Beam 7' 0" (2.13 m) Total Height 4'3" (1.3 m.) Cockpit Height at Helm 25" (63 cm.) Approx. boat & engine weight 1900 lbs. (861 kg)

Draft Drive Unit Up 14" (35.6 cm.) Draft Drive Unit Down 301/4" (76.8 cm.) Deadrise 17° Fuel Capacity 12 gallons (45/68 L.) Maximum Load 1590 lbs (720 kg.) Maximum Persons 6 (USA) (5 CE) Trailer Weight Single 754 lbs. (342 kg) Maximum Horsepower 115 (86 kw)

Standard Features

Aft swim platforms Automatic bilge pump **Bucket seats** Color coordinated upgrade steering wheel Color match single axle trailer w/brakes Courtesy lights Curved glass windshield with walk-thru Dash, chrome pull switches Drink holders Electric horn Fiberglass floor Glove box w/hinge & latch Grab handles Hinged ski locker lid

3 cleats GTS Cockpit interior GTS Gel Scheme & Graphics GTS two tone deck & hull GTS Yellow gauges Gunneling, black plastic w/flex chrome insert Instrumentation, helm: tachometer and speedometer, navigation lights & courtesy lights LED lights - bow Merc/Brp/Yam prop Navigation lighting Stainless steel bow & stern eyes Storage under bow seat Swim platform mat

Optional Features

XL Package:

Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (3), Bow scuff plate, Chrome vent, Ski pylon, Closed deck only: deck plate

Single Options: Bimini top w/boot Bow Scuff Plate Care cover (black) Color coordinated Bow cover Color coordinated Cockpit cover

Color Choices

White w/Jet Black Gel coat White w/Laser Red Gel coat Fixed fuel tank -18 Gal Side glass wings Stereo w/2 speakers covers & MP3 adaptor Ski pylon Snap-in carpet Tilt steering hydraulic High altitude prop Retractable ladder

Trailer Options: Spare Tire w/mount Galvanized W/ GatorHyde finish

GT 160 BR

GTS 160 BR

Specifications

LOA 16' 6" (5.03 m) Beam 7' 0" (2.13 m) Total Height 4'3" (1.3 m.) Cockpit Height at Helm 25" (63 cm.) Approx. boat & engine weight 1900 lbs. (861 kg)

Trailer Weight Single 754 lbs. (342 kg)

Maximum Persons 6 (USA) (5 CE)

Maximum Horsepower 115 (86 kw)

Draft Drive Unit Up 14" (35.6 cm.) Draft Drive Unit Down 301/4" (76.8 cm.) Deadrise 17° Fuel Capacity 12 gallons (45/68 L.) Maximum Load 1590 lbs (720 kg.) Maximum Persons 6 (USA) (5 CE)

Standard Features

Aft swim platforms Automatic bilge pump **Bucket seats** Color coordinated upgrade steering wheel
Color match single axle trailer w/brakes Courtesy lights Curved glass windshield with walk-thru Dash, chrome pull switches Drink holders Electric horn Fiberglass floor Glove box w/hinge & latch Grab handles Hinged ski locker lid 3 cleats

GTS Cockpit interior GTS Gel Scheme & Graphics GTS two tone deck & hull GTS Yellow gauges Gunneling, black plastic w/flex chrome insert Instrumentation, helm: tachometer and speedometer, navigation lights & courtesy lights LED lights - bow Merc/Brp/Yam prop Navigation lighting Stainless steel bow & stern eyes Storage under bow seat Swim platform mat.

Optional Features

XL Package: Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (3), Bow scuff plate, Chrome vent, Ski

pylon, Two tone deck, Spear Graphics, Close deck only: deck plate

GTL package:

Upgrade interior in Saddle or Cashmere Ski pylon Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat, Fiberglass seat back, XL pkg, Stereo upgrade, Fiberglass seat back, LED lights - bow

Single Options: Bimini top w/boot Bow Scuff Plate Care cover (black) Color coordinated Bow cover Color coordinated Cockpit cover Fixed fuel tank -18 Gal LED lights - bow Two tone deck High altitude prop Side glass wings Snap-in carpet Stereo w/2 speakers covers & MP3 adaptor Swim platform mat Tilt steering hydraulic Retractable ladder

Trailer Options: Spare Tire w/mount Galvanized W/ GatorHyde finish

Color Choices

White w/let Black Gelcoat White w/Laser Red Gelcoat White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat

Specifications

LOA 16' 6" (5.03 m) Beam 7'0" (2.13 m) Total Height 4'3" (1.3 m.) Cockpit Height at Helm 25" (63 cm.) Approx. boat & engine weight 1900 lbs. (861 kg)

Maximum Persons 6 (USA) (3 CE)

Trailer Weight Single 754 lbs. (342 kg)

Maximum Horsepower 115 (86 kw)

Draft Drive Unit Up 14" (35.6 cm.) Draft Drive Unit Down 301/4" (76.8 cm.) Deadrise 17 Fuel Capacity 12 gallons (45/68 L.) Maximum Load 1590 lbs (720 kg.) Maximum Persons 6 (USA) (5 CE)

Standard Features

Aft swim platforms Automatic bilge pump **Bucket seats** Color coordinated upgrade steering wheel Color match single axle trailer w/brakes Courtesy lights Curved glass windshield with walk-thru Dash, chrome pull switches Drink holders Electric horn Fiberglass floor Glove box w/hinge & latch Grab handles Hinged ski locker lid 3 cleats

GTS Cockpit interior GTS Gel Scheme & Graphics GTS two tone deck & hull GTS Yellow gauges Gunneling, black plastic w/flex chrome insert Instrumentation, helm: 5" tachometer and speedometer, navigation lights & courtesy lights LED lights - bow Merc/Brp/Yam prop Navigation lighting Stainless steel bow & stern eyes Storage under bow seat Swim platform mat

Optional Features

XL Package:

Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (3), Bow scuff plate, Chrome vent, Ski pylon.

Single Options: Bimini top w/boot Bow Scuff Plate Care cover (black) Color coordinated Bow cover Color coordinated Cockpit cover Fixed fuel tank -18 Gal Side glass wings Stereo w/2 speakers covers & MP3 adaptor Ski pylon Snap-in carpet Tilt steering hydraulic High altitude prop Retractable ladder

Trailer Options: Spare Tire w/mount Galvanized W/ GatorHyde finish

Color Choices

White w/let Black Gel coat White w/Laser Red Gel coat

GTSF 160 BR

PERFORMANCE DATA FOR GT 160's (all inclusive)

Specifications

LOA 16' 6" (5.03 m) Beam 7' 0" (2.13 m) Total Height 4'3" (1.3 m.) Cockpit Height at Helm 25" (63 cm.) Approx. boat & engine weight

Draft Drive Unit Up 14" (35.6 cm.) Draft Drive Unit Down 301/4" (76.8 cm.) Deadrise 17° Fuel Capacity 12 gallons (45/68 L.) Maximum Load 1590 lbs (720 kg.) Maximum Persons 6 (USA) (5 CE) 1940 lbs. (880 kg)

Maximum Persons 6 (USA) (5 CE)

Trailer Weight Single 754 lbs. (342 kg)

Maximum Horsepower II5 (86 kw)

Standard Features

Aft swim platforms Automatic bilge pump Bow casting platform Bucket seats Casting fishing seat (2) Color match single axle trailer w/brakes Courtesy lights Curved glass windshield with walk-thru Custom non-directional steering wheel Dash, chrome pull switches Drink holders Electric horn Fiberglass floor Instrumentation, helm: 5" tachometer and speedometer nav lights & courtesy lights

4 cleats Glove box w/hinge & latch Grab handles Gunneling, white plastic w/flex chrome insert Hinged ski locker lid Merc/Brp/Yam prop Navigation lighting Rod holders (2) Rod storage S & F Gel Scheme & Graphics S & F two tone deck & hull Stainless steel bow & stern eyes Storage under bow seat Trolling motor mount

Optional Features

XL Package:

Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (4), Bow scuff plate, Chrome vent, Ski pylon

Fishing Package: 12 volt trolling motor w/removable plate & fish finder

Single Options: Bimini top w/boot

Bow Scuff Plate Color coordinated Bow cover Color coordinated Cockpit cover

Color Choices

White w/jet Black Gelcoat White w/Laser Red Gelcoat

Fixed fuel tank -18 Gal LED lights - bow High altitude prop Side glass wings Ski pylon Snap-in carpet Stereo w/2 speaker,SS covers & MP3 adaptor Swim platform mat Tilt steering hydraulic Retractable ladder

Trailer Options:

Spare Tire w/mount Galvanized W/ GatorHyde finish

White w/Royal Blue Gelcoat

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model .	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
GT 160 LBS	Merc 115 ProXS	1200	375	72	80	754
GT 160 KG	Merc 115 ProXS	544	170	33	36	342

PERFORMANCE

	Prope (Dia x l		Туре	Тор	Speed	Cruise	Range
Power hp (kw)	IN	СМ		МРН	КРН	MI	КМ
EV 75 E-TEC 75 hp (56kw)	13 I/4 X 17	34 X 43	AL	38-41	61-66	50	81
EV 90 E-TEC 90 hp (67kw)	13 I/4 X 17	34 X 43	AL	40-43	64-69	50	81
EV IIS E-TEC. IIS hp (86kw)	13 I/4 X I7	34 _. X 43	AL	43-46	69-74	50	81
Merc 75 Opti 75 hp (56kw)	13 X 19	33 X 48	AL	39-41	63-66	50	81
Merc 90 Opti 90 hp (67kw)	13 X 19	33 X 48	ÅL	41-44	66-71	50	81
Merc II5 ProXS II5 hp (86kw)	13 X 19	33 X 48	AL	46-49	74-79	50	81
Yam F75 75 hp (56kw)	13 X 19	33 X 48	AL	39-41	63-66	50	. 81
Yam F90 90 hp (67kw)	13 X 19	33 X 48	ĄL	41-44	66-71	50	81
Yam FII5 II5 hp (86kw)	13 × 19	33 X 48	AL	45-48	72-77	50	81

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

LOA 17' 10" (5.44 m) Beam 7' 5" (2.26 m) Total Height 4' 10" (1.47 m.) Cockpit Height at Helm 29.5" (76 cm.) Approx. boat & engine weight 2100 lbs. (950 kg)
Trailer Weight Single 639 lbs. (290 kg)

Draft Drive Unit Up 14" (36 cm.) Draft Drive Unit Down 30" (76. cm.) Deadrise 20° Fuel Capacity 24 gallons (91 L.) Maximum Load 1800 lbs (816 kg.) Maximum Persons 8 (USÀ) (7 ČÉ) Maximum Horsepower 115 (86 kw)

Standard Features

Instrumentation, helm: Speedometer, Tachometer, Fuel gauge, Volt gauge Chrome pull switches for bilge pump, navigation/anchor lights, lights, horn & stereo Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Cleats, stainless steel (3) Color match single axle trailer w/brakes Courtesy light Electric horn w/ss grill Fiberglass floor w/built-in footrests Glove box w/hinge & latch

Gunneling, white plastic w/flex chrome insert Hinged ski & wake board locker lid Molded swim platform Navigation lighting Seating: 2 bucket seats/aft bench seat Sony stereo & mp3 adapter, speakers (2) Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Steering wheel, non-directional Synthetic grab handles Two-tone hull

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), Ski pylon, Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (5), Bow scuff plate, Chrome vent, Two tone deck, Spear graphics

Convenience Package:

12 volt trolling motor w/removable plate & fish finder

Legacy Package:

Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat, Fiberglass seat back, Stereo upgrade, XL package

Color Choices

White w/Jet Black Gelcoat White w/Laser Red Gelcoat Single Options:

Bow fill-in cushions **Bow Scuff Plate** Care cover (black) Color coordinated Bimini top w/boot Color coordinated Bow cover Color coordinated Cockpit cover Flip-up buckets (2) High altitude prop Side glass wings Ski pylon. Snap-in carpet Swim platform mat Tilt steering hydraulic Two tone deck Wakeboard tower Wakeboard tower w/black bimini top

Trailer Options: Spare Tire w/mount Gatorhyde galvanized finish

White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat

Specifications

LOA 17' 10" (5.44 m) Beam 7' 5" (2.26 m) Total Height 4' 10" (1.47 m.) Cockpit Height at Helm 29.5" (76 cm.) Approx. boat & engine weight 2100 lbs. (950 kg) Trailer Weight Single 639 lbs. (290 kg)

Draft Drive Unit Up 14" (36 cm.) Draft Drive Unit Down 30" (76. cm.) Deadrise 20° Fuel Capacity 24 gallons (91 L.) Maximum Load 1800 lbs (816 kg.) Maximum Persons 8 (USA) (7 CE) Maximum Horsepower 115 (86 kw)

Standard Features

Instrumentation, helm: Speedometer, Tachometer, Fuel gauge, Volt gauge Seating: 2 bucket seats and Chrome pull switches for bilge aft bench seat. Chrome pull switches for bilge pump, navigation/anchor lights, lights, horn & stereo Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Color match single axle trailer w/brakes Courtesy light Electric horn w/stainless steel grill Fiberglass floor w/built-in footrests Glove box w/hinge & latch Gunneling, black plastic w/flex chrome insert Hinged ski & wake board locker lid Molded swim platform w/swim platform mat

Navigation lighting Sony stereo & mp3 adapter, speakers (2) Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless steel cleats Synthetic grab handles Úpgradeď steering wheel, non-directional Walk thru windshield GTS two-tone deck & hull GTS Gel Scheme & graphics GTS cockpit interior GTS Yellow gauges

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), Ski pylon, Chrome vent, Custom snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (5). Bow scuff plate

Optional Package:

XL Package: Convenience package, Flip-up bucket seats (2), Ski pylon, Chrome vent, Custom snap-in carpet, Stainless steel drink Ski pylon holders, Stainless steel speaker Tilt steer covers, Stainless steelgrab handles, Pull up cleats (5). Bow scuff plate

Convenience Package: Hour meter, Depth sounder

Color Choices

White w/let Black Gelcoat White w/Laser Red Gelcoat

Single Options: Bow Fill-in cushions Bow Scuff Plate Care cover (black)
Color coordinated Bimini top w/boot Color coordinated Bow cover Color coordinated Cockpit cover Wakeboard tower Wakeboard tower w/black bimini top Custom snap-in carpet Flip-up buckets (2) High Altitude Prop Side glass wings Tilt steering hydraulic

Trailer Options: Spare Tire w/mount Gatorhyde galvanized finish

White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat

GTSF 180

PERFORMANCE DATA FOR GT 180's (all inclusive)

Specifications

LOA 17' 10" (5.44 m) Beam 7' 5" (2.26 m) Total Height 4' 10" (1.47 m.) Cockpit Height at Helm 29.5" (76 cm.)

Approx. boat & engine weight 2140 lbs. (971 kg) Trailer Weight Single 861 lbs. (391 kg)

Draft Drive Unit Up 15" (38 cm.) Draft Drive Unit Down 31" (79, cm.) Deadrise 20° Fuel Capacity 24 gallons (91 L.)
Maximum Load 1800 lbs (816 kg.)
Maximum Persons 8 (USA) (7 CE) Maximum Horsepower 150 (112 kw)

Standard Features

Instrumentation, helm: Speedometer, Tachometer, Fuel gauge, Volt gauge Chrome pull switches for bilge Rod storage pump, navigation/anchor lights, lights, horn & stereo

Aerated live well Bilge pump, automatic Bow fishing platform Built-in cockpit side storage Casting fishing seat (2) Color match single axle trailer w/brakes Electric horn w/ ss grill Fiberglass floor w/built-in footrests Glove box w/hinge & latch Gunneling, white plastic w/flex chrome insert Hinged ski & wake board locker lid

Reversible bow seats w/storage Rod storage S & F Gel Scheme hull S & F two tone deck & hull Seating: 2 bucket seats/aft bench seat Ski & Fish graphics Sony stereo & mp3 adapter, speakers (2) Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless steel cleats (4) Steering wheel, non-directional Synthetic grab handles Trolling motor mount Walk thru windshield

Molded swim platform **Optional Features**

XL Package:

Convenience package, Ski pylon, Snap-in carpet, Chrome vent, Stainless steel drink holders, Two tone deck, Stainless steel speaker covers, Stainless steel grab handles, Side glass wings Pull up cleats (4). Bow scuff plate, Flip up bucket seats (2)

Convenience Package: Hour meter, Depth sounder

Fishing Package: 24 volt trolling motor w/removable plate & fish finder

Single Options: Bow Scuff Plate Color coordinated Bimini top w/boot Color coordinated Bow cover Color coordinated Cockpit cover Wakeboard tower Wakeboard tower w/black bimini top High Altitude Prop Ski pylon Snap-in carpet Swim platform mat Tilt steering hydraulic

Trailer Options: Trailer Spare Tire w/mount

Color Choices

S & F Gel Scheme white w/Laser Red Gelcoat S & F Gel Scheme white w/Laser Red Gelcoat S & F Gel Scheme white w/Royal Blue Gelcoat

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
Model	Liig. 17pc			144	100	639
GT 180 LBS	Merc 115 4S	1600	400	144		200
GT 180 KG	Merc 115 4S	726	181	65	45	290

PERFORMANCE

Propeller (Dia x Pitch)		Туре	Top Speed		Cruise Range	
IN	СМ		MPH	КРН	Мі	км
13 1/4 X 17	34 X 43	AL	38-41	61-66	· 110	180
13 1/4 X 17	34 X 43	AL	41-44	66-71	110	180
14.8 x 17	38 X 43	AL	45-48	72-77	110	180
13 1/4 × 17	34 X 43	. AL .	38-41	61-66	110	180
13 1/4 X 17	34 X 43	AL	41-44	66-71	120	190
14 1/2 19	37 X 48	AL	47-50	76-81	120	190
13 1/4 X 17	34 X 43	AL	38-41	61-66	110	180
13 1/4 X 17	34 X 43	AL	41-44	66-71	110	180
14 X 19	36 X 48	AL	47-50	76-81	120	190
	(Dia x Pi IN 13 1/4 × 17 13 1/4 × 17 14.8 × 17 13 1/4 × 17 14 1/2 19 13 1/4 × 17 13 1/4 × 17	(Dia x Pitch) IN CM 13 1/4 × 17 34 × 43 13 1/4 × 17 34 × 43 14.8 × 17 38 × 43 13 1/4 × 17 34 × 43 13 1/4 × 17 34 × 43 14 1/2 19 37 × 48 13 1/4 × 17 34 × 43 13 1/4 × 17 34 × 43	(Dia x Pitch) Type IN CM 13 1/4 X 17 34 X 43 AL 13 1/4 X 17 34 X 43 AL 14.8 x 17 38 X 43 AL 13 1/4 X 17 34 X 43 AL	IN CM MPH	IN CM MPH KPH	IN CM MPH KPH MI

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

LOA 18' 0" (5.49 m) Beam 7' 5" (2.26 m) Total Height 4' 10" (1.47 m.) Cockpit Height at Helm 29.5" (75 cm.)

Approx. boat & engine weight 2400 lbs. (1,090 kg)
Trailer Weight Single 861 lbs. (390 kg)



Draft Drive Unit Up 16" (41 cm.) Draft Drive Unit Down 33" (84 cm.) Deadrise 20° Fuel Capacity 24 gallons (91 L.) Maximum Load 1200 lbs (544 kg.) Maximum Persons 8 (USA) (7 CE Maximum Horsepower 225 (168 kw)

Standard Features

Instrumentation, helm: Speedometer, tachometer, volt/temp/oil,trim & fuel gauge, Chrome pull switches for bilge pump, navigation/anchor lights, lights, horn & accessories

Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Cleats, stainless steel (3) Color match single axle trailer w/brakes Stainless steel bow & stern eyes Courtesy light Electric horn w/ss grill
Fiberglass floor w/built-in footrests
& floor drains

Glove box w/hinge & latch

Gunneling, white plastic w/flex chrome insert Hinged ski & wake board locker lid Molded swim platform Navigation lighting Seating: 2 bucket seats/aft bench seat Sony stereo & mp3 adapter, speakers (2) Stainless steel 3-step ladder w/grab handle

Steering wheel, non-directional Synthetic grab handles Two-tone hull Walk thru windshield

Optional Features

XL Package:

* Convenience package, Flip-up bucket seats (2), Tilt steering, Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Color coordinated Bow cover Pull up cleats (5), Bow scuff plate, Chrome vent, Two tone deck, Spear graphics

Convenience Package: Hour meter, Depth sounder

Legacy Package: Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Świm platform mat, Fiberglass seat back, Stereo upgrade, XL package *Included with the Legacy package

Color Choices

White w/Jet Black Gelcoat White w/Laser Red Gelcoat Single Options:

Bow fill-in cushions Bow scuff plate Care cover (black) Color coordinated Bimini top w/boot Color coordinated Cockpit cover Flip-up buckets (2) High altitude prop Side glass wings Snap-in carpet Swim platform mat Tilt steering Two Tone Deck Wakeboard tower Wakeboard tower w/bimini top (black)

Trailer Options: Spare Tire w/mount Gatorhyde galvanized finish

White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat

Specifications

LOA 18' 0" (5.49 m) Beam 7' 5" (2.26 m) Total Height 4' 10" (1.47 m.) Cockpit Height at Helm 29.5" (75 cm.) Approx. boat & engine weight 2400 lbs. (1,090 kg) Trailer Weight Single 861 lbs. (390 kg)

Draft Drive Unit Up 16" (41 cm.) Draft Drive Unit Down 33" (84 cm.) Deadrise 20 Fuel Capacity 24 gallons (91 L.) Maximum Load 1200 lbs (544 kg.) Maximum Persons 8 (USA) (7 CE) Maximum Horsepower 225 (168 kw)

Standard Features

Instrumentation, helm: Speedometer, tachometer, Fuel gauge, Chrome pull switches for bilge pump, navigation/anchor lights, panel lights, horn & accessories Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Color match w/brakes Courtesy light Electric horn w/stainless steel grill Fiberglass floor w/built-in footrests & floor drains Glove box w/hinge & latch

Gunneling, white plastic w/flex chrome insert Hinged ski & wake board locker lid

Molded swim platform w/swim platform mat Navigation lighting Seating: 2 bucket seats and aft bench seat Sony stereo & mp3 adapter, speakers (2) Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless Steel cleats (5)

Synthetic grab handles Upgraded steering wheel, nondirectional Two-tone hull Walk thru windshield GTS two-tone deck & hull GTS Gel Scheme & graphics

GTS cockpit interior GTS Yellow gauges

Optional Features

XL Package:

XL Package: Tilt steering, Convenience package, Flip-up bucket seats (2), Custom snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats, Bow scuff plate, Chrome vents

Convenience Package: Hour meter, Depth sounder

Single Options: Bow Fill-in cushions Bow scuff plate Care cover (black)

Color Choices

Two Tone Deck & Hull:

Color coordinated Bimini top w/boot Color coordinated Bow cover Color coordinated Cockpit cover Custom snap-in carpet Flip-up buckets (2) Side glass wings Tilt steering Wakeboard tower Wakeboard tower w/bimini top (black) High Altitude Prop

Trailer Options: Spare Tire w/mount Gatorhyde galvanized finish

GTS Gel Scheme Jet Black GTS Gel Scheme Laser Red

GTSF 185

PERFORMANCE DATA FOR GT 185's (all inclusive)

Specifications

Total Height 4' 10" (5.49 m)

Beam 7' 5" (2.26 m)

Total Height 4' 10" (1.47 m.)

Cockpit Height at Helm

29.5" (75 cm.)

Approx. boat & engine weight 2450 lbs. (I,110 kg) Trailer Weight Single 861 lbs. (390 kg)

Draft Drive Unit Up 17" (43 cm.) Draft Drive Unit Down 34" (86 cm.) Deadrise 20° Fuel Capacity 24 gallons (91 L.) Maximum Load 1200 lbs (544 kg.) Maximum Persons 8 (USA) (7 CE) Maximum Horsepower 225 (168 kw)

Standard Features

Instrumentation, helm 5" & 2": Speedometer, Tachometer, Fuel gauge, Chrome pull switches for bilge pump, navigation/anchor lights, panel lights, horn & accessories

Aerated live well
Aft fishing platform
Bilge pump, automatic
Bow fishing platform
Built-in cockpit side storage
Casting fishing seat (2)
Color match trailer w/brakes
Electric horn w/ ss grill
Fiberglass floor w/built-in footrests &
floor drains

Glove box w/hinge & latch Gunneling, white plastic w/flex chrome insert Hinged ski & wake board locker lid
Reversible bow seats w/storage
Rod holders (2)
Rod storage
S & F Gel Scheme hull
S & F two tone deck & hull
Seating: 2 bucket seats/aft bench seat
Ski & Fish graphics
Sony stereo & mp3 adapter,
speakers (2)
Stainless steel 3-step ladder w/grab
handle
Stainless steel bow & stern eyes
Stainless steel cleats (4)
Steering wheel, non-directional
Synthetic grab handles

Optional Features

XL Package:

Convenience package, Snap-in carpet, Chrome vent, Tilt steering, Stainless steel drink holders, Two tone deck, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (4). Bow scuff plate

Convenience Package: Hour meter, Depth sounder

Fishing Package:

24 volt trolling motor w/removable plate & fish finder

Single Options:

Trolling motor mount

Walk thru windshield

Bow scuff plate
Care cover (black)
Color coordinated Bimini top w/boot
Color coordinated Bow cover
Color coordinated Cockpit cover
Wakeboard tower
Wakeboard tower w/bimini top (black)
Flip-up buckets (2)
High Altitude Prop
Side glass wings
Snap-in carpet
Swim platform mat
Tilt steering

Trailer Options: Spare Tire w/mount

Color Choices

S & F Gel Scheme white w/Jet Black Gelcoat S & F Gel Scheme white w/Laser Red Gelcoat S & F Gel Scheme white w/Royal Blue Gelcoat

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
GT 185 LBS	MC 4.3MPI	1590	. 910	144	100	861
GT 185 KG	MC 4.3MPI	721	413	65	45	390

PERFORMANCE

						Propeller (Dia x Pitch)		Top Speed		Range
Power hp (kw)	IN	СМ		MPH "	КРН	МІ	КМ			
MC 3.0MPI/A 135 hp (101kw)	14 1/4 X 2[36 X 53	AL	39-42	63-68	90	145			
MC 4.3L/A 190 hp (142kw)	14 1/4 X 23	36 X 58	AL	48-51	77-82	, <u>9</u> 0	145			
MC 4.3MPI/A 220 hp (164kw)	14 I/4 X 2I	36 X 53	AL	49-52	79-84	95	155			
VP V6-200/SX 200 hp (I49kw)	14 I/4 X 23	36 X 58	AL	47-50	76-81	95	155			
VP V6-225/SX 225 hp (168kw)	14 I/4 X 23	36 × 58	AL.	49-52	79-84	95	155			

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

LOA 20' 4" (6.20 m) Beam 8' 0" (2.44 m) Total Height 5' 3" (1.6 m.) Cockpit Height at Helm 31" (79 cm.) Approx. boat & engine weight

2420 lbs. (1,100 kg)
Trailer Weight Single 971 lbs. (440 kg)

Trailer Weight Tandem 1155 lbs. (524 kg)
Draft Drive Unit Up 18" (46 cm.)
Draft Drive Unit Down 35" (89 cm.) Deadrise 21° Fuel Capacity 32 gallons (121 L.) Maximum Load 2200 lbs (998 kg.) Maximum Persons 9 (USA) (7 CE Maximum Horsepower 200 (150 kw)

Standard Features

Instrumentation, helm: Speedometer, pump, navigation/anchor lights, lights, horn & stereo Sony stereo & mp3 adapter Bilge pump, automatic
Bow seats w/storage & seat latch Built-in cockpit side storage Cleats, stainless steel (3) Courtesy light Steering wheel, non-directional Electric horn w/ss grill Fiberglass floor w/built-in footrests & floor drains Color match single axle trailer w/brakes

Glove box w/hinge & latch Tachometer, Fuel gauge, Volt gauge Chrome pull switches for bilge Hinged ski & wake board locker lid Molded swim platform Molded swim platform Navigation lighting Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Seating: 2 bucket seats/aft bench seat Synthetic grab handles Side glass wings Walk thru windshield Walk thru transom Two-tone deck and hull Gunneling, white plastic w/flex chrome insert

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), Ski pylon, Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (5), Bow scuff plate, Chrome vent ...

Convenience Package: Hour meter, Depth sounder

GTL Package:

Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat Docking lights, Stereo upgrade, XL package

Single Options:

Color coordinated Bimini top w/boot Color coordinated Cockpit cover Color coordinated Bow cover Care cover (black) Wakeboard tower Wakeboard tower w/bimini top Docking lights Bow Scuff Plate Spear Graphics Pkg Side glass wings - delete Flip-up buckets (2) Ski pylon Snap-in carpet Tilt steering hydraulic Stereo upgrade Bow fill-in cushions High altitude prop Swim platform mat

Trailer Options: Tandem w/brakes Spare Tire w/mount Galvanized finish

Color Choices

White w/Jet Black Gelcoat White w/Laser Red Gelcoat

White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat

Specifications

LOA 20' 4" (6.20 m) Beam 8' 0" (2.44 m) Total Height 5' 3" (1.6 m) Cockpit Height at Helm 31" (79 cm.) Approx. boat & engine weight 2420 lbs. (I,100 kg)
Trailer Weight Single 971 lbs. (440 kg)

Trailer Weight Tandem 1155 lbs. (524 kg) Draft Drive Unit Up 18" (46 cm.) Draft Drive Unit Down 35" (89 cm.) Deadrise 21° Fuel Capacity 32 gallons (121 L.) Maximum Load 2200 lbs (998 kg.) Maximum Persons 9 (USA) (7 CE) Maximum Horsepower 200 (150 kw)

Standard Features

Instrumentation, helm: Speedometer, Tachometer, Fuel gauge, Volt gauge Chrome pull switches for bilge pump, navigation/anchor lights, lights, horn & stereo Sony stereo & mp3 adapter Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Electric horn w/stainless steel grill Fiberglass floor w/built-in footrests & floor drains Upgraded steering wheel; non-directional Courtesy light

Color match single axle trailer w/brakes Gunneling, black plastic w/flex chrome insert

Glove box w/hinge & latch Hinged ski & wake board locker lid Molded swim platform w/swim platform mat Navigation lighting Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless steel cleats (5) Seating: 2 bucket seats/aft bench seat Synthetic grab handles Side glass wings Walk thru windshield Walk thru transom GTS two-tone deck & hull GTS Gel Scheme & graphics GTS cockpit interior GTS Yellow gauges

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), Ski pylon, Custom snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (5), Bow scuff plate

Convenience Package: Hour meter, Depth sounder

GTL Package:

Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat Docking lights, Stereo upgrade, XL package

Single Options:

Color coordinated Bimini top w/boot Color coordinated Cockpit cover Color coordinated Bow cover Care cover (black) Wakeboard tower Wakeboard tower w/bimini top Docking lights Bow Fill-in cushions Bow Scuff Plate Side glass wings - delete Flip-up buckets w/fiberglass back panel (2) Ski pylon Custom snap-in carpet Tilt steering hydraulic Stereo upgrade High Altitude Prop

Trailer Options: Tandem w/brakes Spare Tire w/mount Galvanized finish

Color Choices

GTS Gel Scheme Jet Black GTS Gel Scheme Electric Yellow

GTS Gel Scheme Laser Red

GTSF 200

PERFORMANCE DATA FOR GT 200's (all inclusive)

Specifications

LOA 20' 4" (6.20 m)
Beam 8' 0" (2.44 m)
Total Height 5' 3" (1.6 m.)
Cockpit Height at Helm
31" (79 cm.)

Cockpit Height at Helm 31" (79 cm.) Approx. boat & engine weight 2420 lbs. (1,100 kg) Trailer Weight Single 971 lbs. (440 kg) Trailer Weight Tandem 1155 lbs. (524 kg)
Draft Drive Unit Up 18" (46 cm.)
Draft Drive Unit Down 35" (89 cm.)
Deadrise 21°
Fuel Capacity 32 gallons (121 L.)
Maximum Load 2200 lbs (998 kg.)
Maximum Persons 9 (USA) (7 CE)
Maximum Horsepower 200 (150 kw)

Standard Features

Instrumentation, helm: Speedometer,
Tachometer, Fuel gauge, Volt gauge
Chrome pull switches for bilge
pump, navigation/anchor lights,
lights, horn & stereo
Sony stereo & mp3 adapter
Bilge pump, automatic
Reversible bow seats w/storage
Built-in cockpit side storage
Electric horn w/ ss grill
Fiberglass floor w/built-in footrests
& floor drains
Steering wheel, non-directional
Glove box w/hinge & latch
Hinged ski & wake board locker lid
Color match single axle trailer w/brakes

Stainless steel do Stainless steel by
Stainless steel of Stainles

Molded swim platform

Gunneling, white plastic w/flex chrome insert

Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless steel cleats (4) Seating: 3 folding bucket seats/aft bench seat Synthetic grab handles Walk thru windshield Walk thru transom Aerated live well Rod storage Trolling motor mount Bow fishing platform Casting fishing seat Rod holders (2) S & F two tone deck & hull S & F Gel Scheme

Optional Features

XL Package:

Convenience package, Ski pylon,
Snap-in carpet, Stainless steel drink
holders, Stainless steel speaker
covers, Stainless steel grab handles,

Wakeboard tower

Pull up cleats. Bow scuff plate.

Convenience Package: Hour meter, Depth sounder

Fishing Package:

24 volt trolling motor w/removable
plate & fish finder

Tilt steering hydraulic
Stereo upgrade
High Altitude Prop

Single Options:
Color coordinated Bimini top w/boot
Color coordinated Cockpit cover
Color coordinated Bow cover
Wakeboard tower
Wakeboard tower w/bimini top
Docking lights
Bow Scuff Plate
Ski pylon
Snap-in carpet
Tilt steering hydraulic
Stereo upgrade
High Altitude Prop
Swim platform mat
Ski & Fish graphics

Trailer Options: Tandem w/brakes Spare Tire w/mount Galvanized finish

Color Choices

S & F Gel Scheme white w/Jet Black Gelcoat S & F Gel Scheme white w/Laser Red Gelcoat S & F Gel Scheme white w/Royal Blue Gelcoat

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
GT 200 LBS	Merc 150 4S	1930	460	192	150	971
GT 200 KG	Merc 150 4S	875 -	. 209	87	68	440

PERFORMANCE

	Propeller (Dia x Pitch)		Туре	Top Speed		Cruise Range	
Power hp (kw)	IN	СМ	-	мрн	крн	мі	км
EV 115 E-TEC 115 hp (86kw)	14 7/8 X 17	38 X 43	AL	39-42	63-68	105	170
EV 150 E-TEC 150 hp (112kw)	14 7/8 X 17	. 38 X 43	AL	43-46	69-74	105	170
EV 200 E-TEC 200 hp (149kw)	14 I/2 X 19	37 X 48	AL	48-5l	77-82	105	170
Merc 115 Opti 115 hp (86kw)	13 I/4 X 17	34 X 43	AL	39-42	63-68	105	170
Merc 115 4S 115 hp (86kw)	13 1/4 X 17	34 X 43	AL	39-42	63-68	110	180
Merc I50 ProXS I50 hp (II2kw)	15 X 17	38 X 43	ĄL	43-46	69-74	110	180
Merc 150 4S 150 hp (112kw)	15 X 17	38 X 43	AL	43-46	69-74	105	170
Merc 200 Opti 200 hp (149kw)	14 I/2 X I9	37 X 48	AL _.	48-51	77-82	105	170
Merc 200 Verado 200 hp (149kw)	14 1/2 X 19	37 X 48	AL	48-51	77-82	110	180
Yam FII5 II5 hp (86kw)	13 1/4 X 17	34 X 43	ΑĹ	39-42	63-68	105	170
Yam F150 150 hp (112kw)	14 1/4 X 17	36 X 43	AL	43-46	69-74	105	170

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

LOA 20' 6" (6.25 m) Beam 8' 0" (2.44 m) Total Height 5' 3" (1.6 m.) Cockpit Height at Helm

31" (79 cm.) Approx. boat & engine weight 2770 lbs. (1,260 kg) Trailer Weight Single 971 lbs. (440 kg) Trailer Weight Tandem 1155 lbs. (524 kg) Draft Drive Unit Up 18" (46 cm.) Draft Drive Unit Down 35" (89 cm.) Deadrise 21° Fuel Capacity 32 gallons (121 L.) Maximum Load 1500 lbs (680 kg.) Maximum Persons 9 (USA) (7 CE Maximum Horsepower 300 (224 kw)

Standard Features

Instrumentation, helm: Speedometer, Tachometer, Fuel gauge, Volt gauge
Chrome pull switches for bilge

Tachometer, Fuel gauge, Volt gauge
Molded swim platform
Navigation lighting pump, navigation/anchor lights, lights, horn & stereo Sony stereo & mp3 adapter Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Cleats, stainless steel (3) Courtesy light Steering wheel, non-directional Electric horn w/ss grill Fiberglass floor w/built-in footrests

& floor drains Color match single axle trailer w/brakes Glove box w/hinge & latch

Hinged ski & wake board locker lid Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Seating: 2 bucket seats/aft bench seat Synthetic grab handles Side glass wings Walk thru windshield Walk thru transom Two-tone deck and hull Gunneling, white plastic w/flex chrome insert Spear Graphics Pkg

Optional Features

XL Package: Convenience package, Flip-up bucket seats (2), Tilt steering, Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (5), Bow

scuff plate, Chrome vent Convenience Package: Hour meter, Depth sounder

GTL Package:

Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat Docking lights, Stereo upgrade, XL package

Color Choices

White w/Jet Black Gelcoat White w/Laser Red Gelcoat Single Options:

Color coordinated Birnini top w/bootgr. Color coordinated Cockpit cover Color coordinated Bow cover Care cover (black) Wakeboard tower Wakeboard tower w/bimini top Docking lights **Bow Scuff Plate** Flip-up buckets (2) Snap-in carpet Stereo upgrade Bow fill-in cushions High altitude prop Swim platform mat Tilt steering

Trailer Options: Tandem w/brakes Spare Tire w/mount Galvanized finish

White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat* Not available with GTL package

Specifications

LOA 20' 6" (6.25 m) Beam 8' 0" (2.44 m) Total Height 5' 3" (1.6 m.) Cockpil (1.6 m.) 31" (79 cm.)

Approx. boat & engine weight 2770 lbs. (1,260 kg)

Trailer Weight Single 971 lbs. (440 kg)

Trailer Weight Tandem 1155 lbs. (524 kg)
Draft Drive Unit Up 18" (46 cm.) Draft Drive Unit Down 35" (89 cm.) Deadrise 21° Fuel Capacity 32 gallons (121 L.)
Maximum Load 1500 lbs (680 kg.)
Maximum Persons 9 (USA) (7 CE) Maximum Horsepower 300 (224 kw)

Standard Features - Extended Section Instrumentation, helm: Speedometer, Tachometer, Fuel Speedometer, Fuel Speedometer,

gauge, Volt gauge Chrome pull switches for bilge pump, navigation/ anchor lights, lights, horn & stereo

Sony stereo & mp3 adapter Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Electric horn w/stainless steel grill Fiberglass floor w/built-in footrests & floor drains Upgraded steering wheel, non-

directional Courtesy light Color match single axle trailer w/brakes Gunneling, black plastic

w/flex chrome insert

Molded swim platform w/swim platform mat Navigation lighting Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless steel cleats (5) Seating: 2 bucket seats/aft bench seat

Synthetic grab handles Side glass wings Walk thru windshield Walk thru transom GTS two-tone deck & hull GTS Gel Scheme & graphics GTS cockpit interior GTS Yellow gauges

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), Custom snap-in carpet, Stainless steel drink holders, Tilt steering, Stainless steel speaker covers, Stainless steel grab handles. Pull up cleats. Bow scuff plate, Chrome vent covers

Convenience Package: Hour meter, Depth sounder

Single Options: Color coordinated Birnini top w/boot Color coordinated Cockpit cover Color coordinated Bow cover Care cover (black)

Color Choices

GTS Gel Scheme Jet Black GTS Gel Scheme Laser Red

Wakeboard tower Wakeboard tower w/bimini top Docking lights Bow Fill-in cushions Bow Scuff Plate Flip-up buckets (2) Custom snap-in carpet Stereo upgrade High Altitude Prop Tilt steering

Trailer Options: Tandem w/brakes Spare Tire w/mount Galvanized finish

LOA 20' 6" (6.25 m) Beam 8' 0" (2.44 m) Total Height 5' 3" (l.6 m.) Cockpit Height at Helm 31" (79 cm.)

Approx. boat & engine weight 2770 lbs. (1,260 kg)
Trailer Weight Single 971 lbs. (440 kg)

Trailer Weight Tandem 1155 lbs. (524 kg) Draft Drive Unit Up 18" (46 cm.) Draft Drive Unit Down 35" (89 cm.) Deadrise 21° Fuel Capacity 32 gallons (121 L.) Maximum Load 1300 lbs (590 kg.) Maximum Persons 7 (USA) (7 C Maximum Horsepower 300 (224 kw)

Standard Features

Instrumentation, helm 5" & 2": Speedometer, Tachometer, Fuel gauge, Volt gauge Chrome pull switches for bilge pump, navigation/ Stainless steel 3-step ladder anchor lights, lights, horn & stereo Sony stereo & mp3 adapter

Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Electric horn w/stainless steel grill Fiberglass floor w/built-in footrests & floor drains

Upgraded steering wheel, nondirectional Courtesy light
Color match single axle trailer w/brakes

Gunneling, black plastic w/flex chrome insert Glove box w/hinge & latch Hinged ski & wake board locker lid Molded swim platform w/swim platform mat Navigation lighting w/grab handle Stainless steel bow & stern eyes

Stainless steel cleats (5) Seating: 2 bucket seats/aft bench seat Synthetic grab handles Side glass wings Walk thru windshield Walk thru transom GTS two-tone deck & hull GTS Gel Scheme & graphics

GTS cockpit interior GTS Yellow gages Color coordinated upgrade steering wheel

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), Custom snap-in carpet, Stainless steel drink holders, Tilt steering, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats. Bow scuff plate, Chrome vent covers, SS deck plate

Convenience Package: Hour meter, Depth sounder

Single Options: Bow Fill-in cushions

Bow Scuff Plate Color coordinated Bimini top w/boot

Color Choices

GTS Gel Scheme Jet Black GTS Gel Scheme Laser Red Color coordinated Cockpit cover Custom snap-in carpet Flip-up buckets (2) LED lights - bow High Altitude Prop Side glass wings - delete Stereo upgrade Tilt steering Wakeboard tower Wakeboard tower w/bimini top

Trailer Options: Tandem w/brakes Spare Tire w/mount Galvanized finish

Specifications

LOA 20' 6" (6.25 m) Beam 8' 0" (2.44 m) Total Height 5' 3" (1.6 m.) Cockpit Height at Helm 31" (79 cm.) Approx. boat & engine weight 2810 lbs. (1,275 kg) Trailer Weight Single 971 lbs. (440 kg)

Trailer Weight Tandem 1155 lbs. (524 kg) Draft Drive Unit Up 18" (46 cm.) Draft Drive Unit Down 35" (89 cm.) Deadrise 21° Fuel Capacity 32 gallons (121 L.) Maximum Load 1500 lbs (680 kg.) Maximum Persons 9 (USA) (7 CE Maximum Horsepower 300 (224 kw)

Standard Features

Instrumentation, helm: Speedometer, Tachometer, Fuel gauge, Volt gauge Chrome pull switches for bilge pump, navigation/anchor lights, lights, horn & stereo Sony stereo & mp3 adapter Bilge pump, automatic Reversible bow seats w/storage Built-in cockpit side storage Electric horn w/ ss grill Fiberglass floor w/built-in footrests & floor drains Steering wheel, non-directional Glove box w/hinge & latch Hinged ski & wake board locker lid Color match tandem axle trailer w/brakes Molded swim platform Gunneling, white plastic

Stainless steel 3-step ladder w/grab handle Stainless steel bow & stern eyes Stainless steel cleats (4)
Seating: 2 bucket seats/aft bench seat Synthetic grab handles Walk thru windshield Walk thru transom Aerated live well Rod storage Trolling motor mount Bow fishing platform Casting fishing seat (I) & folding bucket seat (I) Rod holders (2) Side glass wings Two tone deck & hull S & F Gel Scheme on Hull Ski & Fish graphics

Optional Features

w/flex chrome insert

XL Package:

Convenience package, Flip-up bucket seats (2), Snap-in carpet, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats. Bow scuff plate Tilt steering, Stainless steel drink holders, Chrome vent covers

Convenience Package: Hour meter, Depth sounder

Fishing Package: 24 volt trolling motor w/removable plate & fish finder

Single Options: Bow Fill-in cushions Bow Scuff Plate Color coordinated Bimini top w/boot Color coordinated Cockpit cover Custom snap-in carpet Flip-up buckets (2) LED lights - bow High Altitude Prop Side glass wings - delete Stereo upgrade Tilt steering Wakeboard tower Wakeboard tower w/bimini top

Trailer Options: Spare Tire w/mount Galvanized finish

Color Choices

S & F Gel Scheme white w/Jet Black Gelcoat S & F Gel Scheme white w/Laser Red Gelcoat S & F Gel Scheme white w/Royal Blue Gelcoat

PERFORMANCE DATA FOR GT 205's (all inclusive)

GT 225

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
GT 205 LBS	VP V8-270/SX	1770	1010	192	150	1155
GT 205 KG	VP V8-270/SX	803	458	87	68	524

PERFORMANCE

	Propeller (Dia x Pitch)		Туре	pe Top Speed		Cruise	Range
Power hp (kw)	IN	CM	-	МРН	КРН	MI	КМ
MC 4.3L/A 190 hp (142kw)	14 I/4 X 21	36 X 53	· AL	45-48	72-77	90	145
MC 4.3M PI/A 220 hp (164kw)	14 1/2 X 19	37 X 48	AL	47-50	76-81	95	155
MC 5.0 MPI/A 260 hp (194kw)	14 I/4 X 21	36 X 53	AL	52-55	84-89	95	155
MC 350 MPI/A 300 hp (224kw)	14 1/4 X 21	36 X 53	AL	54-57	87-92	95	155
VP V6-200/SX 200 hp (149kw)	14 I/4 X 2I	36 X 53	AL	45-48	72-77	95	155
VP V6-225/SX 225 hp (168kw)	14 1/4 × 21	36 × 53	AL	48-51	77-82	95	155
VP V8-225/SX 225 hp (168kw)	14 1/4 × 21	36 × 53	AL	48-51	77-82	95	155
VP V8-270/SX 270 hp (201kw)	14 1/4 × 21	36 × 53	AL	52-55	84-89	95	155
VP V8-300/SX 300 hp (224kw)	14 1/4 X 21	36 × 53	AL	54-57	87-92 .	95	155

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

Specifications

LOA 22' (6.71 m) Beam 8' 4" (2.54 m) Total Height 5' 4" (1.63 m.) Cockpit Height at Helm 33" (84 cm.)
Approx. boat & engine weight
3300 lbs. (1,500 kg) Trailer Weight Tandem 1095 lbs. (497 kg)

Draft Drive Unit Up 17" (43 cm.) Draft Drive Unit Down 34" (86 cm.) Deadrise 20° Fuel Capacity 40 gallons (151 L.)
Maximum Load 1800 lbs (816 kg.)
Maximum Persons II (USA) (9 CE) Maximum Horsepower 320 (239 kw)

Standard Features

Instrumentation, helm gauges: Speedometer, Tachometer, Fuel gauge, Volt gauge temp gauge, oil gauge, trim gauge Chrome pull switches for bilge pump, navigation/anchor lights, lights, horn & blower

Aft facing transom seat Anchor locker w/rope storage Bilge pump, automatic Bow seats w/storage & seat latch Built-in cockpit side storage Cleats, stainless steel (4) Color match tandem axle trailer w/brakes Courtesty lights (2) Drink cup holders (12) Electric horn w/ss grill Fiberglass floor w/built-in footrests & floor drains

Glove box w/hinge & latch

Gunneling, white plastic w/flex chrome insert Hinged ski & wake board locker lid Molded swim platform

Navigation lighting Seating: 2 bucket seats/aft U-bench seat Side glass wings Ski tow ring Sony stereo & mp3 adapter 2 bow & 2 cockpit speaker. Spear Graphics Pkg

Stainless steel 3-step ladder w/lid & grab handle Stainless steel bow & stern eyes Steering wheel, non-directional Storage behind bow backrest Synthetic grab handles Two-tone deck and hull Walk thru transom w/storage Walk thru windshield

Optional Features

XL Package:

Convenience package, Flip-up bucket seats (2), tilt steering. Snap-in carpet, Stainless steel drink holders, Stainless steel speaker covers, Stainless steel grab handles, Pull up cleats (6), Bow scuff plate

Convenience Package:

Hour meter, Depth sounder.

GTL Package: Upgrade interior in Saddle or Cashmere color w/chain weave material on sidewall, Steering wheel upgrade, Color matched carpet, Swim platform mat Docking lights, Stereo upgrade, XL package.

Single Options:

Black Bimini top w/boot for wake tower Gatorhyde/galvanized finish Bow fill-in cushions w/backrest windbreak

Color Choices

White w/let Black Gelcoat White w/Laser Red Gelcoat

Bow Scuff Plate Care cover (black) Cockpit table Color coordinated Bimini top w/boot Color coordinated Bow cover Color coordinated Cockpit cover Docking lights Flip-up buckets (2) High altitude prop Snap-in carpet Stereo upgrade: swim remote & subwoofer Swim platform mat Thru side exhaust Tilt steering Transom shower Wakeboard tower

Trailer Options: Spare Tire w/mount

White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat* * Not available with GTL package

GTS 225

PERFORMANCE DATA FOR GT 225's (all inclusive)

Specifications

LOA 22' (6.71 m)
Beam 8' 4" (2.54 m)
Total Height 5' 4" (1.63 m.)
Cockpit Height at Helm 33" (84 cm.)
Approx. boat & engine weight
3300 lbs. (1,500 kg)
Trailer Weight
Tandem 1095 lbs. (497 kg)

Draft Drive Unit Up 17" (43 cm.) Draft Drive Unit Down 34" (86 cm.) Deadrise 20° Fuel Capacity 40 gallons (151 L.) Maximum Load 1800 lbs (816 kg.) Maximum Persons II (USA) (9 CE) Maximum Horsepower 320 (239 kw)

Standard Features

Instrumentation: Speedometer,
Tachometer, Fuel gauge, Volt gauge
Chrome pull switches for bilge
pump, navigation/anchor lights,
lights, horn & stereo
Aft facing transom seat
Bilge pump, automatic
Bow seats w/storage & seat latch
Built-in cockpit side storage
Cleats, stainless steel (4)
Color match tandem axle trailer w/brakes \$
Courtesy lights (2)
Drink cup holders
Electric horn w/ss grill

floor drains Glove box w/hinge & latch Gunneling, black plastic w/flex chrome insert Hinged ski & wake board locker lid

Fiberglass floor w/built-in footrests &

Molded swim platform w/swim platform mat
Navigation lighting
Seating: 2 bucket seats/aft U-bench seat
Side glass wings
Ski tow ring
Sony stereo & mp3 adptr 2 bow &
2 cockpit speaker.
Stainless steel 3-step ladder w/lid &
grab handle
Stainless steel bow & stern eyes
Storage behind bow backrest
Synthetic grab handles
Upgraded steering wheel, non-directional
Walk thru transom
Walk thru windshield
GTS two-tone deck & hull
GTS Gel Scheme & graphics
GTS cockpit interior
GTS Yellow gauges

Optional Features

XL Package:

Convenience package, Flip-up bucket
seats (2), tilt steering. Custom
snap-in carpet, Stainless steel drink
holders, Stainless steel speaker
covers, Stainless steel grab handles,
Pull up cleats (6), Bow scuff plate

Color coordinated
Color coordinated
Custom snap-in ca
Docking lights
Flip-up buckets (2)
High altitude prop

Convenience Package: Hour meter, Depth sounder.

Single Options:

Bimini top w/boot for wake tower (black) Bow fill-in cushions w/backrest windbreak Bow Scuff Plate Care cover (black) Cockpit table w/mount

Color Choices

GTS Gel Scheme Jet Black GTS Gel Scheme Laser Red Color coordinated bimini top w/boot
Color coordinated bow cover
Color coordinated cockpit cover
Custom snap-in carpet
Docking lights
Flip-up buckets (2)
High altitude prop
Stereo upgrade: swim remote
& subwoofer
Thru side exhaust

Trailer Options: Spare Tire w/mount

Tilt steering

Transom shower

Wakeboard tower

Gatorhyde/Galvanized finish

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
GT 225 LBS	VP V8-300/ SX	2300	1010	240	150	1095
GT 225 KG	VP V8-300/ SX	1040	458	109	68	497

PERFORMANCE

	Prope (Dia x I	eller Pitch)	Туре	Top S	peed	Cruise	Range
Power hp (kw)	ĺN	CM		МРН	КРН	мі	км
MC 4.3 MPI/A 220 hp (164kw)	14 1/2 X 19	37 X 48	· AL	44-47	71-76	130	210
MC 5.0 MPI/A 260 hp (194kw)	14 _. 1/2 X 19	37 X 48	AL	47-50	76-81	130	210
MC 350 MPI/BI 300 hp (224kw)	14 1/2 X 19	37 X 48	AL.	50-53	81-85	130	210
MC 350 MPI/B3 300 hp (224kw)	26P	66	SST	51-54	82-87	130	210
MC 377 MPI/BI 320 hp (239kw)	14 1/2 X 19	37 X 48	AL	51-54	82-87	130	210
MC 377 MPI/B3 320 hp (239kw)	28P	71	SST	53-56	85-90	130	210
VP V6-225/SX 225 hρ (168kw)	14 1/4 X 21	36 × 53	AL	45-48	72-77	130	- 210
VP V8-225C/SX 225 hp (168kw)	14 1/4 X 21	36 × 53	AL	45-48	72-77	- 130	210
VP V8-270/SX 270 hp (201kw)	14 1/2 X 19	37 × 48	AL	47-50	76-81	, 130	210
VP V8-300/SX 300 hp (224kw)	14 1/2 X 19	37 X 48	AL	50-53	81-85	130	210
VP V8-300/DP 300 hp (224kw)	FH5	FH5	SST	51-54	82-87	130	210
VP V8-320/SX 320 hp (239kw)	14 1/2 X 19	37 X 48	AL	51-54	82-87	130 ्.	210
VP V8-320/DP 320 hp (239kw)	FH6	FH6	SST	53-56	85-90	130	210
							-

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

Deadrise 21°
Fuel Capacity 24 gal. (91 L.)
Maximum Load 1800 lbs. (816 kg.)
Cockpit Height at Helm 28½" (.72 m.)
Approx. boat & engine weight
1950lbs. (884 kg.)
Trailer Weight Single 731 lb- (222 kg.)
Maximum Persons 8 or 1150 lbs.
(522 kg.)
Maximum L.

Maxi Trailer Weight Single 731 lbs. (332 kg)
Draft Drive Unit Up 151/2" (.39 m.)
Draft Drive Unit Down 281/2" (72 m.)

Maximum Horsepower 150 (112 kw.)

Standard Features

Instrument panel includes: speedometer, tachometer & fuel gauges; plus switches for bilge pump, navigation/anchor lights, panel lights, horn & accessories AM/FM Sirius satellite-ready stereo w/2 speakers & MP3 adaptor

Bilge pump Bow seats w/molded storage & seat latch

Custom non-directional woodgrain steering wheel Drink cup holders Dual cable steering Electric horn

Fiberglass floor w/built-in footrests & floor drain Glove box w/stainless steel hinge & latch Hinged ski locker lid Molded swim platform Navigation lighting Cleats SL seating: 2 bucket seats/aft bench

seat Stainless steel bow & stern eyes Synthetic grab handles Walk-thru curved windshield w/o full glass side wings

Optional Features

Color-coordinated soft top & boot Color-coordinated Canvas Package Color-coordinated Bimini top w/boot Color-coordinated cockpit cover Color-coordinated bow cover Mooring cover 3-step boarding ladder Convenience Package: hour meter,

depth sounder Fishing Package: 24 volt trolling motor w/slider plate & fish finder

Ski & Fish Package: (2) fish seats, tackle box trays, Trolling motor mount, rod storage, aerated live well

Flip-up bucket seat (1) Flip-up bucket seats (2) Full side glass wings Ski tow pylon Snap-in carpet Tilt steering

full side glass wings, convenience package, flip-up bucket seat (1), ski tow pylon, snap-in carpet, stainless steel drink holders, stainless steel speaker covers, stainless steel grab handles

Color Choices

White w/let Black Gelcoat White w/Laser Red Gelcoat White w/Royal Blue Gelcoat White w/Electric Yellow Gelcoat

Engine Choices

Bombardier Pre-Package includes: ignition switch with ignition interrupt switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls, pre-drilled transom & Bombardier Systems check

Evinrude 90 DSLSE* Evinrude 115 DSLSE* Evinrude I50 DSLSE* Evinrude 115 HO

Mercury Pre-Package includes: ignition switch with ignition interrupt switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls & pre-drilled transom

Mercury 90 ELPT Optimax* Mercury 115 ELPT Optimax* Mercury 150 L Optimax* Mercury 115 PRO XS

Yamaha Pre-Package includes: ignition switch with ignition interrupt switch, Yamaha multi-function gauges, manufacturer controls & pre-drilled

Yamaha F90 TLR Yamaha F 115 TLR* Yamaha F 150 TLR*

* Engine will be shipped with boat not installed; boat will be Bombardier, Mercury or Yamaha pre-rigged.

Performance

Engine: Evinrude E-TEC 115 FastStrike: 19 pitch

	mph	gph	range*
rpm			107
2500	15	2.9	
	25	4.2	123
3200	25	**	115
4200	. 35	6.3	115
WOT	43-45		
YYC71	15.15		

Time to plane: 3.5 seconds

Acceleration U-20 MFF1. 19	110	W/\
Fraince Enimendo E-TEC	150 FastStrike: 19 pitch =	- N/A 150
rpm	mph gph	range*
2400	15 3.7	- 84
3200	30 5.0	124
4200	40 7.5	110
TOW	49-52 —	

Time to plane: 3.2 seconds Acceleration 0-20 MPH: N/A**

HANdling 155uls

Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Not available.


- Chins Wolk

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 18' 5" (5.61 m.) Beam 88" (2.24 m.) Total Height 44" (1.12 m.) Cockpit Height at Helm 281/2" (72 cm) Maximum Persons 8 Approx. boat & engine weight
2280 lbs. (1035 kg)
Trailer Weight Single 846 lbs. (384 kg)
Praft Drive Unit Up 16" (41 m.) Draft Drive Unit Down 31" (.79 m.)

GT185

Deadrise 21° Fuel Capacity 24 gal. (91 L.) Maximum Load 1100 lbs. (499 kg.) Maximum Horsepower 220 hp (164 kw)



Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn & lights. AM/FM Sirius satellite-ready stereo w/2 speakers & MP3 adaptor Automatic bilge pump

Bow seats w/molded storage & seat latch Custom non-directional woodgrain steering wheel Drink cup holders

Electric horn

Extended swim platform w/3-step ladder Fiberglass floor w/built-in footrests & floor drain Glove box w/stainless steel hinge & latch Hinged ski locker lid Merc/Volvo prop Navigation lighting Cleats Ski tow ring SL seating: 2 bucket seats/aft bench seat/sunlounge Stainless steel boarding ladder Stainless steel bow & stern eyes Synthetic passenger grab handles

Walk-thru curved windshield w/o full

glass side wings

Optional Features

Color-coordinated soft top & boot Color-coordinated Canvas Package Color-coordinated Birnini top w/boot Color-coordinated cockpit cover Color-coordinated bow cover Mooring cover Convenience Package: hour meter & depth sounder Flip-up bucket seat (I)

Flip-up bucket seats (2) Full side glass wings High altitude prop Snap-in carpet Tilt steering

XL Package: tilt steering, full side glass wings, convenience package, flip-up bucket seat (I), snap-in carpet, stainless steel speaker covers, stainless steel drink holders, stainless steel grab handles

Cockpit Upgrade Package: side storage tubs, coming pads, cooler/slider, cockpit aft bulk, cargo net, aft engine room bulk

(All canvas choices except mooring cover are color-coordinated fabric)

Color Choices

White w/jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

Specifications

LOA 18' 5" (5.61 m.)
Beam 88" (2.24 m.)
Total Height 44" (1.12 m.)
Cockpit Height at Helm 28'/1" (72 cm) Approx. boat & engine weight 2335 lbs. (1059 kg) Trailer Weight Single 846 lbs. (384 kg) Maximum Horsepower

Draft Drive Unit Up 16" (.41 m.) Draft Drive Unit Down 31" (.79 m.) Deadrise 21 Fuel Capacity 24 gal. (91 L.) Maximum Load 1100 lbs. (499 kg.) Maximum Persons 8 220 hp (164 kw)

Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn & lights AM/FM Sirius satellite-ready stereo w/2 speakers & MP3 adaptor Automatic bilge pump sunlounge
Bow seats w/molded storage & seat latch Stainless steel boarding ladder Custom non-directional woodgrain steering wheel

Drink cup holders Electric horn Extended swim platform w/3-step ladder Fiberglass floor w/built-in footrests & floor drain

Glove box w/stainless steel hinge & latch Hinged ski locker lid Merc/Volvo prop Navigation lighting Cleats Ski tow ring SL seating: 2 bucket seats/aft bench seat/ sunlounge Stainless steel bow & stern eyes Synthetic passenger grab handles Walk-thru curved windshield w/o full glass side wings

Optional Features

Color-coordinated soft top & boot Color-coordinated Canvas Package Color-coordinated Bimini top w/boot Color-coordinated cockpit cover Color-coordinated bow cover Mooring cover Convenience Package: hour meter & depth sounder Flip-up bucket seat (1) Flip-up bucket seats (2) Full side glass wings High altitude prop Snap-in carpet Tilt steering XL Package: tilt steering, convenience

Color Choices

White w/Jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat package, flip-up bucket seat (1), snap-in carpet, stainless steel rubrail insert, stainless steel speaker covers, stainless steel drink holders, stainless steel thru-hull fittings, stainless steel horn grill, stainless steel grab handles



Engine Choices

3.0L MerCruiser (WPS) (135) 3.0L MPI EC MerCruiser (WPS) (135) 4.3L MerCruiser (190) (Some engines not available in U.S.)

Engine: 3.01 MerCruiser, Prop. 21 pitch

4.3 MPI MerCruiser (220) 4.3 MPI EC MerCruiser (220) V6-200 Volvo Penta (200)

Performance

mph 8 25 37	gph 2.1 3.2. 7.6	range* 99 129 95
41-43	-	-
econds		
	8 25	8 2.1 25 3.2 37 7.6 41-43 —

Engine: 4.3L MerCruiser, F rpm 2400 3200 4000	mph 15 35 45	gph 3.0 5.0 8.5	range* 104 145 110
WOT	48-50	_	
Time to plane: 3.5 seconds			

Time to plane: 3.5 second: Acceleration 0-20 MPH: N/A**

Engine: V6-200 Volvo	Penta, Prop. 23 pit	ich .	range*
rpm	mph	gph	range
2000	8		. —
3000	32		
4000	. 44		
WOT	48-50		· ·

Time to plane: 3.2 seconds Acceleration 0-20 MPH: 6.1 seconds

- Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.
- Not available.

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

Actual performance will be affected by higher altitude, load, weather/water conditions, and optional equipment, such as wakeboard tower, extended swim platform and generator.

Specifications

Instrument panel includes:

LOA 20' 8" (6.30 m.) Beam 92" (2.33 m.) Total Height 43" (1.09 m.) Cockpit Height at Helm 29" (.74 m.) Approx. boat & engine weight 275 lbs (1247 kg) Trailer Weight Single 925 lbs. (420 kg)

Draft Drive Unit Up 161/2" (42 m.) Draft Drive Unit Down 311/2" (80 m.) Deadrise 21° Fuel Capacity 34 gal. (128 L.) Maximum Load 1275 lbs. (578 kg.) Maximum Persons 9 Maximum Horsepower 270 hp (201kw)

Standard Features

speedometer, tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn & lights AM/FM Sirius satellite-ready stereo w/2 speakers & MP3 adaptor Automatic bilge pump Bow seats w/molded storage & seat latch Built-in cockpit side storage steering wheel Drink cup holders Electric horn Extended swim platform

w/3-step ladder

Fiberglass floor w/built-in footrests & floor drain Ski tow ring Glove box w/stainless steel hinge & latch Hinged ski locker lid Merc/Volvo prop Navigation lighting Cleats SL seating: 2 bucket seats/aft bench seat/ sunlounge & walk-thru

transom Stainless steel bow & stern eyes Synthetic passenger grab handles Walk-thru curved windshield w/o full glass side wings

Optional Features

Color-coordinated soft top & boot Color-coordinated Canvas Package Color-coordinated Bimini top w/boot Color-coordinated Bimini for wakeboard tower Color-coordinated cockpit cover Color-coordinated bow cover Mooring cover Convenience Package: hour meter & depth sounder Flip-up bucket seat (I) Flip-up bucket seats (2)

Wakeboard tower (factory installed) Snap-in carpet Tilt steering XL Package: tilt steering, convenience package, flip-up bucket seat (l), snap-in carpet, full side glass wings,

Full side glass wings

High altitude prop

stainless steel speaker covers, stainless steel drink holders, stainless steel grab handles

Color Choices

White w/Jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

MX 205 SF

PERFORMANCE DATA FOR MX 205's

(all inclusive)

Specifications

LOA 20' 8" (6.30 m.)
Beam 92" (2.33 m.)
Total Height 43" (1.09 m.)
Cockpit Depth 29" (.74 m.)
Approx. boat & engine weight 2750lbs. (1247 kg) Trailer Weight Tandem 1086 lbs. (493 kg)

Draft Drive Unit Up 161/2" (.42 m.) Draft Drive Unit Down 311/2" (.80 m.) Deadrise 21° Fuel Capacity 34 gal. (128 L.) Maximum Load 1275 lbs. (578 kg.) Maximum Persons 9 Maximum Horsepower 270 hp (201kw)

Standard Features

Instrument panel includes: speedometer, Ski tow ring tachometer, trim, fuel, oil pressure, voltmeter and engine temperature gauges; plus switches for bilge pump, blower, horn & lights
AM/FM Sirius satellite-ready stereo w/2 speakers & MP3 adaptor Automatic bilge pump sunlounge & walk-thru tran Bow seats w/molded storage & seat latch Stainless steel bow & stern eyes Custom non-directional woodgrain

steering wheel Drink cup holders Electric horn Extended swim platform w/3-step ladder Fiberglass floor w/built-in footrests & floor drain

Glove box w/stainless steel hinge & latch Hinged ski locker lid Merc/Volvo prop Navigation lighting Cleats SL seating: 2 bucket seats/aft bench seat/

sunlounge & walk-thru transom Synthetic passenger grab handles Walk-thru curved windshield w/o full glass side wings

Optional Features

Color-coordinated soft top & boot Color-coordinated Canvas Package Color-coordinated Bimini top w/boot Color-coordinated cockpit cover Color-coordinated bow cover Mooring cover Convenience Package: hour meter & depth sounder Flip-up bucket seat (1) Flip-up bucket seats (2) Full side glass wings High altitude prop

Color Choices

White w/Jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

Roswell wakeboard tower Snap-in carpet Tilt steering

XL Package: tilt steering, convenience package, stainless steel horn grill, flip-up bucket seat (1), snap-in carpet, stainless steel speaker covers, stainless steel drink holders, stainless steel rubrail insert, stainless steel thru-hull fittings, stainless steel grab handles

Engine Chaices

migito wildings	
4.3L MerCruiser (190)	V6-200 Volvo Penta (200)
4.3L MPI MerCruiser (220)	V6-225 Volvo Penta (225)
4.3L MPI EC MerCruiser (220)	V8-225C Volvo Penta (225)
5.0L MPI MerCruiser (260)	V8-270 Volvo Penta (270)
5.0L MPI EC MerCruiser (260)	V8-270C Volvo Penta (270)
(Some engines not available in U.S.)	, ,

Performance

Engine: 4.3L MerCrui	iser, Prop: 23 pitch	1	
rpm	mph	gph	range*
2000	15	2.8	169
3000	25	3.8	207
4000	35	6.9	160

WOT Time to plane: 3.5 seconds Acceleration 0-20 MPH: N/A**

Engine: V8-270 Volvo Penta, Prop. 21 pitch

rpm	mph	gph	range ⁴
2000	13	3.6	114
3000	31	6.5	149
4000	45	11.0	130
WOT	55-58		

Time to plane: 2.8 seconds Acceleration 0-20 MPH: N/A**

- Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.
- Not available.

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 19' 4" (5.89 m.)
Beam 94" (2.39 m.)
Total Height 49'/₂" (1.26 m.)
Cockpit Depth 33'/₂" (.85 m.)
Approx. Wt. 2915 lbs. (1322 kg.)
w/5.0 GL Volvo Penta
Trailer Weight Tandem 1086 lbs.
(493 kg.)

Draft Drive Unit Up 16" (41 m.)
Draft Drive Unit Down 29" (.74 m.)
Deadrise 21°
Fuel Capacity 34 gal. (129 L.)
Maximum Load 1350 lbs. (612 kg.)
Maximum Persons 9
Maximum Horsepower
270 hp (201kw)

Standard Features

Instrument panel includes: 5"
speedometer, 5" multi-function
tachometer/fuel/trim gauge, 2" oil
pressure/2" voltmeter/2" engine
temperature gauges; plus switches
for bilge pump, blower, navigation/
anchor lights, courtesy lights, horn,
depth sounder, stereo remote in
dash, 12 volt outlet

AM/FM stereo w/4 stainless steel speaker covers & MP3 adaptor Automatic bilge pump Custom non-directional woodgrain

steering wheel
Deck reinforcement for Xtreme tower
(dealer installed)

Electric horn
Ski tow ring
Full fiberglass floor w/built-in footrest
& drains

Glove box w/stainless steel hinge & latch Hinged ski locker lid Merc/Volvo prop Molded extended swim platform SL Seating: Adjustable bucket seats w/flip-up bolsters/aft bench seat/ sunlounge & stbd. walk-thru

Snap-in carpet
Stainless steel bow & stern eyes
Stainless steel courtesy lights
Stainless steel drink holders
Stainless steel passenger grab handles
Stainless steel pull-up cleats
Stainless steel stern rails
Telescopic 3-step boarding ladder, stern
Tilt steering
Walk-thru full glass windshield w/full

side wings

Optional Features

Color-coordinated Bimini Canvas
Package
Color-coordinated Bimini top w/boot
Color-coordinated Bimini top for
wakeboard tower
Color-coordinated cockpit cover
Color-coordinated bow cover
Mooring cover
High altitude prop

Premium Sound System
Stainless Steel Package: stainless steel
stern logo plate, stainless steel bow
plate, exhaust decals, aft pullup
cleats stainless steel rubrail insert
Upgrade Package: docking lights, tilt/
trim switch, hour meter, transom
shower, ski locker mat, carry on

cooler Xtreme wakeboard tower & rack

Color Choices

White w/Jet Black Gelcoat White w/ Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

Engine Choices

4.3L MerCruiser (190)
4.3L MPI MerCruiser (220)
4.3L MPI MerCruiser (220)
5.0L MPI MerCruiser (260)
5.0L MPI MerCruiser (260)
(Some engines not available in U.S.)

V6-200 Volvo Penta (200) V6-225 Volvo Penta (225) V8-225C Volvo Penta (225) V8-270 Volvo Penta (270) V8-270C Volvo Penta (270)

Performance

Engine: v6-225 Volvo Penta, Prop: 23 pitch

rpm	mph	gph	range*
2000	8		_
3000	29		_
4000	43		_
WOT	52-55		<u>.</u>

Time to plane: 3.2 seconds Acceleration 0-20 MPH: 5.3 seconds

* Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 21' 4" (6.50 m.) Beam 101" (2.57 m.) Total Height 52" (1.32 m.) Cockpit Height at Helm 36" (.91 m.) Approx. boat & engine weight 3330 lbs. (1510 kg.) Trailer Weight Tandem 1146 lbs. (520 kg) Maximum Horsepower

Draft Drive Unit Up 16" (.41 m.) Draft Drive Unit Down 29" (.74 m.) Deadrise 21° Fuel Capacity 40 gal. (I51 L.) Maximum Load 1475 lbs. (669 kg.) Maximum Persons 10 300 hp (224 kw)

Standard Features

Instrument panel includes: 5" speedometer, 5" multi-function tachometer/fuel/trim gauge, 2" oil pressure/2" voltmeter/2" engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, courtesy lights, horn, depth sounder, stereo remote in dash, 12 volt outlet

AM/FM Sirius satellite-ready stereo w/4 stainless steel speaker covers & MP3 adaptor

Automatic bilge pump Custom non-directional woodgrain steering wheel Deck reinforcement for Xtreme tower

(dealer installed) Electric horn Ski tow ring Ski tow ring
Tilt steering
Full fiberglass floor w/built-in footrest
Walk-thru full glass windshield w/full & drains

Glove box w/stainless steel hinge & Hinged ski locker lid Merc/Volvo prop Molded extended swim platform SL Seating: Adjustable bucket seats w/flip-up bolsters/aft bench seat/sunlounge & stbd. walk-thru Snap-in carpet Stainless steel bow & stern eyes Stainless steel courtesy lights Stainless steel drink holders Stainless steel passenger grab handles Stainless steel pull-up cleats

Stainless steel stern rails Telescopic 3-step boarding ladder, fore & aft side wings

Optional Features

Color-coordinated Bimini Canvas Package Color-coordinated Birnini top w/boot Color-coordinated Bimini top for wakeboard tower Color-coordinated cockpit cover Color-coordinated bow cover Mooring cover Cockpit table w/stern base High altitude prop Premium Sound System

Color Choices

White w/Jet Black Gelcoat White w/ Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat Stainless Steel Package: stainless steel stern logo plate, stainless steel bow plate, exhaust decals, aft pull up cleats stainless steel rubrail insert Upgrade Package: docking lights, tilt/ trim switch, hour meter, transom shower, ski locker mat, carry on cooler Xtreme wakeboard tower & rack

Engine Choices

Vacant S		
5.0L MPI MerCruiser (260)	٠.	
5.0L MPI EC MerCruiser (260)		
350 Magnum MPI Alpha MerCruiser	(350	0)
350 Magnum MPI EC Alpha	١.	
MerCruiser (300)		

V8-225C Volvo Penta (225) V8-270 Volvo Penta (270) V8-300 Volvo Penta (300) V8-300C Volvo Penta (300) V8-320C Volvo Penta (320)

(Some engines not available in U.S.)

Performance

Engine: 5.0L MPI MerCruiser, Prop: 19 pitch

rpm	mph	gph	range*
2000	9	4.3	65
3000	27	7.1	114
4000	36	14.0	79
WOT	50-53	17.8	84
Time to plane: 2.6 secon	nds		

Engine: V8-270 Volvo Penta (270), Prop. 19 pitch

-6e. to mie teller (mre), tropt to piccii				
rpm	mph	gph	range*	
2000	10	4.1	. 73	
3000	27	7.1	. 117	
4000	39	14.0	86	
5000	. 50	19.3	79	
WOT	50-52	22.3	70	
·	to a contract of			

Time to plane: 3.0 seconds Acceleration 0-20 MPH: 4.9 seconds

Acceleration 0-20 MPH: 3.9 seconds

Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

> Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 20' |" (6.12 m.) Beam | 102" (2.59 m.) Total Height 50'/2" (1.28 m.) Cockpit Depth 35" (89 m.) Approx. boat & engine weight 2710 lbs. (1230 kg) Trailer Weight Tandem 1086 lbs. (493 kg) Maximum Horsepower

Draft Drive Unit Up 13" (.33 m.) Draft Drive Unit Down 28" (.71 m.) Deadrise 17 Fuel Capacity 50 gal. (189 L.) Maximum Load 2200 lbs. (997 kg) Maximum Persons 10 300 hp (224 kw)

Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, voltmeter, plus switches for bilge pump, horn, lights & accessories; hour meter & depth sounder

6" cleats AM/FM Sirius satellite-ready stereo w/MP3 adaptor Automatic bilge pump Bow storage compartments Carry-on cooler Color-coordinated bimini top w/boot Electric horn Fiberglass floor w/drains Flip-up bucket seat Snap-in carpet Hour meter, depth finder Aft sun pad

Smoked windscreen Stainless steel boarding ladder Stainless steel bow & stern eyes Stainless steel courtesy lights Adjustable bucket seat Walk-thru transom w/gate Wraparound cockpit & bow seats Stainless steel drink holders Stainless steel grab handles Stainless steel rub rail Stainless steel speaker grills Tilt steering Hinged ski locker lid Molded swim platform Navigation lighting Anchor locker with Bow ladder

Optional Features

Color-coordinated cockpit cover Fishing package: aerator pump, rod holder, two fishing seats, 12V receptacle

Ski tow pylon Bow table w/floor mount Cockpit faucet & Transom shower Docking lights

Color Choices

White w/Jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

Engine Options

Bombardier Pre-Package includes: ignition switch with ignition interrupt switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls, pre-drilled transom & Bombardier Systems check

Evinrude II5 DPX II* Evinrude 150 DPX II*

Mercury Pre-Package includes: ignition switch with ignition interrupt switch, speedometer, tachometer, trim gauge, fuel gauge, voltmeter, manufacturer controls & pre-drilled transom

Mercury 115 EXLPT Optimax* Mercury I50 EXLPT Optimax*

Yamaha Pre-Package includes: ignition switch with ignition interrupt switch, Yamaha multi-function gauges, manufacturer controls & pre-drilled transom

Yamaha F 115 TXR* Yamaha F 150 TXR*

Engine will be shipped from Bombardier, Mercury or Yamaha; boat will be Bombardier, Mercury or Yamaha pre-rigged.

> Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 20' I" (6.12 m.)
Beam 102" (2.59 m.)
Total Height 50\/2" (1.28 m.)
Cockpit Height at Helm 35" (.89 m.)
Approx. Wt. 2900 lbs. (1315 kg.)
Trailer Weight Tandem 1086 lbs. (493 kg.)

Draft Drive Unit Up 13" (.33 m.) Draft Drive Unit Down 28" (.71 m.) Deadrise 17° Fuel Capacity 50 gal. (189 L.) Maximum Load 1400 lbs. (635 kg.) Maximum Persons 10 Maximum Horsepower 300 hp (224 kw)

Standard Features

Instrument panel includes:
speedometer, tachometer, trim,
fuel, oil pressure, voltmeter &
engine temperature gauges; plus
switches for bilge pump, blower,
horn, lights & accessories; hour
meter & depth sounder

6" cleats AM/FM Sirius satellite-ready stereo w/MP3

adaptor
Automatic bilge pump
Bow storage compartments
Carry-on cooler
Color-coordinated bimini top w/boot
Electric horn
Fiberglass floor w/drains
Flip-up bucket seat
Snap-in carpet
Hour meter, depth finder

· Hinged ski locker lid Merc/Volvo prop Molded swim platform Navigation lighting Removable padded sunlounge Single fishing seat for aft casting deck Ski tow ring Smoked windscreen Stainless steel boarding ladder Stainless steel bow & stern eyes Stainless steel courtesy lights SuspensionAire adjustable bucket seat
Walk-thru transom w/gate Wraparound bow seats Stainless steel drink holders Stainless steel grab handles Stainless steel rub rail Stainless steel speaker grills Tilt steering

Optional Features

Color-coordinated cockpit cover Bow table w/floor mount Extended swim platform Forward fishing seat & pedestal Fishing package: aerator pump, rod holder, fishing seat, 12V receptacle High altitude prop

Color Choices

White w/Jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

Engine Choices

4.3L MerCruiser (190)
4.3 MPI MerCruiser (220)
4.3L MPI EC MerCruiser (220)
5.0L MPI MerCruiser (260)
5.0L MPI EC MerCruiser (Some engines not available in U.S.)

V6-200 Volvo Penta (200) V6-225 Volvo Penta (225) V8-225C Volvo Penta (225) V8-270 Volvo Penta (270) V8-270C Volvo Penta (270)

Performance

Engine: V6-225 Volvo Penta (225), Prop: 21 pitch

rpm	mph -	gph	range*
2500	21	4.8	197
3500 -	35	8.2′	192
4500	41	14.8	125
WOT	51-53		-
to plane: \$1/A**			

Time to plane: N/A**
Acceleration 0-20 MPH: N/A**

Engine: V8-270 Volvo Penta (270), Prop: 21 pitch

rpm	mph	gph	range*
2000	12	4.1	85
3000	- 31	7.1	142
4000	45	8.8	143
WOT	54-56	· —	· —

Time to plane: 2.7 seconds Acceleration 0-20 MPH: 4.5 seconds

 Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

** Not available.

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

Specifications
LOA 20' II" (6.38 m.)
Beam 102" (2.59 m.)
Total Height 57'/½" (1.46 m.)
Cockpit Height at Helm 28'/½" (.72 m.)
Approx. Wt. 3600 lbs. (1633 kg.)
Trailer Weight Tandem 1163 lbs. (528 kg.)
Maximum Persons I3
Maximum Horsepower

Draft Drive Unit Up 14" (.36 m.) Draft Drive Unit Down 30" (.76 m.) Maximum Horsepower 300 hp (224 kw)

Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; hour meter & depth sounder AM/FM Sirius satellite-ready stereo w/4 stainless steel speaker covers & MP3 adaptor Automatic bilge pump Bow anchor locker Bow storage compartments Color-coordinated Birnini top w/boot Custom non-directional woodgrain steering wheel Dockside boarding gate Electric horn Enclosed head Entertainment console w/sink, electric water pump (12.5 gal) & carry-on cooler Fiberglass floor w/drain Fore & aft swim platforms w/concealed ladders

Compass Snap-in carpet Tilt steering Hinged ski locker lid w/latch Merc/Volvo prop Navigation lighting Padded sunlounge 6" cleats Ski tow ring Smoked windscreen Stainless steel bow & stern eyes Stainless steel courtesy lights Adjustable bucket seats w/flip-up bolster Wraparound bow seats Stainless steel drink holders Stainless steel grab handles Stainless steel rub rail insert Tilt steering Flip-up bucket seat Stainless steel speaker grills Hour meter, depth sounder

Optional Features

Color-coordinated cockpit cover Bow filler cushions Docking lights Extended swim platform High altitude prop
Table w/bow & aft floor mounts

Fishing Package: livewell with switch at dash, 2 bow fishing seats & bow trolling motor plug Porta-pottie

Color Choices

White w/Jet Black Gelcoat White w/Royal Blue Gelcoat White w/Laser Red Gelcoat White w/Electric Yellow Gelcoat

Engine Choices

4.3L MPI MerCruiser (220) 4.3L MPI EC MerCruiser (220) 5.0L MPI MerCruiser (260) 5.0L MPI EC MerCruiser (260) 350 Magnum MPI Alpha MerCruiser (300) (Some engines not available in U.S.)

350 Magnum MPI EC Alpha MerCruiser (300) V6-225 Volvo Penta (225) V8-225C Volvo Pentà (225) V8-270C Volvo Penta (270) V8-300 Volvo Penta (300)

Performance

Engine	: V8-270 Volvo	Penta (270), Prop	: 21 pitch	4 - 4 - 4
Ū	rpm	mph	gph	range*
	2000	9	4.2	100
	3000	28	7.4	
	4000	40	12.5	161
_	WOT	49-51	 ,	-

Time to plane: 3.0 seconds Acceleration 0-20 MPH: 5.4 seconds

Engir	Engine: 5.0L MPI MerCruiser, Prop: 19 pitch			
٠	rpm	mph	gph ·	range*
	2000	9 .	3.8	119
	3000	27	7.0	194
	4000	39	11.4	172
	WOT	47-49		

Time to plane: 4.3 seconds Acceleration 0-20 MPH: N/A**

Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Not available.

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 24' (7.31 m.) Beam 102" (2.59 m.) Total Height 80¹/₂" (2.04 m.)
Bridge Clearance 80¹/₂" (2.04 m.)
Cockpit Height at Helm 36" (.91 m.)
Approx. boat & engine weight 4437 lbs. (2013 kg.)

Draft Drive Unit Up 17" (.43 m.)

Draft Drive Unit Down 35" (.89 m.) Deadrise 20° Fuel Capacity 56 gal. (212 L.) Maximum Load 2000 lbs. (907 kg.) Maximum Persons 10-Maximum Horsepower 300 hp (224 kw)

Standard Features

Instrument panel includes: speedometer, tachometer, trim, fuel, oil pressure, voltmeter & engine temperature gauges; plus switches for bilge pump, blower, navigation/anchor lights, panels lights, interior lights & horn

speakers & MP3 adaptor Automatic bilge pump Color-coordinated Birnini top & boot Custom non-directional woodgrain steering wheel Dinette w/V-berth

Dual battery switch Convenience Package: depth sounder & hour meter Chrome vents

Chrome thru-hull fittings Cockpit area includes: adjustable bucket Walk-thru curved full glass windshield seat w/flip-up bolster, L-shaped passenger seating w/double-wide fold-out sunlounge, stern storage compartment & walk-thru transom

w/gate Main cabin includes: enclosed head w/4-gallon porta-pottie, fiberglass shower stall, hanging clothes locker, wood cabin table, SS cabin courtesy lights, ice box, alcohol stove, on-demand water faucet

Att cabin w/overhead reading light

AM/FM Sirius satellite-ready stereo w/4
sneakers & MP3 polarics

Sneakers & MP3 polarics

Sneakers & MP3 polarics Merc/Volvo prop Molded swim platform/stainless steel telescopic 3-step boarding ladder Snap in carpet Stainless steel bow rail Stainless steel bow & stern eyes

> Translucent deck hatch w/screen Vented cabin windows (4) Walkaround deck 18-gallon water tank Stainless steel

Stainless steel cleats

Tilt steering

rubrail insert Stainless steel drink holders Stainless steel speaker covers & stereo remote for dash

Optional Features

Color-coordinated Camper Canvas **Package**

Color-coordinated Canvas Package for Bimini top Color-coordinated cockpit cover Dockside air conditioner/reverse heat

Electric anchor windlass Electric china head

Galley Package: microwave oven, refrigerator, electric stove, water heater, 110V dockside power & battery charger Starboard windshield wiper Stereo remote for dash Transom shower Remote control spotlight/compass

package Hydraulic trim tabs Manual china head w/pump out High altitude prop

Color Choices

White w/Jet Black Gelcoat

White w/Navy Blue Gelcoat White w/Pewter Gelcoat

Engine Choices

5.0L MPI Bravo III MerCruiser (260) 5.0L MPI Bravo III EC MerCruiser (260) V8-270 Volvo Penta (270) V8-270C Volvo Penta (270) V8-300 Volvo Penta (300) 350 Magnum MPI Bravo III V8-300C Volvo Pentà (300) MerCruiser (300) 350 Magnum MPI Bravo III EC

MerCruiser (300) (Some engines not available in U.S.)

Performance

Engine: V8-270 Volvo Penta (270), Props: F3

rpm	mph	gph	range*
2000	· • •	4.3.	106
3000	22	7. 4	150
4000	33	12.1	138
WOT	43-45		—'

Time to plane: 5.3 seconds Acceleration 0-20 MPH: 7.5 seconds

Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

Not available.

Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 24' 10" (7.57 m.) Beam 102" (2.59 m.) Total Height 84" (2.13 m.) Bridge Clearance 81 1/4" (2.06 m.) Cockpit Height at Helm 36" (.91 m.) Approx. boat & engine weight 5450 lbs. (2472 kg.) Draft Drive Unit Up 22" (.56 m.)

Draft Drive Unit Down 36" (.91 m.)

Deadrise 20° Fuel Capacity 56 gal. (212 L.) Maximum Load 2240 lbs. (1016 kg.) Maximum Persons 10 Maximum Horsepower 300 hp (224 kw)

Standard Features

Instrument panel includes: wood accent Horn/blower/compass trim panels, speedometer, tachometer, trim, fuel, oil pressure, voltmeter, engine temperature, hour meter & depth sounder gauges; plus switches for bilge pump, blower, navigation /anchor lights, ignition/panel lights, courtesy lights, horn, accessory, wiper, 12V adaptor

Aft cabin w/overhead reading light AM/FM Sirius satellite-ready stereo w/2 stainless steel speaker covers & MP3 adaptor

Automatic bilge pump Bow roller & bow rope locker Color-coordinated Bimini top & boot Custom non-directional woodgrain steering wheel

Cockpit area includes: wet bar w/ sink lounge seat

Dual battery switch Fiberglass floor w/built-in footrest & drains

18-gallon water tank Galley Package: microwave oven, coffee Translucent deck hatch w/screen maker, electric stove, 12/110V refrigerator, water heater &IIOV dockside power, battery charger

Hydraulic trim tabs Main cabin includes: plush two-toned upholstery w/wood accents, enclosed head w/fiberglass shower stall, wood cabin table, hanging clothes locker, cabin courtesy lights, on-demand water, cabin mirror w/ reading lights Manual china head w/pump-out Merc/Volvo prop Molded swim platform w/stainless steel telescopic 3-step boarding ladder Remote control spotlight Ski tow ring Stainless steel bow rail Stainless steel bow & stern eyes Stainless steel cleats Stainless steel courtesy lights Stainless steel control plate Stainless steel drink holders Stainless steel rubrail insert Stereo remote at helm Teak style snap-in carpet Tilt steering Transom shower Vented cabin windows (3)

Walk-thru curved full glass windshield

Optional Features

Color-coordinated Camper Canvas Package

Color-coordinated Canvas Package for Bimini top

Color-coordinated cockpit cover Decor Package

Dockside air conditioner/reverse heat Electric anchor windlass

Color Choices

White w/Jet Black Gelcoat

White w/Navy Blue Gelcoat White w/Pewter Gelcoat

Electric china head

Grey water system

High altitude prop

Radar arch

Flat screen TV w/DVD player

Starboard windshield wiper

Stern filler cushion & table

Engine Choices

5.0L MPI Bravo III MerCruiser (260) 5.0L MPI Bravo III EC MerCruiser (260) 350 Magnum MPI Bravo III V8-270 Volvo Penta (270) V8-270C Volvo Penta (270) V8-300 Volvo Penta (300) MerCruiser (300) 350 Magnum MPI Bravo III EC V8-300C Volvo Pentà (300) MerCruiser (300)

Performance

(Some engines not available in U.S.)

Engine:	V8-270 Volv	o Penta (270), Prop: 17 p	oitch	
	rpm	mph	gph .	range*
	2000	8	3.7	109
	3000	20	7.4	136
	4000	35	13.0	135
-	WOT	43-45	_	
Time to	olane: 5.2 sec	onds		
Accelerat	tion 0-20 MPI	H: 8.6 seconds		
Engine:	V8-300 Volv	o Penta (300), Props: F4		+4
•	rpm	mph	gph	range*

rom	mph	gph	range*
2000	9	4.4	: IŎĬ
3000	22	9.0	123
4000	34	12.3	137
5000	43	20.7	105
WOT	44	22.3	101
Time to plane: 6.0 sec	onds		
Acceleration 0-20 MPI			

Engine: 350 Magnum MPI Bravo III MerCruiser, Props: 221/2 pitch

_	rpm	mph	gph	range*	
	2000	8	4.7	92	
	3000	23	8.6	133	
	4000	35	12.7	138	
	5000	45	21.4	106	
	WOT	46-48	23,3	101	
				_	

Time to plane: 5.8 seconds Acceleration 0-20 MPH: 8.0 seconds

Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

> Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

LOA 28' 10" (8.79 m.) Beam 109" (2.77 m.) Total Height 101" (2.57 m.) Cockpit Height at Helm 30" (.76 m.)
Approx. boat & engine weight 6500 lbs. (2948 kg.) w/5.7 Gi DP Volvo

Draft Drive Unit Up 28" (.71 m.) Draft Drive Unit Down 41" (1.04 m.)

Deadrise 20° Fuel Capacity 84 gal. (318 L.) Bridge Clearance 83" (2.11 m.) Bridge Clearance w/Arch 98" (2.49 m.) Maximum Horsepower 380 hp (283 kw)

Standard Features

Instrument panel Includes: woodgrain accent trim panels w/grey main dash shroud, built-in footrest, stainless steel cup holder, speedometer, tachometer, trim, fuel, oil pressure, voltmeter, engine temperature, hour meter, depth sounder gauges; plus switches for bilge pump, forward & aft blower, navigation/anchor lights, panel back lights, courtesy lights, horn, 12V adaptor

Aft automatic bilge pump
Aft cabin w/overhead reading light AM/FM Sirius satellite-ready stereo w/4 stainless steel speaker covers

Battery charger Bow roller & bow rope locker
Color-coordinated Bimini top & boot Custom non-directional woodgrain

steering wheel Cockpit area includes: wet bar w/sink, refrigerator, water system, removable stern seat, portside lounge seat & high/ low dual helm seat

Compass Deck hatch w/screen Dual battery switch 18-gallon water tank Electric china head w/pump-out Electric horn Fiberglass cockpit floor w/built-in footrest

Galley Package: microwave oven, 12/110V refrigerator, coffee maker, electric stove, 110V dockside power, sink & water system

Hydraulic trim tabs & switch at helm MP3 remote jack at dash

Main cabin includes: hanging clothes locker, V-berth cushions w/table & filler cushions, cabin courtesy lights, woodtrimmed cabin bo w mirror w/speaker covers & hot water system
Manual bilge mid/forward

Merc/Volvo prop Molded swim platform w/stainless steel telescopic 3-step boarding ladder Remote control spotlight

Ski tow ring Stainless steel bow & stern eyes Stainless steel bow & stern rails Stainless steel control plate Stainless steel courtesy lights Stainless steel pull-up cleats Stainless steel rubrail insert Stainless steel starboard windshield wiper Stainless steel transom shower Stainless steel vented cabin windows (4) Stereo remote for dash Teak style snap-in carpet Tilt steering Walk-thru curved full glass windshield Walk-thru transom w/gate Walkaround deck

Optional Features

Color-coordinated Camper Canvas Package (offered with or without Radar Arch) Color-coordinated Canvas Package for Bimini top (offered without Radar Arch) Color-coordinated cockpit cover (offered with or without Radar Arch)

Decor Package Dockside air conditioner/reverse heat Electric anchor windlass Electronics Package for radar arch: C70 display, DSM 30 depth finder, 2KW radar, GPS Extended swim platform

Color Choices

White w/Jet Black Gelcoat White w/Navy Blue Gelcoat White w/Pewter Gelcoat

Engine Choices

350 Magnum MPI Bravo III MerCruiser (300) V8-300 Volvo Penta (300) V8-300C Volvo Penta (300) 350 Magnum MPI Bravo III EC V8-380C Volvo Penta (380) MerCruiser (300) 8.2 Bravo III EC MerCrusier (375)

(Some engines not available in U.S.)

Performance

Engine: V8-300 Volvo	Penta (300), Prop	s: F4 gph	range*
rpm	mph	3.8	178
2000	9	8.9	141
3000	16	12.7	185
4000	31 41	21.4	144
5000 WOT	40-42	23.1	136

Time to plane: 5.6 seconds Acceleration 0-20 MPH: 6.6 seconds

Engine: V8-380 Volvo Penta (380), Props: F4 range* mph rpm 119 6.4 10 2000 147 11.7 26 3000 164 17.4 38 4000 116 26.4 WOT

Time to plane: 5.3 seconds Acceleration 0-20 MPH: 6.2 seconds

Range: Mileage range calculated on designated RPM and MPH figures shown above, and based on 90 percent of boat's fuel capacity.

> Performance data is measured with two passengers, 3/4 to full tank of fuel, at altitudes of 0 to 1200 feet.

TRAILERS

GT 160, GTS 160, GTSF 160, GT 160 CB, GTS 160 CB Single Axle Trailer

	US	METRIC
Trailer length	19' 5"	5.918 m
Trailer lenght w/ Tongue Folded	17'.3"	5.258 m
Boat & trailer length w/ tongue	22' 6"	6.883 m
Boat & trailer lenght w/ Tongue Folded	20' 6"	6.248 m
Width	81.	2.438 m
Trailer Empty weight w/ spare	754 LBS	342 KG
Carrying Capacity	2196 LBS	996 KG
GVWR (Gross Vehical Weight Rating)	2950 LBS	1338 KG
GAWR (Gross Axle Weight Rating)	2950 LBS	1338 KG
Tire Size / Range (Standard)	ST 205/75D14 BIAS	ST 205/75DI4 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity each (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	2950 LBS	1338 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM 49 PATTERN
Wheel Type	SILVER	SILVER
lack Capacity	1,200 LBS	544 KG ·-
Winch	1400 LBS	635 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM

GT 180, GTS 180 Single Axle Axle Trailer

·	US	METRIC
Trailer length	20' 1"	6.121 M
Trailer lenght w/ Tongue Folded	17' 11"	5.461 M
Boat & trailer length w/ tongue	23' 3"	7.188 M
Boat & trailer lenght w/ Tongue Folded	18'	5.486 M
Width	8' 2"	2.489 M
Trailer Empty weight w/ spare	639 LBS	290 KG
Carrying Capacity	2861 LBS	1298 KG
GVWR (Gross Vehical Weight Rating)	3,500 LBS	1,588 KG
GAWR (Gross Axle Weight Rating)	3,500 LBS	1,588 KG
Tire Size / Range (Standard)	ST 205/75D14 BIAS	ST 205/75D14 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity each (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	3,500 LBS	1,588KG
Hub	5 LUG 4.5" PATTERN	5 LUG IICM PATTERN
Wheel Type	CHROME	CHROME
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG -
Ball Size	2"	5 CM
Ball Towing Height	22.5"	· 57 CM ·

GTSF 180, GT 185, GTS 185, GTSF 185 Single Axle Trailer

	US	METRIC
Trailer length	20' "	6.096 M
Trailer lenght w/ Tongue Folded	. 17' 11"	5.461 M
Boat & trailer length w/ tongue	23' 2"	7.188 M
Boat & trailer lenght w/ Tongue Folded	21' I" .	6.426 M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	861 LBS	390 KG .
Carrying Capacity	3539 LBS	1606 KG
GVWR (Gross Vehical Weight Rating)	4,400 LBS	1,996 KG
GAWR (Gross Axle Weight Rating)	4,400LBS	1,996 KG
Tire Size / Range (Standard)	ST 225/75D15 BIAS	ST 225/75D15 BIAS
Tire Pressure (standard)	65 PSI COLD	450 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Lug Nut Torque	90-120 FT/LBS	120.6 NM-162.8NM
Axle .	SINGLE	SINGLE
Axle Rating (Per Axle)	4400 LBS	1996 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM

GT 200, GTS 200, GTSF 200, GT 205, GTS 205, GTS 205 CB Single Axle Trailer

	US	METRIC
Trailer length	21' 9"	6.629 M
Trailer length	19' 7"	5-969 M
Boat & trailer length w/	25'	7.62 M
Boat & trailer lenght w/ Tongue Folded	22' 10"	6.96 M
Width	8' 6"	2.591 M
Trailer Empty weight	971 LBS	440 KG
Carrying Capacity	4029 LBS	1828 KG
GVWR (Gross Vehical Weight Rating)	5,000 LBS	2,268 KG
GAWR (Gross Axle Weight Rating)	5,000 LBS	2,268 KG
Tire Size / Range (Standard)	ST 225/75DI5 BIAS	ST 225/75DI5 BIAS
Tire Pressure (standard)	65 PSI COLD	450 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Lug Nut Torque	90-120 FT/LBS	120.6 NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	5,000 LBS	- 2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG
Ball Size	· 2" ·	5 CM
Ball Towing Height	- · · 24" -	- 61 CM ·

AND CHARLES

GT 200, GTS 200, GTSF 200, GT 205, GTS 205, GTSF 205, GTS 205 CB Tandem Axle Trailer

-	US	METRIC
Trailer length	21' 9"	6.629 M
Trailer variables	19' 7"	5-969 M
Boat & trailer length w/	25'	7.62 M
Boat & trailer lenght w/ Tongue Folded	22' 10"	6.96 M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	1155 LBS	524 KG
Carrying Capacity	5845 LBS	2651 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75D14 BIAS	ST 205/75D14 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity each (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG IICM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG
Ball Size	2"	.5 CM
Ball Towing Height	21"	53.3 CM

GT 225, GTS 225 Tandem Axle Trailer

	US	METRIC
TRAILER LENGTH	22' 8"	6.909M
Trailer lenght w/ Tongue Folded	20° 6"	6.248 M
Boat & trailer length w/tongue	25' 10"	7.874M
Boat & trailer length w/ Tongue Folded	23' 8"	7.214M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	1095 LBS	497 KG
Carrying Capacity	5905 LBS	2678 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75D14 BIAS	ST 205/75D14 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG IICM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	2,600 LBS	1179 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM
	- -	

TRAILERS=

MX 180 Single Axle Trailer

	US	METRIC
Trailer length	20' !"	6.121 M
Trailer lenght w/ Tongue Folded	17' 11"	5.461 M
Boat & trailer length w/ tongue	23' 2"	7.188 M
Boat & trailer lenght w/ Tongue Folded	21' 1"	6.426 M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	731 LBS	332 KG
Carrying Capacity	2769 LBS	1256 KG
GVWR (Gross Vehical Weight Rating)	3,500 LBS	1,588 KG
GAWR (Gross Axle Weight Rating)	3,500 LBS	1,588 KG
Tire Size / Range (Standard)	ST 205/75D14 BIAS	ST 205/75D14 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity each (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle . ·	SINGLE	SINGLE
Axle Rating (Per Axle)	3,500 LBS	1,588KG
Hub	5 LUG 4.5" PATTERN	5 LUG IICM PATTERN
Wheel Type	CHROME	CHROME
ack Capacity	1,200 LBS	544KG
Winch -	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	22.5"	57 CM

MX 185, MX 185 SF Single Axle Trailer

	ÙS	METRIC
Trailer length	20' I"	6.121 M
Trailer lenght w/ Tongue Folded	17' 11"	5.461 M
Boat & trailer length w/ tongue	23' 2"	7.188 M
Boat & trailer lenght w/ Tongue Folded	21' 1"	6.426 M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	846 LBS	⁴ 384 KG ·
Carrying Capacity	2196 LBS	996 LBS
GVWR (Gross Vehical Weight Rating)	4400 LBS	1996 KG
GAWR (Gross Axle Weight Rating)	4400LBS	1996 KG
Tire Size / Range (Standard)	ST 225/75D15 BIAS	ST 225/75DI5 BIAS
Tire Pressure (standard)	65 PSI COLD	450 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Lug Nut Torque	90-120 FT/LBS	120.6 NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	4400 LBS	1996 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM

MX 205 Single Axle Trailer

	US	METRIC
Trailer length	22' 7"	6.883 M
Trailer lenght w/ Tongue Folded	20' 5"	6.223 M
Boat & trailer length w/ tongue	25' 11"	7.899 M
Boat & trailer lenght w/ Tongue Folded	23' 10"	7.264 M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	925 LBS	420 KG
Carrying Capacity	4075 LBS	1848 KG :
GVWR (Gross Vehical Weight Rating)	5,000 LBS	2,268 KG
GAWR (Gross Axle Weight Rating)	5,000 LBS	2,268 KG
Tire Size / Range (Standard)	ST 225/75D15 BIAS	ST 225/75D15 BIAS
Tire Prèssure (standard)	65 PSI COLD	450 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Lug Nut Torque	90-120 FT/LBS	120.6 NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM

MX 205, MX 205 Ski/Fish Tandem Axle Trailer

	US	METRIC
Trailer length	22' 7"	6.883 M
Trailer lenght w/ Tongue Folded	20' 5"	6.223 M
Boat & trailer length w/ tongue	25' 11"	7.899 M `
Boat & trailer lenght w/ Tongue Folded	23' 10"	7.264 M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	1086 LBS	493 KG
Carrying Capacity	5914 LBS	2683 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75D14 BIAS	ST 205/75DI4 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity each (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM

GLS 195 Single Axle Trailer

	US	METRIC
	20' 10"	6.35 M
Trailer length	17' 10"	5.436 M
Trailer lenght w/ Tongue Folded	23' 11"	7.29 M
Boat & trailer length w/	23'11	6.629 M
Boat & trailer lenght w/ Tongue Folded		353.8 M
Width	8' 6"	422 KG
Trailer Empty weight	931 LBS	
w/ spare	4069 LBS	1846 KG
Carrying Capacity	5,000 LBS	2,268 KG
GVWR (Gross Vehical Weight Rating)		2,268 KG
GAWR (Gross Axle	5,000 LBS	ST 225/75D15 BIAS
Tire Size / Range (Standard)	ST 225/75D15 BIAS 65 PSI COLD	450 KPA COLD
Tire Pressure (standard)	2,540 LBS	1,152 KG
Tire Capacity (Standard)		120.6 NM-162.8NM
Lug Nut Torque	90-120 FT/LBS	SINGLE
	SINGLE	2,268 KG
Axle Axle Rating (Per Axle)	5,000 LBS	6 LUG 14 CM
Hub	6 LUG 5.5" PATTERN	PATTERN
1100	CHROME	
Wheel Type	1,200 LBS	544KG
lack Capacity	1,800 LBS	818 KG
Winch	1,800 LBS	5 CM
Ball Size	24"	61 CM
Ball Towing Height	<u> </u>	

GLS 215 Tandem Axle Trailer

	US	METRIC
	22' 7"	6.883M
Trailer length		6.223 M
Trailor lenght W/	20' 5"	
Tongue Folded	25' 8"	7.823 M
Boat & trailer length w/	20	7.163 M
tongue	23' 6"	7.105 1 1
Boat & trailer lenght w/ Tongue Folded		2.591 M
Width	8: 6"	- 520 KG
Trailer Empty weight	1146 LBS	
w/ spare	5854 LBS	2655 KG
Carrying Capacity		3,175 KG
CVVVR (Gross Vehical	7,000 LBS	
Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle		ST 205/75D14 BIAS
Weight Rating)	ST 205/75D14 BIAS	\$1 203/735.1.
Tire Size / Range (Standard)		350 KPA COLD
Tire Pressure	50 PSI COLD	
(standard)	1,760 LBS	798 KG
Tire Capacity	1,700 ==	120.6NM-162.8NM
(Standard)	90-120 FT/LBS	
Lug Nut Torque	TANDEM	TANDEM
Axle	3,500 LBS	1,588 KG
Axle Rating (Per Axle)	5 LUG 4.5"	5 LUG HCM PATTERN
Hub	PATTERN	TAI Tail
Time	CHROME	544KG
Wheel Type	1,200 LBS	818 KG
Jack Capacity	1,800 LBS	5 CM
Winch	2"	
Ball Size	21"	53.3 CM
Ball Towing Height		

TRAILERS

DS 200 & DS 205 Tandem Axle Trailer

US	METRIC
21' 11"	6.68M
19' 9"	6.02 M
25'	7.62M
22' 10"	6.96M
8' 6"	2.591 M
1086 LBS	493 KG
5914 LBS	2682 KG
7,000 LBS	3,175 KG
7,000 LBS	3,175 KG
ST 205/75D14 BIAS	ST 205/75D14 BIAS
50 PSI COLD	350 KPA COLD
1,760 LBS	798 KG
90-120 FT/LBS	120.6NM-162.8NM
TANDEM	TANDEM
3,500 LBS	1,588 KG
5 LUG 4.5" PATTERN	5 LUG IICM PATTERN
CHROME	
1,200 LBS	544KG
1,800 LBS	818 KG
2 "	5 CM
21"	53.3 CM
	21' 11" 19' 9" 25' 22' 10" 8' 6" 1086 LBS 5914 LBS 7,000 LBS 7,000 LBS ST 205/75D14 BIAS 50 PSI COLD 1,760 LBS 7ANDEM 3,500 LBS 5 LUG 4.5" PATTERN CHROME 1,200 LBS 1,800 LBS 2"

DS 215 Tandem Axle Trailer

	US	METRIC
Trailer length	23' 6"	7.163M
Trailer lenght w/ Tongue Folded	21' 4"	6.502 M
Boat & trailer length w/ tongue	26 ^t 7"	8.IM
Boat & trailer length w/ Tongue Folded	24' 5"	7.442M
Width	8' 6"	2.591 M
Trailer Empty weight w/ spare	1163 LBS	528 KG
Carrying Capacity	5837 LBS	2647 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75D14	ST 205/75DI4 BIAS
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG IICM PATTERN
Wheel Type	CHROME	
Jack Capacity	1,200 LBS	544KG
Winch	2,600 LBS	1179 KG
Ball Size	2 ⁿ	5 CM
Ball Towing Height	21"	53.3 CM

SLISTRON

925 Frisbie Street, Cadillac, MI 49601 Phone 231-775-1351 • www.glastron.com

and a

Part # 090-3069-13